



Cap.	Weighting Surface D	W	H	Overall W	L	Standards	Mr. Model	Item No.
Mechanical Scales								
1 lb, 500 g	3 in	4 1/4 in	3 1/2 in	3 3/4 in	3 1/4 in	—	37204014T	3NZN2
900 g, 32 oz	6 in	5 1/4 in	7 1/4 in	7 1/2 in	7 in	NSF	TS32F	3NZH2
22 lb, 10 kg	1 in	9 3/4 in	6 3/4 in	9 3/4 in	6 3/4 in	—	38804016T	3ZN6
11 kg, 25 lb	6 in	5 1/4 in	7 1/4 in	7 1/2 in	7 in	NSF	TS25KL	3NZH3
50 lb	5 1/4 in	6 in	7 1/4 in	7 1/2 in	7 in	NSF	TS50	3NZH4
50 lb	8 3/4 in	8 3/4 in	10 3/4 in	8 3/4 in	10 1/2 in	NSF	THD50	14F322
Digital Scales								
2 lb	5 1/2 in	5 1/2 in	1 1/2 in	6 in	6 1/4 in	NSF	TE Series	3NZG9
8 lb, 4 kg	6 in	6 in	2 in	6 in	7 1/2 in	—	3800N	3ZN5
10 lb, 5 kg	5 1/2 in	5 1/2 in	2 3/4 in	7 3/4 in	6 3/4 in	NSF	TE Series	3NZH1
22 lb	7 1/2 in	7 1/2 in	2 3/4 in	8 1/2 in	12 1/4 in	NSF	TE22FT	45RM74

Scales TAYLOR

Mechanical—Rotating dial allows container weight deduction and ingredient measuring. Removable stainless steel platform and shatter-proof lens protect dial, except plastic model 3NZN2. 3NZN2 includes dishwasher safe bowl and lid and weighs in 1/4 oz. and 5g increments.

Digital—LCD readout with tare and auto/off features. Overload and low battery indicators. 3NZG9 and 3NZH1 include AC adapter or operates on one 9V battery. All others run on batteries only.



Food Thermometers

Description	Temp. Range (F)	Accuracy	Includes	Dial Size	Stem Length	NSF Certified	Mr. Model	Item No.
Analog								
Candy Thermometer	100° to 380°F	±5°F	Pan Clip	2 in	6 in	Yes	3505	35HV40
Chef Thermometer - Features Field Recalibratable	100° to 400°F	±5°F	Pan Clip	—	—	Yes	3510	35HV43
Deep Fry Thermometer	0° to 220°F	±2°F	Pocket Sheath	1 in	5 in	Yes	3512	35HV44
Meat Thermometer - Features USDA Guidelines	50° to 550°F	±10°F	Pan Clip	2 in	12 in	Yes	3522	35HV50
Mechanical Food Service Thermometer Food Safety	120° to 190°F	±2°F	—	2 in	4 in	Yes	3504	35HV39
Mechanical Food Service Thermometer Food Safety	0° to 220°F	±1%	Recall Tool	1 in	5 in	Yes	6072N	3NZR8
Mechanical Food Service Thermometer HACCP Food Safety	0° to 220°F	±1°C, ±2°F	Safe T Guard Sleeve	1 3/4 in	5 in	Yes	8018N	14F307
Pocket Test Chef Thermometer	50° to 550°F	±5°F	Pocket Sheath	1 in	5 in	Yes	3517	35HV47
LCD								
Digital Chef Thermometer	-40° to 302°F	±3.5°F	Pocket Sheath	—	5 in	Yes	3516	35HV46
	-40° to 176°F	±2°F	—	2 3/4 in	—	—	1445	53DL84
	-40° to 450°F	±1°C, ±2°F	LR44 Battery, Storage Sleeve Printed with Convenient Cooking Temperature Chart	—	5 in	—	9836	14F308
Digital Food Service Thermometer	-40° to 450°F	±1°F	(2) Lithium Batteries	—	3 3/4 in	—	9835	23WF59
	-40° to 450°F	±1.8°F, ±1°C	Lithium Battery	—	3 3/4 in	—	9877FDA	23WF61
	-40° to 450°F	—	1.5V Battery	1 1/2 in	4 in	Yes	9842FDA	3NZT1
	-40° to 450°F	—	1.5V Battery	1 1/2 in	3 1/2 in	Yes	9847FDA	3NZT2
	-40° to 500°F	—	CR2032 Battery	2 in	4 1/2 in	Yes	9878E	3NZT4
Digital Food Service Thermometer Candy, Deep Fryer, Jelly	-40° to 450°F	±1°C, ±2°F	Li-Ion Battery	—	9 in	—	983915	14F310
Digital Food Service Thermometer - Features Hold Function	-40° to 572°F	±2°F	(2) AAA Batteries	—	4 in	Yes	9867FDA	14F309
Digital Food Service Thermometer HACCP Food Safety	-40° to 450°F	±2°F	Lithium Battery	1 1/2 in	3 in	Yes	9848FDA	3NZT3
	-40° to 450°F	±1 Over HACCP Range	9V Battery	—	—	Yes	9405	14F318
Digital Food Service Thermometer with Probe	32° to 392°F	—	AAA Battery, Instructions, Probe	—	—	—	1470	2BD5
Digital Thermometer	32° to 392°F	±5°F	(2) AAA Batteries	—	—	Yes	3518N	35HV48
Digital Thermometer Coded Purple for Allergy	-40° to 302°F	±2°C	Pocket Sheath	—	5 in	Yes	9840PRN	35HV28
Pocket Test Thermometer	-40° to 450°F	±4°F	LR44 Lithium Battery, Pocket Sheath	—	4 in	Yes	3519	35HV49
Waterproof Thermometer	-40° to 500°F	±1°F	Pocket Sheath	—	5 in	Yes	9878EPR	35HV29



Appliance Thermometers

Description	Temp. Range (F)	Accuracy	Includes	Dial Size	NSF Certified	Mr. Model	Item No.
Analog							
Liquid Filled	100° to 600°F	±10°F	—	—	—	5921N	14F306
Liquid Filled Food Service Thermometer	-20° to 60°F	±1°F	—	—	NSF	5927	23WF60
	-20° to 80°F	±2°C, ±2°F	—	—	NSF	3509	14F312
Mechanical Food Service Thermometer	100° to 700°F	±10°C, ±10°F	Stainless Steel Coil for Lifting Thermometer with Spatula	2 in	—	6021	14F311
Mechanical Food Service Thermometer HACCP Food Safety	-30° to 70°F	±2°C, ±2°F	—	2 3/4 in	NSF	5981N	3NZR5
Oven Thermometer - Features Hanger	100° to 600°F	±5°F	—	2 in	NSF	3506	35HV41
Refrigerator/Freezer Thermometer	-20° to 80°F	±10°F (-20°F), ±2°F (32° to 40°F), ±3°F (0° to 32°F), ±4°F (-19° to 0°F), ±5°F (40° to 80°F)	—	3 in	NSF	5924	44C64
	-20° to 86°F	±2°F	—	—	NSF	3503	35HV38
LCD							
Digital Food Service Thermometer	-4° to 140°F	±0.1°C, ±0.1°F	Li-Ion Battery	—	—	1443	14F305
	-67° to 428°	±0.1%	(1) Batteries, Case	—	No	9527	35HV21
Infrared Thermometer	-49° to 752°F	±2°F/±1°C	(2) AAA Batteries, Nylon Case	—	—	9523	14F320

TAYLOR