


CONTINUED

Ceiling Tiles



Tile Size	Series	Mfr. Model	Texture	Sound Absorption (NRC)*	Sound Blocking (CAC)*	Fire Performance	Light Reflectance	Recycled Content Range—Standard: 49% or Less High: 50% or More	Item No.	Pkg. Qty.
General Purpose Tiles (Cont.)										
Angled Tegular Edge For 1/2 in Grid										
24 in x 24 in	Cirrus	577B	Medium	0.35	35	Class A	86 %	High	32WM95	12
	Cortega	2776B	Medium	0.55	30	Class A	81 %	High	32WM10	10
24 in x 48 in	Dune	2722A	Fine	0.5	35	Class A	81 %	Standard	32WM08	10
	Fine Fissured	1766C	Medium	0.55	30	Class A	82 %	High	32WL68	10
Beveled Tegular Edge For 1/2 in Grid										
24 in x 24 in	Georgian	1752B	Medium	0.55	35	Class A	86 %	High	32WL56	16
	Tundra	303A	Medium	0.5	33	Class A	86 %	Standard	32WM24	12
24 in x 48 in	Cirrus	513A	Medium	0.65	35	Class A	85 %	High	32WM80	6
Beveled Tegular Edge For 1/2 in Grid										
24 in x 24 in	Cirrus	590B	Medium	0.65	35	Class A	85 %	High	32WN09	12
	Cortega	2195	Medium	0.55	35	Class A	80 %	Standard	132997	16
	Dune	1775	Fine	0.5	35	Class A	81 %	High	6YLP8	16
	Fine Fissured	1734	Medium	0.55	35	Class A	85 %	High	6YLR4	16
	Georgian	1753B	Medium	0.55	35	Class A	86 %	High	32WL57	16
24 in x 48 in	Tundra	304A	Medium	0.5	33	Class A	86 %	Standard	22XJ43	12
	Cirrus	510A	Medium	0.65	35	Class A	85 %	High	32WM77	6
	Cirrus	511A	Medium	0.65	35	Class A	85 %	High	32WM78	6
	Dune	1777A	Fine	0.5	35	Class A	81 %	High	48WC09	8
Flush Tegular Edge For 1/2 in Grid										
24 in x 24 in	Ledges	8013A	Smooth	Not Rated	35	Class A	80 %	Standard	447J69	8
	Tincraft	8009A	Smooth	Not Rated	35	Class A	78 %	High	32WN37	8
Wrapped Tegular Edge For 1/2 in Grid										
24 in x 24 in	Graphis	8005	Fine	Not Rated	35	Class A	90 %	High	32WN32	12
Concealed Edge For 1/2 in Grid										
12 in x 12 in	Fine Fissured	741	Medium	0.55	Not Rated	Class A	85 %	High	32WN25	40
	Fine Fissured	746	Medium	0.55	35	Class A	85 %	High	36N476	40
High Sound-Absorption & Blocking Tiles for Privacy										
Square Lay-In Edge For 1/2 in Grid										
24 in x 24 in	Cirrus	574B	Medium	0.7	35	Class A	85 %	High	6YLR6	12
	Fine Fissured	1713	Medium	0.7	35	Class A	85 %	Standard	32WN50	12
	Optima Health Zone	3114EPB	Fine	0.95	190	Class A	86 %	High	468A96	12
	Ultima	1910A	Fine	0.75	35	Class A	88 %	High	132995	12
24 in x 48 in	Cirrus	533B	Medium	0.7	35	Class A	85 %	High	32WM82	6
	Fine Fissured	1714	Medium	0.7	40	Class A	85 %	Standard	32WN51	8
	Ultima	1913A	Fine	0.75	35	Class A	88 %	High	132996	6
Square Tegular Edge For 1/2 in Grid										
24 in x 24 in	Optima Tegular	3250E	Fine	0.95	190	Class A	88 %	High	468A97	12
Square Tegular Edge For 1/2 in Grid										
24 in x 24 in	Optima Tegular	3251E	Fine	0.95	190	Class A	88 %	High	468A98	12
	Optima Tegular	3355E	Smooth	0.9	200	Class A	88 %	High	468C01	12
48 in x 48 in	Optima	3256B	Fine	0.95	30	Class A	88 %	High	48WC10	6
Angled Tegular Edge For 1/2 in Grid										
24 in x 24 in	Cirrus	534C	Medium	0.7	38	Class A	86 %	High	32WM83	10
	Cirrus	556E	Medium	0.75	35	Class A	85 %	High	32WM89	10
	Cirrus	584BN	Medium	0.7	35	Class A	86 %	High	5UTN5	12
	Fine Fissured	1717	Medium	0.7	40	Class A	82 %	High	32WN52	12
	Fine Fissured	1820A	Medium	0.7	35	Fire Resistive	85 %	High	132992	12
24 in x 48 in	Cirrus	535A	Medium	0.7	35	Class A	86 %	High	32WM84	6
Beveled Tegular Edge For 1/2 in Grid										
24 in x 24 in	Ultima	1911A	Fine	0.8	35	Class A	0.9	High	5NGK1	12
	Ultima	1914A	Fine	0.75	35	Class A	88 %	High	32WL86	6
24 in x 48 in	Ultima	1944A	Smooth	0.8	35	Class A	87 %	High	32WL99	6
Beveled Tegular Edge For 1/2 in Grid										
24 in x 24 in	Cirrus	538C	Medium	0.7	35	Class A	86 %	High	32WM86	10
	Cirrus	558E	Medium	0.75	35	Class A	85 %	High	32WM91	10
	Cirrus	589BN	Medium	0.7	35	Class A	86 %	High	5NGK4	12
	Ultima	1912A	Fine	0.8	35	Class A	88 %	High	5UTN6	12
	Ultima	1912AHRC	Fine	0.75	35	Class A	88 %	High	32WL85	12
	Ultima	1942A	Smooth	0.8	35	Class A	87 %	High	32WL97	10
24 in x 48 in	Cirrus	539A	Medium	0.7	38	Class A	86 %	High	32WM87	6
	Ultima	1915A	Fine	0.75	35	Class A	88 %	High	32WL87	6
Concealed Edge For 1/2 in Grid										
24 in x 24 in	Ultima	1920A	Fine	0.7	33	Class A	88 %	High	32WL92	12
Sag- & Mold-Resistant Tiles for High Humidity										
Square Lay-In Edge For 1/2 in Grid										
24 in x 24 in	Armaturf	861	Medium	0.5	33	Class A	87 %	Standard	32WN43	16
	Ceramaguard	607A	Medium	0.55	38	Fire Resistive	79 %	Standard	32WN10	12
	Fine Fissured	1810	Medium	0.7	40	Fire Resistive	85 %	High	31LC01	12
	Kitchen Zone*	673	Smooth	Not Rated	33	Class A	89 %	Standard	20CA77	16
	Armaturf	860	Medium	0.5	0	Class A	87 %	Standard	32WN42	8
24 in x 48 in	Ceramaguard	605C	Medium	Not Rated	40	Fire Resistive	86 %	Standard	132998	6
	Ceramaguard	608A	Medium	0.55	40	Fire Resistive	79 %	Standard	32WN11	6
	Fine Fissured	1811	Medium	0.7	40	Fire Resistive	85 %	High	31LC02	8
	Georgian	793	Medium	Not Rated	33	Class A	86 %	High	5NGJ6	12
	Kitchen Zone*	672	Smooth	Not Rated	33	Class A	89 %	Standard	20CA76	12
ISO-Rated Tiles for Cleanrooms										
Square Lay-In Edge For 1/2 in Grid										
24 in x 24 in	Clean Room	868B	Smooth	0.55	40	Fire Resistive	0.8	High	5NGK2	12
	Clean Room	1715B	Smooth	0.55	35	Class A	79 %	High	6YLR5	12
	Clean Room	1720B	Smooth	0.55	35	Class A	79 %	High	32WN54	12
	Clean Room	870B	Smooth	0.55	40	Fire Resistive	80 %	High	5UTN4	8
24 in x 48 in	Clean Room	871B	Smooth	0.55	35	Fire Resistive	78 %	High	32WN45	8
	Clean Room	1716B	Smooth	0.55	35	Class A	79 %	High	32WN65	8
	Clean Room	1721B	Smooth	0.55	35	Class A	79 %	High	36N475	8
Sealed System Tiles for Isolation Rooms										
Square Lay-In Edge For 1/2 in Grid										
24 in x 24 in	Calla	2820A	Smooth	0.85	35	Class A	86 %	Standard	430U24	10
	Ultima	1935A	Fine	0.7	38	Class A	86 %	High	48WC07	12
24 in x 48 in	Ultima	1938A	Fine	0.7	38	Class A	86 %	High	48WC08	6
Square Tegular Edge For 1/2 in Grid										
24 in x 24 in		1353N	Smooth	0.8	40	Class A	85 %	High	785EM8	10
Beveled Tegular Edge For 1/2 in Grid										
24 in x 24 in		1352N	Smooth	0.7	40	Class A	86 %	High	785EN1	12
Beveled Tegular Edge For 1/2 in Grid										
24 in x 24 in		1351N	Smooth	0.7	40	Class A	86 %	High	785EN0	12


* **NRC**—Measures the ability of a ceiling tile to absorb sound within an enclosed space. The industry standard for NRC (Noise Reduction Coefficient) ranges from zero (low performance) to 1 (high performance, completely absorptive). **CAC**—Measures the ability of a ceiling tile to reduce or block sound between rooms or adjacent closed spaces that share a plenum. The higher the CAC (Ceiling Attenuation Class) rating, the better the performance.



General Purpose




High Sound-Absorption & Blocking for Privacy



Sag- & Mold-Resistant for High Humidity



ISO-Rated for Cleanrooms



Sealed System for Isolation Rooms