



Airpot and Infusion Coffee Brewers

- NSF Certified (except leaver airpots)
- For coffee, see page 1440

Stainless steel units brew directly into airpots (sold separately). Newco 48FP52 is a fresh water system and only boils the required amount of water that is poured into the brewer,

for a fresher cup of coffee. 48FP57 features a dump valve system and a water level detection system and a tank on/off switch. Bunn airpot brewers include hot water faucet and cold brew lockout capability. SmartWAVE brewers are low-profile and feature an energy-saver mode.

Description	Plumbing Req.	Cap.	Brewing Cap.	H (in.)	W (in.)	D (in.)	Brand	Mfr. Model	Item No.
Airpot Brewers									
Pourover	No	4 gal	0.5 gph	23 29/32	8 1/2	17 45/64	Newco Coffee	AK-AP	48FP52
Automatic Electric	Yes	4 gal	0.5 gph	23 29/32	8 1/2	16 13/32	Newco Coffee	FC-AP	48FP57
CWTF Airpot, Single	Yes	102 oz	3.8 gph	23 3/8	9	18 1/2	Bunn	CWTF Airpot	6DHA5
CW Aps, Pourover	No	102 oz	3.9 gph	23 3/8	9	18 1/2	Bunn	CW Aps	6DHD4
Axiom APS, Single Head	Yes	102 oz	4.2 gph	23 3/8	9	18 1/2	Bunn	Axiom APS	6DHA1
Axiom APS, Dual Head	Yes	102 oz	15 gph	23 1/2	16	17 3/4	Bunn	Axiom Twin APS	6DHA2
SmartWave Silver, Single Low Profile	Yes	102 oz	3.9 gph	16 1/2	8 3/4	17	Bunn	WAVE15S-APS	6DHA3
SmartWave, Single Low Profile	Yes	102 oz	3.9 gph	16 1/2	8 3/4	17	Bunn	WAVE15-APS	6DHA4
Leaver Airpots									
Glass Lined	—	2.2 L	—	16	6 1/2	6 1/2	Crestware	APL22G	19H509
Stainless Steel Lined	—	2.2 L	—	15	6 1/2	6 1/2	Crestware	APL22S	19H510
Glass Lined	—	2.5 L	—	18	6 1/2	6 1/2	Crestware	APL25G	19H512
Stainless Steel Lined	—	2.5 L	—	15	6 1/2	6 1/2	Crestware	APL25S	19H513
Glass Lined	—	3 L	—	17	6 1/2	6 1/2	Crestware	APL30G	19H514
Stainless Steel Lined	—	3 L	—	16 1/4	6 1/2	6 1/2	Crestware	APL30S	19H515
Accessories									
Replacement Lid For Use With Crestware Airpots							Crestware		19H516
Insulated Server - 77 oz.							Newco Coffee		48FP60
Airpot Serving Rack							Newco Coffee		48FP61



48FP52

Shown w/Airpots,
Sold Separately



19H509



6DHA1



Decanter-Style Coffee Brewers

- NSF Certified
- UL Listed
- 120V, 15A
- Stainless steel
- Carafes not included
- For coffee, see page 1440

Automatic Electric Coffee Brewers—Use dump valve solenoid operation for accurate brew volumes and brew temperatures. Standard ready light, pulse water inlet, gravity fed water faucet, and auto-arm with a smart multi-server base design. Plumbing required.

Pourover Coffee Brewers—Have a traditional displacement hot water tank system, a ready light for optimum brewing temperature, and a master On/Off power switch.

Warming Stations	Cap.	Brewing Cap.	Watts	Plumbing Req.	H (in.)	W (in.)	D (in.)	Mfr. Model	Brand	Item No.
Automatic Electric Coffee Brewers										
3	4 gal	0.5 gph	120V, 15 A, 1500 W	Yes	16 29⁄₃₂	15 39⁄₆₄	17 13⁄₃₂	FC-3	Newco Coffee	48FP56
3	4 gal	0.5 gph	120V, 15 A, 1500 W	Yes	18 1⁄₂	8 1⁄₂	21	FCS-3	Newco Coffee	48FP55
3	64 oz	3.9 gph	120V, 15 A, 1500 W	Yes	17	16 1⁄₂	17 3⁄₄	CWTF 15 - 3L	Bunn	6DHC0
3	64 oz	3.9 gph	120V, 15 A, 1500 W	Yes	19	8 1⁄₂	17 3⁄₄	CWTF 15 - 3	Bunn	6DHA9
Pourover Coffee Brewers										
2	4 gal	0.5 gph	120V, 15 A, 1500 W	No	18 1⁄₂	8 1⁄₂	16 13⁄₃₂	AK-2	Newco Coffee	48FP50
2	4 gal	0.5 gph	120V, 15 A, 1500 W	No	18 1⁄₂	8 1⁄₂	16 13⁄₃₂	AK-2AS	Newco Coffee	48FP53
2	64 oz	3.9 gph	120V, 15 A, 1575 W	No	26 9⁄₁₆	15 1⁄₈	8	VPR	Bunn	6DHD1
3	4 gal	0.5 gph	120V, 15 A, 1500 W	No	16 29⁄₃₂	15 1⁄₂	16 13⁄₃₂	AK-3	Newco Coffee	48FP51
3	4 gal	0.5 gph	120V, 15 A, 1500 W	No	16 29⁄₃₂	15 1⁄₂	16 13⁄₃₂	AK-3AS	Newco Coffee	48FP54
3	64 oz	3.9 gph	120V, 15 A, 1660 W	No	19 3⁄₄	23 1⁄₂	8	VPS	Bunn	6DHD2
Description					H	W (in.)	Dia.	Brand		Item No.
2 Station Warmer, 120V, 200W					3 1⁄₂ in	14 in	—	Newco Coffee		48FP65
Replacement Decanters										
64-oz - Black					7 in7	6 1⁄₄	6 3⁄₄ in	Crestware		19H527
64-oz - Orange					7 in7	6 1⁄₄	6 3⁄₄ in	Crestware		19H528

*Automatic warmer shutdown.



48FP50



48FP51



19H528



Coffee Urns

Automatic Drip—BUNN urns feature large water tank and half-batch option. Draw off hot water during brewing cycle without affecting coffee quality.

Percolating—Coffee Pro includes a permanent filter basket and locking safety lid with carrying handles.

Insulated—Cambro versatile servers can be used for both hot and cold beverages. Feature dripproof recessed spigot. Servers can be stacked for easy storage.

Description	Material	Cap.	Brewing Cap.	W x H x D	Brand	Mfr. Model	Item No.
Automatic Drip							
Twin	Stainless Steel	20 gal	16.3 gph	34 1/2 in x 32 1/2 in x 21 in	Bunn	U3	6DHC2
Percolating							
Single	Stainless Steel	—	50 °C	12" W X 12" H	Coffee Pro	CP50	51VN86
Description	Material	Cap.	W x H x D	Color	Brand	Mfr. Model	Item No.
Insulated							
Single	Polyethylene	2 1/2 gal.	16 1/2" x 9" x 18 3/4"	Black	Cambro	EA250LCD	4UJL5
Single	Polyethylene	2 1/2 gal.	16 1/2" x 9" x 18 3/4"	Dark Brown	Cambro	EA250LCD	4UJL6
Single	Polyethylene	4 3/4 gal.	16 1/2" x 9" x 24 1/4"	Black	Cambro	EA500LCD	4UJL7
Single	Polyethylene	4 3/4 gal.	16 1/2" x 9" x 24 1/4"	Dark Brown	Cambro	EA500LCD	4UJL8



6DHC2



51VN86



4UJL7