## **FOOD SERVICE & HOSPITALITY Storage Bins, Holding & Transport Racks**



2ERY2









2ERY4

**4UEY1** 

# Commercial Products **Bulk Storage Bins**

Stores dry bulk ingredients.

#### **MOBILE BULK STORAGE BINS**

Sloped, clear plastic hinged lid. 3" casters (2 rigid, 2 swivel).

#### **BULK STORAGE BINS**

Allow 1-handed access to contents while bins are stacked. Feature first-in, first-out barrier for proper rotation of ingredients. Clear windows and ingredient labels. Include scoop.

#### **MOBILE INGREDIENT BINS**

Clear sliding lid reduces handling and provides quick content identification. Designed to fit under work tables. All bins have a slant top, except 4UJT2 has a flap top. No liners are needed. 3" casters with 2-front swivel, and 2-fixed. Scoop not included.

Con (col.)	Overall	Overall	Overall	ltem No.				
	Length (in.)		H (in.)	NU.				
Mobile Bulk Storage Bins w/32 oz Scoop - RUBBERMAID COMMERCIAL PRODUCTS								
84 gt	29 1/4 in	13 1/8 in	28 in	5M684				
	29 1/4 in		28 in	5M685				
124 gt	29 1/4 in	18 in	28 in	5M686				
<b>Bulk Storag</b>	e Bins w/2-cu	p Clear Scoo	ip -					
RUBBERMAI	D COMMERCI	AL PRODUCT	Ś					
10.48 qt	15 in	11 ¾ in	8 ½ in	4UEX9				
21.63 qt	23 ½ in	11 ½ in	16 ¾ in	2ERY4				
42.8 qt	23 1/2 in	19 1⁄8 in	16 ¾ in	2ERY5				
	edient Bins w							
84 qt	29 1⁄2 in	13 in	28 in	4UJR8				
106.8 qt	30 1/8 in	13 in	28 ½ in	4UJT2				
108 qt	29 5⁄8 in	16 5⁄16 in	28 in	4UJR9				
148 qt	29 ½ in	21 ½ in	28 in	4UJT1				
	Item							
	Description							
Accessories - Rubbermaid Commercial Products								
	oz. Scoop for			2ERX8 2ERX9				
	Lid with 32-oz. Scoop for 5M685							
	Lid with 32-oz. Scoop for 5M686							
Lid with 2 Cup Scoop for 4UEY4 4UEY1								
Lid with 4 C	4UEY3							

2MGC8



CAMBRO Camshelving **Polypropylene** Shelving with **Steel Core** 

**Polypropylene Vented Shelving** Units-For use in walk-in freezers, refrigerators, or wet/dry environments. Shelf plates are dishwasher safe. Shelves adjust in 4" increments. Include 2 post kits, 8 traverses, and shelf plates.

Mobile Shelving Unit Stands— Include 4 posts, post connectors,

traverses, vented shelf plates, and casters

#### **Center Support for Shelving**

Stands—Weight bearing capacities up to 1000 lb. on bottom shelf units 54" or longer.

### Lockable Security Cage for

Shelving Stands—Fit on standard Camshelving units 24" wide and 48" longer.

Н	W	D	ltem No.
<b>Polypropylene Venter</b>	d Shelving Units		
		18"	2MGC8
		18"	22NV17
	36"	21"	2MGD2
		24"	2MGD5
		24"	22NV20
		21"	2MGD3
		24"	2MGD6
72"	48"	18"	2MGC9
		18"	22NV18
		24"	22NV21
		21"	2MGD4
		24"	2MGD7
	60"	18"	2MGD1
		18"	22NV19
		24"	22NV22
<b>Mobile Shelving Unit</b>	Stands		
751	401	18"	4UHX4
75"	48" —	24"	4UHX3
<b>Center Support for Sh</b>	elving Stands		
		18"	4UHX5
6"		21"	4UHX6
		24"	4UHX7
Lockable Security Ca	ges for Shelving Stands		
18"	42 1/2"	25 1⁄4"	4UHX8
65"	501	24"	22NV16
68"	- 50"	24"	22NV15
1452 <b>GR</b>	<b>AINGER</b> ®	Fin	nd even



н	w	D	PREMIUM Item No.
Mobile \$ - 800 lb.			its
	36"	18"	12F885
	36"	21"	12F893

70⁼ ·	36"	21"	12F893
	36"	24"	12F902
70	48"	18"	12F889
	48"	21"	12F897
	48"	24"	12F906
78" -	36"	18"	12F887
	36"	21"	12F895
	36"	24"	12F904
	48"	18"	12F891
	48"	21"	12F899
	48"	24"	12F908

## CAMBRO

# **Camshelving Elements Series**

Replacement Scoop, 32 Oz., Pkg. of 6

- Composite material
- Brushed graphite color

- Shelf plates are easily removed and dishwasher safe Resistant to moisture: won't rust or corrode. Withstand temperatures from -36° to 190°F.

Mobile Starter Shelf Units-Include 4 mobile posts, post connectors and wedges installed, 8 mobile traverses, 32 dovetails, and shelf plates for 4 shelves.

Stationary Starter Shelf Units-Include 2 post kits, 8 traverses. 32 dovetails, and shelf plates to build 1 entire unit.

Stationary Add-On Shelf Units-Include 1 post kit, 8 traverses, 32 dovetails, and shelf plates to attach to adjoining unit.

			STARTER		ADD	-ON	
			Item	Shelf	Item	Shelf	
Н	W	D	No.	Cap.	No.	Cap.	
Stationary Shelf Units							
72"	36"	18"	12F910	800 lb.	—		
72"	48"	18"	12F911	800 lb.	12F919	800 lb.	
72"	60"	18"	12F912	600 lb.	12F920	600 lb.	
72"	36"	21"	12F913	800 lb.	_		
72"	48"	21"	12F914	800 lb.	12F921	800 lb.	
72"	60"	21"	12F915	600 lb.	12F922	600 lb.	
72"	36"	24"	12F916	800 lb.	_		
72"	48"	24"	12F917	800 lb.	12F923	800 lb.	
72"	60"	24"	12F918	600 lb.	12F924	800 lb.	





Feature easy snap-on/snap-off installation with low-profile, polypropylene mounting hardware. Stay securely in place for all-day use. Cost-effective strips are energy efficient.

Temp. Range	Strip Type	Strip Width	Strip Length	No. of Strips	Mfr. Model	ltem No.
Strip Door						
-20°to 140°F	Reinforced, Smooth	6 in	7 ft 3 in	10	999-00209	1VKB7
-20°to 140°F	Reinforced, Smooth	8 in	7 ft 3 in	7	999-00211	1VKB9
Replacement Strips						
-20° to 140°F	Reinforced, Smooth	6 in	7 ft 3 in	5	999-00663	407K52
-20° to 140°F	Reinforced, Smooth	8 in	7 ft 3 in	4	999-00015	3TB16
Strip Door Hardware						
3 ft. 4" L	_	_	_	_	999-10106	407K51

GRAINGER®

Find even **MORE** on **Grainger.com**®

1-800-GRAINGER (472-4643)