







Pressure Washer Chemicals



Designed for use in all types of pressure washers.

Description	Size	Brand	No.
Crankcase Oil, SAE Grade 30	16 oz.	_	1MDJ8
Deck and Fence Cleaner Concentrate	1 gal	Simple Green	3ANW4
House and Siding Cleaner Concentrate	1 gal	Simple Green	3ANW5
Concrete and Driveway Cleaner Concentrate	1 gal	Simple Green	3ANW6
Heavy-Duty Cleaner and Degreaser Concentrate	1 gal	Simple Green	3ANW7

Water **Brooms**



Rust-resistant brooms provide a wide cleaning path for fast and easy cleaning. Units hook up to pressure washer spray gun lance with a standard 1/4" quick disconnect plug.

		wax.	item
Description	W	Pressure	No.
3-Nozzle	12 in	4,000 psi	1MDK4
4-Nozzle	16 in	4,000 psi	1MDK5







Pressure Wash Hand-Crank Hose Reels

Hose reels are equipped with a high-pressure water swivel that handles a broad range of pressures, temperatures, and chemicals. Steel reels withstand corrosion, hold tangle-free hose, and mount on the floor, wall, bench, or in trucks. They are used with water or chemical hoses for equipment cleaning, pressure washing, and in agricultural spraying.

	Overall Dim.		Reel Color	Brand	Item No.	
in I.D.)	13 ½ in L x 18 in W x 17 in H	Nitrile	Black	_	1MDK1	
Max. Operating Pressure: 5,000 psi						
in I.D.)	32 in L x 17 ½ in W x 20 in H	FKM	Black	Mi-T-M	3WE19	
250 ft (% in I.D.)	18 in L x 18 in W x 18 in H	Nitrile	Silver	_	5RCC7	





Prolongs the life of pressure washer pumps by protecting pistons and seals from damage during storage. Prevents build up of hard water deposits and provides antifreeze protection down to -25°F. Includes

Size	Inlet	Max. Fluid Temp.	For Use With	ltem No.
16 oz	3/4 in (F)NPT	160 °F	Pressure Washers	52JN19









Pressure Washer Hoses **Ontinental**





Bulk Hose—Used to replace worn or damaged hoses on pressure washer machines. Hoses convey pressurized jets of water that loosen and remove dirt, grime, grease, oils, and other substances from equipment and surfaces. Can be cut to the desired length, and compatible hose fittings can be added to the ends of the hoses to create custom hose assemblies

Neptune and Simpson—Coupled hose assemblies are suitable for hot- and cold-water pressure-washing applications. Include fittings on the ends of the hose for connecting to pressure-washing equipment. Dual-braid steel wire reinforcement.

Sewer Hoses—Sewer hoses (also known as jetter hoses) with coupled hose assemblies are used with compatible sewer-cleaning equipment to clean drains, unblock sewer pipes, or prevent clogged drains. Hose is lightweight, abrasion-resistant, and slippery, and it can be pushed inside a pipe. Used

in plumbing and waste-management applications. Compatible sewer nozzles must be attached to the hoses

Nitrile Washdown—Washdown hose assemblies have a nitrile tube. Designed to convey hot water in washdown and cleanup applications in foodprocessing plants, dairies, breweries, canneries, creameries, and similar industrial locations. Outside cover has Microban antimicrobial protection. Single wire braid reinforcement.

Steam Cleaner & Pressure Washer—Hose assemblies are used for replacing old or worn hoses on steam cleaner machines or combination steam cleaner/pressure washer machines. Convey pressurized jets of water or steam that loosen and remove dirt, grime, grease, oils, and other substances from surfaces and equipment. Have an EPDM tube and fittings on their ends for connecting to compatible equipment. Single wire braid reinforcement.

Inside Dia.	Hose Length	Max. Working Pressure @ 70°F	Fitting Size*	Max. Temp.	Brand	Item No.
ilk Pressure Was trile Hose Cover						
½ in	500 ft	3,000 psi		250°F	Continental	1ZLH
½ in	500 ft	3,000 psi	No Fittings	250°F	Continental	1ZLH(
3% in	500 ft	3,000 psi	. Wo i ittiligs	250°F	Continental	1ZLH
	sure Washer Hose	Assemblies		230 1	Continental	IZLIII
oprene Hose Cov	er Material, Blac	k				
1/4 in	30 ft	3,000 psi	1/4 in x 1/4 in	250°F	Continental	2P76
	30 ft	3,000 psi		250°F	Continental	2P76
3/8 in	50 ft	3,000 psi	3/s in x 3/s in	250°F	Continental	2P76
	100 ft	3,000 psi		250°F	Continental	3JT3
	rer Material, Blue					
½ in	50 ft	3,000 psi	½ in x ½ in		Continental	55CN9
1/4 in	50 ft	3,000 psi	1/4 in x 1/4 in	250°F	Continental	3JT3
74 111	100 ft	3,000 psi	74 III X 74 III	250°F	Continental	3JT3
	25 ft	3,000 psi		_	Continental	55CN9
3⁄8 in	50 ft	3,000 psi	3⁄8 in x 3∕8 in	250°F	Continental	3JT4
	100 ft	3,000 psi		250°F	Continental	3JT3
	essure Washer Ho					
	er Material, Blac		2/ . 2/ .			
3% in	100 ft	4,000 psi	% in x % in		Continental	55CN9
ptune 4500 Pres	sure Washer Hose			05005	0 1: 1:	0.17.
3/8 in	50 ft	4,500 psi	3% in x 3% in	250°F	Continental	3JT4
	100 ft	4,500 psi	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	250°F	Continental	3JT4
	sure Washer Hose	ASSEMBIIES				
trile Hose Cover		0.000		05005	0 1' 1 1	47111
3/8 in	50 ft	6,000 psi	% in x % in	250°F	Continental	1ZLH
	100 ft	6,000 psi		250°F	Continental	1ZLH
	ssure Washer Hos					
iyuretnane nose	Cover Material,			05005	0:	001170
2/:-	50 ft	4,500 psi	2/ ! 2/ !-	250°F	Simpson	33HZ2
3⁄8 in	100 ft	4,500 psi	% in x % in		Simpson	33HZ2
museu Meneter D	200 ft Pressure Washer H	4,500 psi			Simpson	33HZ2
	Cover Material, I					
nyuremane nose	50 ft	4,500 psi		140°F	Simpson	33HZ3
3/8 in	100 ft	4,500 psi	3% in x 3% in			33HZ
98 III	200 ft	4,500 psi	78 III X 78 III		Simpson Simpson	33HZ
wer Hoses	200 11	4,500 psi			Sillipsuli	JULIA
C Hose Cover Ma	aterial Rlack					
	25 ft	2,600 psi	M22 Female x M22 Female	140°F	Speedaire	22KD9
1/4 in	25 ft	2,600 psi	1/4 in x M22	140°F	Speedaire	22KD
hher Hose Cover	Material, Black	۷,000 وا	/4 III A IVICC	140 1	эрссиане	ZZRD:
	30 ft	3,000 psi		250°F	Speedaire	22KE0
	50 ft	3,000 psi		250°F	Speedaire	22KE
3/8 in	50 ft	4,500 psi	⅓ in x ¾ in -	250°F	Speedaire	22KE
	100 ft	3,000 psi		250°F	Speedaire	22KE
	25 ft	3,500 psi		250°F	Speedaire	22KE0
5∕16 in	50 ft	3,500 psi	M22 Female x M22 Female	250°F	Speedaire	22KE
rile Washdown I		vith Antimicrohial Car	boxylated Nitrile Cover	200 1	Spooduilo	LLIKE
	Material, Yellow		,			
	50	3,000 psi	2/1 (84) NIDT 2/1 (84) NIDT C	-20 to 250	Continental	1ZLT
3/8	100	3,000 psi	%" (M)NPT x %" (M)NPT S	-20 to 250	Continental	1ZLT
eam Cleaner & P	ressure Washer H	ose Assemblies				
Iorinated Polvet	hylene Hose Cove	r Material, Black				
	30 ft	2,500 psi		325°F	Continental	4KT6
1/2 in	50 ft	2,500 psi	½ in x ½ in	325°F	Continental	4KT6
/4 111	100 ft	2,500 psi	/2111 / /2111	325°F	Continental	4KT6
		2,000 poi		325°F	Continental	2P76
	30 ft	3 000 nsi				
3% in	30 ft 50 ft	3,000 psi 3,000 psi	% in x % in	325°F	Continental	2P76