



Interior & Exterior Paint Primers

These primers contain additives that help prevent fading and rust, repel moisture, stop oxidation and mildew, and resist staining. Exterior primers also help restore already-rusted objects and prepare them for topcoat paints.

**Solvent Base
H7179**



**Water Base
4HFD3**



Compatible Surface Material	► CHOOSE: Color	Sheen	Container Size	Coverage Area	Dry Time	VOC Content	Brand	Sub Brand	Item No.
Solvent									
All Surfaces	Red	Flat	1 gal	690 sq ft/gal	2 hr	450 g/L	Rust-Oleum	High Performance	5H888
Metal	White, Red	Flat	1 gal	330 to 660 sq ft/gal	12 hr	100 g/L	Rust-Oleum	High Performance	H7179
Metal, Steel	Flat Red	Flat	1 gal	255 to 435 sq ft/gal	12 hr	92 g/L	Rust-Oleum	Professional	3ZHx2
Metal, Wood	Gray, Red, White	Gloss	1 gal	300 to 500 sq ft/gal	5 hr	340 g/L	Rust-Oleum	High Performance	H7159
	Gray	Flat	1 qt	300 to 650 sq ft/gal	2 hr	450 g/L	Rust-Oleum	High Performance	6A931
Water									
Aluminum, Concrete, Cured Plaster, Drywall, Masonry, Metal, PVC, Steel, Stucco, Vinyl, Wood	White	Flat	1 qt	350 to 450 sq ft/gal	1 hr	100 g/L	Zinsser	Bulls Eye 1-2-3	4HFD4
	White	Flat	1 gal	350 to 450 sq ft/gal	1 hr	100 g/L	Zinsser	Bulls Eye 1-2-3	4HFD3
Aluminum, Galvanized Steel, Metal, Rusted Steel	Gray	Semi-Gloss	1 gal	137 to 523 sq ft/gal	30 min	0 g/L	Rust-Oleum	Sierra Performance	1TBG2
Concrete, Glass, Hardboard, Metal, Plaster, Tile, Wallboard, Wood	White	Flat	1 gal	155 to 520 sq ft/gal	30 min	100 g/L	Rust-Oleum	Commercial	30RK17
	White	Flat	5 gal	155 to 520 sq ft/gal	30 min	100 g/L	Rust-Oleum	Commercial	30RK16
Machinery, Pipes	Gray, Red	Matte	1 gal	250 to 350 sq ft/gal	2 hr	250 g/L	Rust-Oleum	Commercial	H7176



Interior & Exterior Stain-Blocking Primers

■ Solvent base

Primers coat and protect pre-painted objects that will have a very different, bright, or distinctive topcoat. They prevent the bottom layers of paint from staining through to the new colors.

Compatible Surface Material	Color	Sheen	Size	Container Size	Coverage Area	Dry Time	VOC Content	Sub Brand	Mfr. Model	Item No.
Aluminum, Concrete, Drywall, Metal, Plaster, PVC, Steel, Wood	White	Flat	1 qt	1 qt	350 to 400 sq ft/gal	30 min	350 g/L	Odorless	3954	4HFE9
	White	Gloss	1 qt	1 qt	300 to 400 sq ft/gal	35 min	350 g/L	Cover Stain	3554	4HFE6
	White	Flat	1 gal	1 gal	350 to 450 sq ft/gal	2 hr	350 g/L	Odorless	3951	4HFE8
	White	Semi-Gloss	1 gal	1 gal	300 to 400 sq ft/gal	35 min	350 g/L	Cover Stain	3551	4HFE5



**Odorless
4HFE9**



**Cover Stain
4HFE6**



4CY28



4CY29



Sierra Water-Based Acrylic Enamel and Primer

Fast-drying, water-based acrylic system has low solvent odor and 0 VOCs and HAPs content. Provide excellent blocking resistance, is washable, and protects against corrosion. For interior and exterior applications.

Note: All paint is nonreturnable.

DRY TIME AND COVERAGE			
	Beyond Satin	Beyond Gloss	Griptec
Dry Time:	30 min	30 min	30 min
Coverage:	135 to 490 sq ft/gal	165 to 520 sq ft/gal	180 to 545 sq ft/gal

Color	BEYOND SATIN Item No.	BEYOND GLOSS Item No.
Sierra Performance Finishes (1-gal. Can)		
White Pastel	4CY29	4CY31
White	1TBf5	1TBf4
Black	4CY30	4CY32
Clear	4CY43	4CY44
Safety Blue	—	1TBf7
Safety Red	—	4CY45
Safety Yellow	—	4CY46
Color		Item No.
Sierra Performance Griptec Primers (1-gal. Can)		
White	4CY28	
Gray	21CJ87	



4HFE3



4HFD7

PERMA-WHITE Mold & Mildew Proof Latex Acrylic Paint

■ Low odor

Self-priming paint forms a washable coating that contains a mildewcide to prevent the growth of mold and mildew on the paint film only. Moisture-and-stain resistant. 4HFD7 is a noncorrosive interior sealer that goes on white and dries clear to form a tough, durable overcoat. Exterior paint have a washable finish that withstands moisture and resists dirt pickup.

		DRY TIME AND COVERAGE		
		Interior Paint	Exterior Paint	Sealer
VOC Content:	<50g/L	Less Than 150g/L	100 g/L	
Dry Time:	2 hr.	30 min	2 hr	
Coverage:	300 to 400 sq ft/gal	300 to 400 sq ft/gal	300 to 400 sq ft/gal	
Color	Finish	Size	INTERIOR Item No.	EXTERIOR Item No.
PERMA-WHITE Paint				
White	Eggshell	1 gal	4HFE3	—
	Satin	1 gal	4HFD9	4FZX6
	Satin	5 gal	—	4FZX7
	Semi-Gloss	1 gal	4HFE2	4FZX4
	Semi-Gloss	5 gal	—	4FZX5
PERMA-GUARD Sealer				
Clear	—	1 gal	4HFD7	—