



**Single Component  
4YPK2**



**Multi Component  
J1514**



**Pre Packaged Kits  
19NZ14**



## Urethane Activators & Base Coatings

Urethanes have better resistance to UV rays and abrasion than epoxies but are less hard. They are well suited for use on surfaces that are exposed to sunlight.

**Single Component Urethane Systems** provide toughness, flexibility, abrasion resistance, and excellent UV resistance on commercial or residential floors.

**Multi Component Urethane Systems** are abrasion resistant and more color-retentive than epoxy coatings. These coatings can last longer and look better because the two-process application system bonds more tightly to the floor surface than single-component systems. Activator and base sold separately.

**Pre Packaged Urethane Component Kits** resurface concrete floors and add color to designate walkways or other markings. They are able to provide a number of performance functions such as slip resistance, chemical resistance, and abrasion resistance.

Activator, Base, Paint or Primer	Resin Type	Base Type	Surface	Series Number	Surface Material	Finish	►CHOOSE: Color	Coverage Area	Container Size	VOC Content	Dry Time	Item No.
<b>Single Component Urethane Systems</b>												
<b>CRC SEAL COAT</b>												
Base	Urethane	Solvent	Smooth		Bus Bars, Commutator Ends, Motor Windings, PC Boards, Stator Coils, Terminals	—	Red	20 to 25 sq ft/gal	11 oz	417.4 g/L	72 hr	<b>4YPK2</b>
	Urethane	Solvent	Smooth		Bus Bars, Commutator Ends, Motor Windings, PC Boards, Stator Coils, Terminals	—	Clear	20 to 25 sq ft/gal	11 oz	457.8 g/L	72 hr	<b>4YPK3</b>
<b>Multi Component Urethane Systems</b>												
<b>RUST-OLEUM 3300 Commercial</b>												
Activator	Acrylic Urethane	Solvent	Rough, Smooth	3300	Concrete, Metal	High Gloss	White	260 to 620 sq ft/gal	1 pt	Less Than 250 g/L	5 to 9 hr	<b>J1514</b>
Base	Acrylic Urethane	Solvent	Rough, Smooth	3300	Concrete, Metal	High Gloss	Safety Yellow, Safety Blue, Safety Red	260 to 620 sq ft/gal	1 gal	Less Than 250 g/L	5 to 9 hr	<b>J1514</b>
<b>Pre Packaged Urethane Component Kits</b>												
<b>FLOROCK 4700</b>												
Activator, Base	Urethane	Solvent	Rough, Smooth	4700	Concrete	Gloss	Clear	500 sq ft/gal	4.5 gal	50 g/L	24 hr	<b>19NZ15</b>
Activator, Base	Urethane	Solvent	Rough, Smooth	7100	Concrete	Gloss	Clear	500 sq ft/gal	4.5 gal	46 g/L	24 hr	<b>19NZ14</b>



**Concrete Saver  
4VYH1**



**Wooster  
1AJZ3**



## Single Component Acrylic Systems

Acrylic primers are designed for use on both interior and exterior floors. They dry rapidly to a tough, alkali-resistant finish that will withstand hard wear, abrasion, grease, and strong cleaners.

**Concrete Saver** eliminates dusting, blocks stains, and makes floor easier to clean. Easy touch-up and recoat. Roller application.

**H&C** creates the look of acid stain, and penetrates into the concrete for a faux layered look. A clear coat is required.

**Rust-Oleum** provides numerous primers and activators including mildew-resistant paint for wood and line striping to anti-slip coatings.

**Wooster** anti-slip coating provides safe traction for pedestrian traffic. For use on bare wood, concrete, primed metal, asphalt, marble, stone, and other surfaces.

Activator, Base, Paint or Primer	Base Type	Coating Type	Surface	Surface Material	Finish	►CHOOSE: Color	Coverage Area	Container Size	►CHOOSE: VOC Content	Dry Time	Item No.
<b>Concrete Saver</b>											
<b>Concrete Saver 5600</b>											
Base	Water	Floor Sealer	Rough	Concrete	Semi-Gloss	Clear	150 to 400 sq ft/gal	1 gal	62 g/L	12 hr	<b>4VYH1</b>
<b>H&amp;C Infusion</b>											
	Water	Floor Coating	Rough, Smooth	Concrete, Masonry	Satin	Autumn Breeze, Cocoa Bean	200 sq ft/gal	1 gal	Less Than 50 g/L	4 to 6 hr	<b>J5611</b>
Paint	Water	Floor Coating	Rough, Smooth	Concrete, Masonry	Satin	Cordovan, Semi-Trans Espresso, Semi-Trans Henna, Semi-Trans Tumbled Stone	200 sq ft/gal	1 gal	Less Than 50 g/L	4 to 6 hr	<b>J1441</b>

CONTINUED