



**Anti-Skid Additive 6A936**



**Boiled Linseed Oil 44ZU21**



**Paint Solidifier 2AJN4**



**Leveling & Conditioning 44ZU19**

## Paint Additives

■ Exterior, interior use

**Anti-Skid Additives**—When mixed with epoxy, latex or oil-based paints, stains, or sealers, create a skid-resistant coating for concrete, wood, metal, or fiberglass. Made from aluminum oxide, these additives are frequently used on industrial stairs, decks, and walkways.

**Boiled Linseed Oil**—Both a thinner for oil-based paints and a coating. As a thinner, it improves the flow and gloss of oil-based paints. As a coating, it creates a shiny hand-rubbed finish on wood and furniture. It increases wood's resistance to watermarks, scratches, and warping.

Base Type	Color	Coverage Area	Container Size	Brand	Item No.
<b>Anti-Skid Additives</b>					
Oil, Water	Clear	—	16 oz	H&C	38EK69
	Clear	—	19 lb	H&C	38EK72
Polypropylene	Clear	1 lb; 5 gal	1 lb	Rae	19N218
	Clear	1 lb; 5 gal	15 lb	Rae	19N219
Silica	Off-White	1 lb/gal	1 lb	Rust-Oleum	6A936
	Clear	16 oz/gal	16 oz	Homax	29UR95
<b>Boiled Linseed Oils</b>					
Oil	Amber	80 sq ft	1 gal	Sunnyside	44ZU21
	Amber	400 sq ft	5 gal	Sunnyside	487F10
<b>Paint Solidifiers</b>					
Sodium Polyacrylate	Clear	3/4 gal	3.5 oz	Homax	2AJN4
Sodium Polyacrylate, Sodium Potassium Alumina Silicate	White	Absorbs Up to 3 gal	2 L	XSORB	3VY28
	White	Absorbs Up to 25 gal	4 gal	XSORB	3VZ33
	White	Absorbs Up to 38 gal	23 lb	XSORB	21YX75
<b>Leveling &amp; Conditioning Additives</b>					
Water	Blue	2 to 6 oz/gal	1 qt	M-1	44ZU19

**Paint Solidifiers**—Turn liquid latex paint into a solid material within minutes for fast cleanup and curbside disposal. One package hardens up to two-thirds of a gallon of paint in less than an hour.

**Leveling and Conditioning Additives**—Add flowing or leveling properties to paint without excessively thinning or foaming. These additives are available for both oil-based and water-based paints. They slow down the drying process to ensure that brush streaks can be eliminated.



**6EXK4**



**6EXK0**



**Explosion Proof 6EXK3**



**6EXK2**

## Classic Electric and Air Driven Paint Shakers and Accessories



■ Accommodate pints, quarts, and gallons

Multisize clamping action shakes a variety of container sizes and shapes ranging from 3 1/2" to 11" in height. High-speed bi-axial motion ensures a complete mix and limit switch stops mixing cycle when safety enclosure is opened. Require a base, sold separately.

Style	Timer	W	D	H	Mr. Model	Item No.
Electric Paint Shakers, 110 VV						
Single Arm Electric	15 min Manual	27 1/4 in	29 3/4 in	31 1/2 in	141000	6EXK4
Single Arm Electric	1 hr Manual	27 1/4 in	29 3/4 in	31 1/2 in	14100H	6EXK5
Twin Arm Electric	15 min Manual	41 1/4 in	21 1/4 in	31 1/2 in	140000	6EXK0
Twin Arm Electric	1 hr Manual	41 1/4 in	29 3/4 in	31 1/2 in	14000H	6EXK1
Twin Arm Electric Explosion Proof	—	41 1/4 in	29 3/4 in	31 1/2 in	1400X1	6EXK3
Air Driven Paint Shakers, 8 cfm @ 100 psi						
Single Arm Pneumatic	—	27 1/4 in	29 3/4 in	31 1/2 in	1410A1	6EXK6
Twin Arm Pneumatic	—	41 1/4 in	29 3/4 in	31 1/2 in	1400A1	6EXK2
Description	For Use With				Mr. Model	Item No.
Accessories						
Counter Base for The Classic Shakers	14000H, 1400A1, 141000, 14100H, 1410A1, Mr. No. 140000				515300	6FWG7



**39UL63**

## Floor Chips

■ Interior use

Decorative polymer floor flakes are specially formulated paint aggregates used to enhance the aesthetic qualities of seamless, resin-based chip/flake flooring systems. Sprinkle the chips directly onto the wet epoxy coating, then finish with a clear top coat.

Color	Coverage Area	Container Size	Item No.
Black/Blue/White	0.002 lb/sq ft	1 lb	39UL63
Black/Gray/White	0.002 lb/sq ft	1 lb	39UL68
Black/White	0.002 lb/sq ft	1 lb	39UL66
Blue/White	0.002 lb/sq ft	1 lb	39UL69



**14C564**



**6FWH0**

## RADIA Paint Mixing Equipment Accessories

Description	Mr. Model	Item No.
Counter Mount Lid Press	5080-03	14C563
Lid Press With Base Plate	5080-04	14C564
5-gal. Lid Sealer	507000	6FWH0
Draw Down 40-Slot Drying Tower	A3525	6FWH2
Magnetic Mallet Holder	A3522	6FWH3



## RADIA Red D Mix Intrinsically-Safe Mixer

Features gyroscopic mixing action with direct-drive gear system. No timer or power cord included; requires installation by qualified electrician.

Accommodates	Voltage	Mr. Model	Item No.
5 gal Pails	110 V	05025-X1	34AU66