Scan. Order. Done. Details on page A1.





3 5 fl oz

Crank Tool

Xylene/

Toluene

12H847

r.	
aint	
n Tool	
be refilled or h aerosol-filling	
also charge	
e in the can. allow users	

Item

Nn

2KRF2

Material

Aluminum





Thermoplastic pavement marking paints clearly mark traffic lanes, legends, symbols, and road boundaries on roads, parking lots, and other paved surfaces. They are thicker and more wear resistant than other types of marking paints. These paints are heated and applied to paved surfaces to increase visibility and provide long-term wear. Line rolls come in a variety of colors for varied road and pavement needs. These rolled strips can be applied to any roadway to delineate the lanes and keep traffic flowing.

Legend	Color	Overall Length	Overall Width	Thickness	Minimum Application Temperature	Maximum Application Temperature	ltem No.
Pavement P	re-Determined	Messages					
Handicap —	Blue	38 in	3-ft	90 mil	_	300 °F	18E570
	Blue/White	45 in	45 in	90 mil	_	300 °F	18E572
Pavement Li	ne Rolls						
	Yellow	30-ft	4 in	90 mil	32 °F	275 °F	18E661
Rolls	Yellow	30-ft	6 in	90 mil	32 °F	275 °F	18E667
	Yellow	30-ft	12 in	90 mil	32 °F	275 °F	18E669



14 in

9 ¼ in

Xylol Thinner 5KPY4

Water

Immersion 6H076



Container

Paint Thinners

These liquid paint thinners reduce the viscosity of paint.

General Purpose Paint Thinners—

Solvents used to thin or reduce the viscosity of paints to prepare them for spray application or to clean up after their use.

Mineral Spirits-Petroleum-derived clear liquids used as a common organic solvent in cleaning up after painting. Mineral spirits are less expensive than turpentine and thin oil-based paints, stains and varnishes.

Lacquer Thinners-A mixture of solvents able to dissolve a number of different resins or plastics used in lacquer finishes. They clean tools and equipment after a lacquer project.

Xylene Thinners—Used for thinning paints, enamels, varnishes, and alkyd resins. They are highly flammable and are recommended for ventilated or exterior use. Toluene paint removers are fast-drying solvents for thinning oil-based paints, varnishes, enamels and alkyd resins.

Xylol Thinners—Used for thinning paints, enamels, varnishes, and alkyd resins. Often specified as a thinner for specialty paints and coatings, xylene is highly flammable and is recommended for ventilated or exterior use.

Water Immersion Coatings—Protective layers that are applied to a material that will be subjected to water or liquid for an extended period of time. Thinners for immersion coatings reduce the viscosity of the coatings so that it can be spray-applied instead of brushed or rolled onto a surface. This is commonly done for surfaces that are not flat or are uneven.

Item

Container

Materials Removed	Contains	Strength	Container Type	Container Size	Brand	ltem No.
General Purpose Paint Thinners						
Oil Base Type						
Dirt, Grease	LVP Mineral Spirits	Regular	Pail	5 gal	Sunnyside	499H58
Solvent Base Type						
9400 System, Adhesive, Epoxy Coating, Grease, Oil, Urethane Coating	Ethyl 3-Ethoxypropionate, Ethyl Acetate, Methyl Ethyl Ketone	Regular	Can	1 gal	Rust-Oleum	5H949
Alkyd Coating, Epoxy Coating, VOC Compliant Products	Acetone	Regular	Can	1 gal	Rust-Oleum	3JR74
Alkyd Coating, Industrial Enamel, Latex Coating	n-Nonane, Naphtha, Pine oil	Regular	Can	1 gal	Rust-Oleum	5H887
Alkyd Coating, Latex Coating	n-Heptane, Naphtha, Octane, Pine oil	Regular	Can	1 gal	Rust-Oleum	5A261
Dirt, Grease	Acetone, Aliphatic Naphtha	Regular	Can	1 gal	Sunnyside	499H54
Paint, Solvent Based Products	Parachlorobenzotrifluoride	Regular	Can	1 gal	Rust-Öleum	426J32
Water Base Type						
Paint	Dipropylene Glycol Monomethyl Ether, Naphtha, p-Chloro- a,a,a-Trifluorotoluene, Sodium Dioctyl Sulfosuccinate	Regular	Bottle	1 gal	Green Envy	5KPY0
Mineral Spirits						
Oil Base Type						
Dirt, Grease	Mineral Spirits	Regular	Can	1 gal	Sunnyside	5KPY3
Dirt, Grease	Mineral Spirits	Regular	Pail	5 gal	Sunnyside	44ZU14
Lacquer Thinners						
Solvent Base Type						
Epoxy Coating, Lacquer	2-Butoxyethanol, Acetone, Parachlorobenzotrifluoride	Regular	Can	1 gal	Sunnyside	12H845
Epoxy Coating, Lacquer	2-Butoxyethanol, Acetone, Parachlorobenzotrifluoride	Regular	Pail	5 gal	Sunnyside	499H52
Epoxy Coating, Lacquer	Acetone, Aliphatic Naphtha, Ethyl Acetate, Ethylbenzene, Methyl Alcohol, Methyl Ethyl Ketone, Toluene, Xylene	Regular	Can	1 gal	Sunnyside	5KPY2
Epoxy Coating, Lacquer	Acetone, Aliphatic Naphtha, Ethyl Acetate, Ethylbenzene, Methyl Alcohol, Methyl Ethyl Ketone, Toluene, Xylene	Regular	Pail	5 gal	Sunnyside	22M494
Xylene/Toluene						
Solvent Base Type						
Adhesive	Acetone, Parachlorobenzotrifluoride	Regular	Can	1 gal	Sunnyside	12H847
Paint	Cumene, Ethylbenzene, Mixed Xylenes, Toluene	Premium	Bucket	5 gal	Rae	19NZ68
Paint	Toluene	Premium	Bucket	5 gal	Rae	3EHJ6
Xylol Thinners				0		
Solvent Base Type						
Adhesive, Anti-Rust, Epoxy, Lacquer, Oil-Based Paint, Porch and Deck Paint, Synthetic Enamel, Varnish	Ethylbenzene	_	Can	1 gal	Sunnyside	5KPY4
Water Immersion Coating Thinners						
Solvent Base Type						
Epoxy Mastic, Paint	Ethylbenzene, Methyl Isobutyl Ketone, n-Butanol, Toluene, Xylene	Regular	Can	1 gal	Rust-Oleum	6H076

GRAINGER® 1550

Find even MORE on Grainger.com®

1-800-GRAINGER (472-4643)