



**Kool Seal Patching Cement**  
4FJK6



**Kool Seal Storm Patch**  
4FJK7



**Storm Patch**  
4FJK3

**Flexx Sealer Roll**  
4FJL1



**Flexx Sealer**  
4FJK8



**Storm Patch**  
4FJK4



## Roof Patching & Repair Products



**Kool Seal Acrylic Patching Cement**—Stops leaks on damp or dry surfaces. Blends in on existing white roofs.

**Storm Patch All-Weather Rubberized Cements**—Displace water from wet surfaces and create a tight seal.

**Flexx Sealer Permanent Leak Repair**—Bonds immediately, seals instantly to clean dry surface. Never hardens, cracks, peels or shrinks.

Description	Container Type	Size	Color	Item No.
<b>Patching, Plugging, and Joint Compounds</b>				
Kool Seal Acrylic Patching Cement	Tube	10.5 oz	White	4FJK6
Kool Seal Acrylic Patching Cement	Can	115 oz	White	4FJK7
Storm Patch All-Weather Rubberized Cement Patch	Tube	10 oz	Clear	4FJK3
Storm Patch All-Weather Rubberized Cement Patch	Tube	10.5 oz	Black	4FJK4
<b>Leak Repair</b>				
Flexx Sealer Leak Repair and Sealer Roll	Roll	2 in x 10 ft	Gray	4FJL1
Flexx Sealer Permanent Leak Repair Strip	Roll	2 in x 3 ft	White	4FJK8



**Rubberized Liquid Coating**  
55KE45



**Rubberized Tape Adhesive**  
55KJ96

## Multisurface Rubberized Coatings

**Rubberized Liquid Coatings** apply to surfaces and then dry to be waterproof barriers.

**Rubberized Tape Adhesives** produce leakproof membranes and insulation necessary to cover the entire surface of a pipe. They can be used in conjunction with liquid coatings like epoxies to enhance surface protection. Withstands tear and abrasion.



RUBBERIZED LIQUID COATINGS							
Color	Coverage Area	Container Size	Container Type	Dry Time	Cure Time	Brand	Item No.
Rubberized Liquid Coatings							
Rubber							
Black	2 sq ft	2 oz	Aerosol	24 to 48 hr	24 to 48 hr	Flex Seal	55KE45
	37.5 sq ft	32 oz	Can	24 to 48 hr	48 hr	Flex Seal	55KE52
Clear	2 sq ft	2 oz	Aerosol	24 to 48 hr	24 to 48 hr	Flex Seal	55KE46
	37.5 sq ft	32 oz	Can	24 to 48 hr	48 hr	Flex Seal	55KE53
Gray	12 sq ft	14 oz	Aerosol	2 to 3 hr	2 to 3 hr	Flex Seal	55KE47
	37.5 sq ft	32 oz	Can	24 to 48 hr	48 hr	Flex Seal	55KE55
White	12 sq ft	14 oz	Aerosol	2 to 3 hr	2 to 3 hr	Flex Seal	55KE50
	37.5 sq ft	32 oz	Can	24 to 48 hr	48 hr	Flex Seal	55KE56
Solvent							
Black	20 sq ft	16 oz	Can	20 to 30 min	30 min	Nu-Calgon	20LP95
White	20 sq ft	16 oz	Can	20 to 30 min	30 min	Nu-Calgon	1ANJ9
RUBBERIZED TAPE ADHESIVES							
Color	Surface Material			Brand		Item No.	
Black	Concrete, Metal, Wood			Flex Seal		55KJ96	
White	Concrete, Metal, Wood			Flex Seal		55KJ99	
Black	Concrete, Metal, Wood			Flex Seal		55KJ95	



**Loctite**  
3KZK5



**Loctite**  
6KVD2



## Cool Rubberized Dip Coatings

These coatings contain an air-dry, specialty rubber formulation that is peelable, flexible, insulating, non-slip, and durable. Metal parts may be dipped into the coating to enhance appearance, provide a soft grip, or protect the part from chemicals or abrasion.

Color	Minimum Application Temperature	Maximum Application Temperature	Container Size	Applic. Method	Dry Time	Dry Time to Recoat	Brand	Item No.
Black	—	—	1 gal	Brush, Spray	24 hr	1 hr	—	3KZK5
Blue	-30 °F	200 °F	14.5 oz	Brush, Dip, Spray	4 hr	4 hr	Loctite	6KV01
	-30 °F	200 °F	1 gal	Brush, Dip, Spray	4 hr	4 hr	Loctite	6KV02
Green	—	—	1 gal	Brush, Spray	24 hr	1 hr	—	3KZK7
	-30 °F	200 °F	1 gal	Brush, Dip, Spray	4 hr	4 hr	Loctite	6KVD4
Red	—	—	1 gal	Brush, Spray	24 hr	1 hr	—	3KZL4
	-30 °F	200 °F	14.5 oz	Brush, Dip, Spray	4 hr	4 hr	Loctite	6KVD3



## Garage Floor Coating Kits

Surfaces: Concrete

**EpoxyShield Professional**—2-component finish strengthens and protects concrete floors. Resists chemicals and standing water.

**EpoxyShield**—One coat brightens floor with a clean, glossy, water-based coating. Protect against gasoline, antifreeze, motor oil, salt, hot tire pickup and cracking.

Color	Coverage Area	VOC Content	Dry Time	Container Size	Mfr. Model	Brand	Item No.
<b>EpoxyShield, Professional</b>							
Dark Gray	150 to 200 sq ft/gal	Less Than 250 g/L	4 day	2 gal	238467	Rust-Oleum	1TBG4
Dunes Tan	150 to 200 sq ft/gal	Less Than 250 g/L	4 day	2 gal	238466	Rust-Oleum	1TBG3
Silver Gray	150 to 200 sq ft/gal	Less Than 250 g/L	24 to 96 hr	2 gal	203373	Rust-Oleum	3BU19
Tile Red	150 to 200 sq ft/gal	Less Than 250 g/L	4 day	2 gal	238468	Rust-Oleum	1TBG5
<b>EpoxyShield</b>							
Clear	250 to 500 sq ft/kit	Less Than 75 g/L	24 to 72 hr	1 gal	292514	Rust-Oleum	52JU45
Gray	250 sq ft/pouch	Less Than 50 g/L	72 hr	120 oz	251965	Epoxyshield	6KP68
Tan	250 sq ft/pouch	Less Than 50 g/L	72 hr	120 oz	251966	Epoxyshield	6KP69



**3BU19**