



simple green

Pressure Washer Chemicals

Designed for use in all types of pressure washers.



Description	Size	Brand	Item No.
Crankcase Oil, SAE Grade 30	16 oz.	—	1MDJ8
Simple Green Deck and Fence Cleaner Concentrate	1 gal	Simple Green	3ANW4
Simple Green House and Siding Cleaner Concentrate	1 gal	Simple Green	3ANW5
Simple Green Concrete and Driveway Cleaner Concentrate	1 gal	Simple Green	3ANW6
Simple Green Heavy-Duty Cleaner and Degreaser Concentrate	1 gal	Simple Green	3ANW7

Water Brooms

Rust-resistant brooms provide a wide cleaning path for fast and easy cleaning. Units hook up to pressure washer spray gun lance with a standard 1/4" quick disconnect plug.



Description	W	Max. Pressure	Item No.
3-Nozzle	12 in	4,000 psi	1MDK4
4-Nozzle	16 in	4,000 psi	1MDK5

REELCRAFT

Mi-T-M

Pressure Wash Hand-Crank Hose Reels

These hose reels are equipped with a high-pressure water swivel that handles a broad range of pressures, temperatures, and chemicals. These steel reels withstand corrosion, hold tangle-free hose, and mount on the floor, wall, bench, or in trucks. They are used with water or chemical hoses for equipment cleaning, pressure washing, and in agricultural spraying.



Hose Cap.	Overall Dim.	Seal Material	Reel Color	Brand	Item No.
Max. Operating Pressure: 3,000 psi					
100 ft (3/4 in I.D.)	13 1/2 in L x 18 in W x 17 in H	Nitrile	Black	—	1MDK1
Max. Operating Pressure: 5,000 psi					
100 ft (3/4 in I.D.)	14 in L x 13 3/4 in W x 20 1/8 in H	TFE/P	Red	Reelcraft	5KPC9
150 ft (1 in I.D.)	32 in L x 17 1/2 in W x 20 in H	FKM	Black	Mi-T-M	3WE19
250 ft (3/4 in I.D.)	18 in L x 18 in W x 18 in H	Nitrile	Silver	—	5RCC7

BRIDGE & STRATTON

Pressure Washer Pump Savers

Unique antifreeze and lubricant formula. Protect pistons and seals from damage during storage. For use before extended storage and before startup the next season.



Size	Max. Pressure	Max. Fluid Temp.	Inlet	Item No.
4 oz	0.1 psi	122 °F	3/4 in NPT	45TP60
10 oz				45TP61



22KD99



22KE01



1ZLT8

SPEEDAIRE

Pressure Washer Hoses

SPEEDAIRE

2600 psi models have a textile braid reinforcement, and RMA Class B oil resistance. 3000 to 4500 psi models have a wire braid reinforcement, and RMA Class A oil resistance.

YELLOW, NITRILE

Stainless steel wire braid reinforcement for protection against oil and animal fat. RMA Class A oil resistance and 4:1 safety factor.

BLUE AND BLACK, NITRILE

1500 psi models have a textile braid reinforcement. 3000 and 4500 psi models have a wire braid reinforcement. Blue hoses are nonmarking and

abrasion resistant. RMA Class B oil resistance and 4:1 safety factor.

FOOD GRADE

Single wire braid reinforcement. Resists oil, abrasion, and animal fats. Outside cover has Microban antimicrobial protection. 4:1 safety factor.

STEAM CLEANER/PRESSURE WASHER

Single wire braid reinforcement. For steam cleaners or combination steam cleaners/pressure washers. Handles hot water up to 250°F at 3000 psi (2500 psi on 1/2"), or steam up to 325°F at 350 psi. 4:1 safety factor.

Inside Dia.	Hose Length	Max. Working Pressure @ 70°F	Fitting Size*	Max. Temp.	Item No.
SPEEDAIRE, Black, PVC					
1/4 in	25 ft	2,600 psi	M22 Female x M22 Female	140°F	22KD99
	25 ft	2,600 psi	1/4 in x M22	140°F	22KE01
SPEEDAIRE, Black, Nitrile					
3/8 in	25 ft	3,500 psi	M22 Female x M22 Female	250°F	22KE04
	50 ft	3,500 psi		250°F	22KE05
	30 ft	3,000 psi		250°F	22KE01
1/2 in	50 ft	3,000 psi	3/8 in x 3/8 in	250°F	22KE02
	50 ft	4,500 psi		250°F	22KE06
	100 ft	3,000 psi		250°F	22KE03
Yellow, Nitrile					
	15 ft	3,000 psi		250°F	1DKL9
	25 ft	3,000 psi		250°F	1DKN1
3/8 in	50 ft	1,500 psi	3/8 in x 3/8 in	250°F	1DKN4
	50 ft	3,000 psi		250°F	1DKN2
	100 ft	1,500 psi		250°F	1DKN5
1/2 in	50 ft	3,000 psi	1/2 in x 1/2 in	250°F	1DKN3
Blue, Nitrile					
1/4 in	50 ft	3,000 psi	1/4 in x 1/4 in	250°F	3JT38
	100 ft	3,000 psi		250°F	3JT37
3/8 in	50 ft	3,000 psi	3/8 in x 3/8 in	250°F	3JT40
	100 ft	3,000 psi		250°F	3JT39
Black, Nitrile					
1/4 in	25 ft	1,500 psi	1/4 in x 1/4 in	200°F	2P768
	30 ft	3,000 psi		250°F	2P763
	30 ft	1,500 psi		200°F	2P769
	30 ft	3,000 psi		250°F	2P764
	50 ft	1,500 psi		200°F	3JT35
3/8 in	50 ft	3,000 psi	3/8 in x 3/8 in	250°F	2P765
	50 ft	4,500 psi		250°F	3JT42
	100 ft	3,000 psi		250°F	3JT36
	100 ft	4,500 psi		250°F	3JT41
Black, Synthetic Rubber					
3/8 in	50 ft	6,000 psi	3/8 in x 3/8 in	250°F	1ZLH4
	100 ft	6,000 psi		250°F	1ZLH5
Bulk Hose without Fittings, Black, Synthetic Rubber					
1/4 in	500 ft	3,000 psi		250°F	1ZLH6
3/8 in	500 ft	3,000 psi	No Fittings	250°F	1ZLH7
1/2 in	500 ft	3,000 psi		250°F	1ZLH8
Food Grade, Yellow					
3/8	50	3,000 psi	3/8" (M)NPT x 3/8" (M)NPT S	-20 to 250	1ZLT8
	100	3,000 psi		-20 to 250	1ZLT9
Steam Cleaner/Pressure Washer, Black					
	30 ft	3,000 psi		325°F	2P766
3/8 in	50 ft	3,000 psi	3/8 in x 3/8 in	325°F	2P767
	100 ft	3,000 psi		325°F	3JT43
	30 ft	2,500 psi		325°F	4KT64
1/2 in	50 ft	2,500 psi	1/2 in x 1/2 in	325°F	4KT65
	100 ft	2,500 psi		325°F	4KT63

* S=Swivel