For additional paint, go to Grainger.com and search interior paint.

Drywall Repair

Use with gypsum, drywall, nailheads, corner beads, wood, plastic, brick, plaster, metal, stucco, masonry, and concrete.

COMPOUNDS

DryDex Premium Lightweight Joint Compound—Features dry time indicator. Compound goes on pink, dries white.

Lightweight Wallboard Joint Compound—Ready-mixed lightweight formula.

DAP FASTPATCH 30 Patching Compound Powder

-Multipurpose formula resists impacts, shrinking, and cracking. Can be painted without priming.

SPACKLING

DryDex Spackling—Dry-time indicator goes on pink and dries

Vinvl Interior Spackling— Resists cracking and crumbling.

Fast n' Final Lightweight Spackling - Interior/Exterior-

1-step interior/exterior formula requires no sanding. White color. Lightweight.



PATCHING

10L498

ElastoPatch Flexible Patching Compound—Permanently eliminates recurring cracks.

Presto Patch Ready-Mixed Multi-Purpose Patching Compound—Ready mixed patching compound for filling, leveling, and patching holes.

All-Purpose Stucco Patch-Blends naturally with existing stucco. Interior and exterior

Wood Filler—Fills small holes and cracks in interior and exterior surfaces. Adheres to stucco, plaster, drywall, and wood.

Plaster of Paris—For patching and repairing large holes in interior plaster or wallboard.

Patching Plaster—For major repairs on interior plaster or wallboard surfaces.

Size	Dry Time	No.	
	•		
1 gal	Varies	10L498	
1 gal	24 hr	2GKY6	*
3 lb	24 hr	2GKY7	*
3.5 lb	Varies	29RU97	
1 qt	5 hr	2GKY9	*
1 qt	5 hr	5E110	
1 qt	Varies	5E113	
1 qt	3 hr	2GKZ6	*
1 qt	3 hr	2GKZ7	*
1 gal	5 hr	2GLA7	*
1 gal	36 hr	2GKZ5	*
1 qt	48 hr	54PC56	
4 lb	72 hr	10L526	
8 lb	72 hr	10L527	
32 oz	5 hr	10L528	
	Item	ı İtem	1
	40TC	72 40TC	73
	1 gal 1 gal 3 lb 3.5 lb 1 qt 1 qt 1 qt 1 qt 1 qt 1 qt 1 qt 4 lb 8 lb	1 gal Varies 1 gal 24 hr 3 lb 24 hr 3 lb 24 hr 3.5 lb Varies 1 qt 5 hr 1 qt 5 hr 1 qt 3 hr 1 qal 5 hr 1 gal 36 hr 1 qt 48 hr 1 qt 48 hr 4 lb 72 hr 8 lb 72 hr 32 oz 5 hr 1 qal lten No.	Size Dry Time No. 1 gal Varies 10L498 1 gal 24 hr 2GKY6 3 lb 24 hr 2GKY7 3.5 lb Varies 29RU97 1 qt 5 hr 2GKY9 1 qt 5 hr 5E110 1 qt Varies 5E113 1 qt 3 hr 2GKZ6 1 qt 3 hr 2GKZ6 1 qt 3 hr 2GKZ7 1 gal 5 hr 2GLA7 1 gal 36 hr 2GKZ5 4 lb 72 hr 10L526 8 lb 72 hr 10L526 8 lb 72 hr 10L526 1 gal 1 gal 1 gal 1 tem No. No.



Rust Tough and Rust Tough 250 Primer and Paint

■ VOC content: < 250 g/L

Corrosion-resistant, direct-to-metal alkyd enamel. Protects against mild chemicals, fumes, oil, and grease stains. Excellent hide, color, and gloss retention. Superior chip. crack. and peel resistance. Rust Tough 250 performs like a traditional alkyd enamel. For use in moderate to severe industrial environments and is acceptable for use in federally inspected meat and poultry plants.



J5605

CHOOSE: Color Rust Tough Paint	Finish	Size	Item No.
Black, White, Light Machinery Gray, Safety Orange, Safety Red, Safety Yellow, White Base	Gloss	1 gal	J5606
Rust Tough 250 Primer			
Gray, Red Oxide	Gloss	1 gal	J5604
Rust Tough 250 Paint			
Black, Dark Machinery Gray, OSHA Equipment			
Yellow, Light Machinery Gray, Safety Blue, OSHA Safety Red, Safety Yellow, White	Gloss	1 gal	J5605
term cannel many remains and the control of the con			



Tough Coat and Tough Coat Quik-Dry Paint

Multipurpose alkyd gloss enamel designed for new construction and industrial maintenance applications. For interior and exterior applications. Dries fast and allows equipment to be placed back in service quickly. Chip and flake resistant. Tough Coat Quik-Dry is ideal for industrial, OEM and metal fabrication. Air dries within 15 min.



J5607

CHOOSE:	Finish	Size	ltem No.
Tough Coat Paint			
Black, Aluminum, Safety Orange, Safety Red, Safety Yellow, White	Gloss	1 gal	J5607
Safety Yellow	Gloss	5 gal	J5607
Tough Coat Quik-Dry Paint			
Black, International Harvester Red, Machine White, White Base	Flat, High Gloss	1 gal	J5608



Industrial Primer

Heavy-duty primer offers good protection for steel in normal industrial environments. Industrial Primer is for interior and exterior use. Easy to apply by spray. Fast drying. Can be topcoated with alkyd and latex coatings. Weld-Thru Primer is rust inhibitive and designed for shop-priming structural steel. Excellent choice for where harsh environments put heavy performance demands on a shop-applied primer. May be welded through with no effect on the weld's integrity.

CHOOSE:	Finish	Size	ltem No.
Industrial Primer			
Gray, Red	Flat	1 gal	J5609
Weld-Thru Primer			
Black, Gray, Red	Flat	1 gal	J1475

