





Bulls Eye 1-2-3 Water-Based **Primer-Sealer** Stain-Blocker

- Low odor
- Mold and mildew resistant

Size	VOC Content	Dry Time Recoat	Coverage	Mfr. Model	Item No.
1 gal	Less Than 100g/L	1 hr	350 to 450 sq ft/gal	2001	4HFD3





B-I-N Shellac-Based Primer-Ultimate Stain Blocker

■ VOC content: <550 a/L Nontoxic, hypoallergenic film stops bleeding knots and sap streaks. No sanding

		requireu.		
Net Weight	Dry Time Recoat	Coverage	Mfr. Model	Item No.
13 oz	30 min	10 to 12 sq ft/gal	1008	4HFC5
10.9 lb	15 to 20 min	500 sq ft/gal	901	4HFC3



4CY28



4CY29

RUST-OLEUM[®]

Sierra Water-Based Acrylic Enamel and Primer

Fast-drying, water-based acrylic system has low solvent odor and 0 VOCs and HAPs content. Provide excellent blocking resistance, is washable, and protects against corrosion. For interior and exterior applications.

Note: All paint is nonreturnable.

DRY TIME AND COVERAGE			
	Beyond Satin	Beyond Gloss	Griptec
Dry Time:	30 min	30 min	30 min
Coverage:	135 to 490 sq ft/gal	165 to 520 sq ft/gal	180 to 54 sq ft/gal

	SATIN	GLOSS
Color	Item No.	Item No.
Sierra Performa	nce Finishes	(1-gal. Can)
White Pastel	4CY29	4CY31
White	1TBF5	1TBF4
Black	4CY30	4CY32
Clear	4CY43	4CY44
Navy Gray	_	1TBF6
Safety Blue	_	1TBF7
Safety Red	_	4CY45
Safety Yellow	_	4CY46
Color		tem No.

REVOND REVOND





ZINSSER

4HFD7

Sealer

PERMA-WHITE Mold & Mildew Proof Latex Acrylic Paint

Low odor

a washable coating that contains a mildewcide to prevent the growth of mold and mildew on the paint film only. Moistureand-stain resistant. 4HFD7 is a noncorrosive interior sealer that goes on white and dries clear to form a tough, durable overcoat. Exterior paint have a washable finish

that withstands moisture

and resists dirt pickup.

Self-priming paint forms

Content:	<50g/L	Less Than 150g/L		100g/L
Dry Time:	2 hr.	30	min	30 min
Coverage:	300 to 400 sq. ft./gal.		to 400 ft/gal	300 to 400 sq ft/gal
Color	Finish	Size	INTERIOR Item No.	EXTERIOR Item No.
PERMA-WHITE Paint				
	Eggshell	1 gal	4HFE3	_
	Satin	1 gal	4HFD9	4FZX6
White	Satin	5 gal	_	4FZX7
	Semi- Gloss	1 gal	4HFE2	4FZX4
	Semi- Gloss	5 gal	_	4FZX5
PERMA-GUAF	RD Sealer			
Clear		1 gal	4HFD7	_

DRY TIME AND COVERAGE

Interior Paint Exterior Paint



4HFF2



Waterproofing Paint

- Low odor
- Interior/exterior

Solvent-based paint stops up to 34-lb. of water pressure. Prevents recurring efflorescence. Prevents growth of mold and mildew on paint film.

DRY TIME A	ND COVERAGE
VOC Content:	Less Than 400g/L
Dry Time:	1 hr.
Coverage:	75 to 100 sq ft/gal

Color	Size	No.
Bright White	1 gal	4HFF2
Bright White	3 gal	4HFF3

Item