



Single Component 4YPK2

Pre Packaged Kits 19NZ14

Pre Packaged Kits K3905



Urethane Activators & Base Coatings

Urethanes have better resistance to UV rays and abrasion than epoxies but are less hard. They are well suited for use on surfaces that are exposed to sunlight.

Single Component Urethane Systems provide toughness, flexibility, abrasion resistance, and excellent UV resistance on commercial or residential floors.

Multi Component Urethane Systems are abrasion resistant and more color-retentive than epoxy coatings. These coatings can last longer and look better because the two-process application system bonds more tightly to the floor surface than single-component systems. Activator and base sold separately.

Pre Packaged Urethane Component Kits resurface concrete floors and add color to designate walkways or other markings. They are able to provide a number of performance functions such as slip resistance, chemical resistance, and abrasion resistance.

Activator, Base, Paint or Primer	Resin Type	Base Type	Surface	Series Number	Surface Material	Finish	▶CHOOSE: Color	Coverage Area	Container Size	VOC Content	Dry Time	Item No.
Single Component Urethane Systems												
CRC SEAL COAT												
Base	Urethane	Solvent	Smooth		Bus Bars, Commutator Ends, Motor Windings, PC Boards, Stator Coils, Terminals	—	Red	20 to 25 sq ft/gal	11 oz	417.4 g/L	72 hr	4YPK2
	Urethane	Solvent	Smooth		Bus Bars, Commutator Ends, Motor Windings, PC Boards, Stator Coils, Terminals	—	Clear	20 to 25 sq ft/gal	11 oz	457.8 g/L	72 hr	4YPK3
Multi Component Urethane Systems												
RUST-OLEUM 3300 Commercial												
Activator	Acrylic Urethane	Solvent	Rough, Smooth	3300	Concrete, Metal	High Gloss	White	260 to 620 sq ft/gal	0.11 gal	Less Than 250 g/L	5 to 9 hr	J1514
Base	Acrylic Urethane	Solvent	Rough, Smooth	3300	Concrete, Metal	High Gloss	Safety Yellow, Safety Blue, Safety Red	260 to 620 sq ft/gal	1 gal	Less Than 250 g/L	5 to 9 hr	J1514
Pre Packaged Urethane Component Kits												
FLOROCK 4700												
Activator, Base	Urethane	Solvent	Rough, Smooth	4700	Concrete	Gloss	Clear	500 sq ft/gal	4.5 gal	50 g/L	24 hr	19NZ15
FLOROCK 7100												
Activator, Base	Urethane	Solvent	Rough, Smooth	7100	Concrete	Gloss	Clear	500 sq ft/gal	4.5 gal	46 g/L	24 hr	19NZ14
RUST-OLEUM 9700 High Performance												
Activator, Base	Acrylic Polyester Urethane	Solvent	Rough, Smooth	9700	Concrete, Galvanized Metal, Metal, Steel	High Gloss	White, Crystal Clear	360 to 860 sq ft/gal	1 gal	Less Than 250 g/L	5 to 15 hr	K3906
RUST-OLEUM 9800 High Performance												
Activator, Base	Urethane Mastic	Solvent	Rough, Smooth	9800	Steel, Concrete, Galvanized Metal, Metal	High Gloss	Aluminum, Safety Blue, Regal Red, Black, Navy Gray, White, Safety Yellow	160 to 280 sq ft/gal	1 gal	Less Than 340 g/L	4 to 9 hr	K3905



1AJZ3 Wooster



Single Component Acrylic Systems

Acrylic primers are designed for use on both interior and exterior floors. They dry rapidly to a tough, alkali-resistant finish that will withstand hard wear, abrasion, grease, and strong cleaners.

Concrete Saver eliminates dusting, blocks stains, and makes floor easier to clean. Easy touch-up and recoat. Roller application.

H&C creates the look of acid stain, and penetrates into the concrete for a faux layered look. A clear coat is required.

INSL-X by Benjamin Moore helps provide a durable finish for interior or exterior applications that require extra skid resistance. It also helps fill and

seal cracks, and provide resistance to abrasions and ponding water. The coating is water-reduced, which allows for easy application, fast drying, and simple clean up. It is ideal for stairs, walkways, patios, and other areas with high foot traffic.

Rust-Oleum provides numerous primers and activators including mildew-resistant paint for wood and line striping to anti-slip coatings.

Wooster anti-slip coating provides safe traction for pedestrian traffic. For use on bare wood, concrete, primed metal, asphalt, marble, stone, and other surfaces.

Activator, Base, Paint or Primer	Base Type	Coating Type	Surface	Surface Material	Finish	▶CHOOSE: Color	Coverage Area	Container Size	▶CHOOSE: VOC Content	Dry Time	Item No.
Concrete Saver 5600											
Base	Water	Floor Sealer	Rough	Concrete	Semi-Gloss	Clear	150 to 400 sq ft/gal	1 gal	62 g/L	12 hr	4VYH1
H&C Infusion											
Paint	Water	Floor Coating	Rough, Smooth	Concrete, Masonry	Satin	Autumn Breeze, Cocoa Bean	200 sq ft/gal	1 gal	Less Than 50 g/L	4 to 6 hr	J5611
	Water	Floor Coating	Rough, Smooth	Concrete, Masonry	Satin	Cordovan, Semi-Trans Espresso, Semi-Trans Henna, Semi-Trans Tumbled Stone	200 sq ft/gal	1 gal	Less Than 50 g/L	4 to 6 hr	J1441
INSL-X by Benjamin Moore											
INSL-X											
Base	Water	Anti-Slip Coating	Rough, Smooth	Asphalt, Concrete, Metal, Wood	Flat	Tintable White, Gray Pearl, Light Gray, Tile Red, Pine Green, Desert Sand, Saddle Brown	80 to 120 sq ft/gal	1 gal	133 g/L	1 to 2 hr	J4599

CONTINUED