

CONTINUED



Single Component Acrylic Systems

Activator, Base, Paint or Primer	Base Type	Coating Type	Surface	Surface Material	Finish	►CHOOSE: Color	Coverage Area	Container Size	►CHOOSE: VOC Content	Dry Time	Item No.
Rust-Oleum Concrete Saver 5600											
Paint	Solvent	Urethane Floor Coating	Rough	Concrete	Gloss	Safety Red, Safety Orange, Safety Blue, Safety Green, Safety Yellow, White	170 to 270 sq ft/gal	1 gal	93 g/L, 80 g/L, 96 g/L, 95 g/L, 97 g/L	72 hr	H7195
	Water	Urethane Floor Coating	Rough	Concrete	Gloss	Silver Gray	170 to 270 sq ft/gal	1 gal	107 g/L	72 hr	H7195
Concrete Saver AS5600											
Base	Water	Anti-Slip Floor and Deck Coating	Rough, Smooth	Concrete, Metal	Gloss	Safety Yellow, Black, Navy Gray	70 to 125 sq ft/gal	1 gal	36 g/L, 54 g/L, 52 g/L	24 hr	H7191
High Performance											
Base	Solvent	Polyurethane Coating	Smooth	Metal	Semi-Gloss	Gray	12 to 13 sq ft/gal	15 oz	—	10 to 20 min	29EK24
High Performance 3800											
Base	Water	DTM Coating	Rough, Smooth	Concrete, Masonry, Metal, Steel	Gloss	White, Navy Gray, Black, Safety Red, Safety Yellow, Safety Green, Safety Blue, Silver Gray, Dunes Tan, Forest Green, Safety Orange	150 to 270 sq ft/gal	1 gal	Less Than 250 g/L	15 min	J6597
	Water	DTM Coating	Rough, Smooth	Concrete, Masonry, Metal, Steel	Gloss	White, Navy Gray, Black, Safety Red, Safety Yellow, Safety Green, Safety Blue, Silver Gray, Dunes Tan, Forest Green, Safety Orange	150 to 270 sq ft/gal	5 gal	Less Than 250 g/L	15 min	J6598
Industrial Choice											
	Solvent	Anti-Slip Coating	Rough, Smooth	Ceramic, Concrete, Metal, Wood	Anti-Slip	Yellow, Black, Clear	14 sq ft/can	15 oz	555 g/L, 573 g/L, 570 g/L	24 to 48 hr	H7167
Mathys											
Base	Water	Acrylic Elastomeric Coating	Rough, Smooth	Concrete, Metal, Steel	Satin	Off White, Blue Gray, Beige Gray, Reseda Green, White, Black, Red, Gray Green, Gravel Gray, Brown	550 sq ft/gal	5 gal	40 g/L	1 hr	J0583
Sierra Performance											
Base	Water	DTM Coating	Smooth	Aluminum, Galvanized Steel, Metal	Gloss	Black	175 to 545 sq ft /gal	5 gal	0 g/L	30 min to 1 hr	21CK03
	Water	DTM Coating	Smooth	Aluminum, Galvanized Steel, Metal	Gloss	Safety Yellow	175 to 545 sq ft /gal	5 gal	0 g/L	1 hr	21CJ98
	Water	DTM Coating	Smooth	Aluminum, Galvanized Steel, Metal	Gloss	White	175 to 545 sq ft /gal	5 gal	0 g/L	1 hr	21CJ95
	Water	DTM Coating	Smooth	Aluminum, Galvanized Steel, Metal	Gloss	White, Safety Red, Safety Yellow, Safety Blue, Navy Gray, Black, Clear	175 to 545 sq ft /gal	1 gal	0 g/L	1 hr	H7187
	Water	DTM Coating	Smooth	Aluminum, Galvanized Steel, Metal	Semi-Gloss	Black, Safety Yellow, Safety Red	135 to 265 sq ft/gal	1 gal	Less Than 50 g/L	30 min	F8747
	Water	DTM Coating	Smooth	Aluminum, Galvanized Steel, Metal	Semi-Gloss	Navy Gray, White Pastel, Safety Blue	137 to 513 sq ft/gal	1 gal	Less Than 50 g/L	30 min	F8747
	Water	DTM Coating	Smooth	Aluminum, Galvanized Steel, Metal	Satin	Black	135 to 265 sq ft/gal	1 gal	Less Than 50 g/L	30 min	34UL42
	Wooster Safe-Stride SSA										
Base	Water	Anti-Slip Coating	Rough	Concrete, Metal, Wood	Flat	Safety Yellow	100 to 125 sq ft/gal	1 gal	VOC Free	4 hr	2TVCS
Unspecified											
Base	—	Anti-Slip Coating	Rough	Concrete, Metal, Wood	Flat	Black	100 to 125 sq ft/gal	1 gal	—	4 hr	1AJZ3
Base	—	Anti-Slip Coating	Rough	Concrete, Metal, Wood	Flat	Gray	100 to 125 sq ft/gal	1 gal	—	2 to 4 hr	3JW47



High Temperature Coatings

These coatings protect metals exposed to high heat from oxidizing, corroding, peeling, and other processes of degradation. They are commonly used to improve the thermal efficiency of heaters, furnaces, and ovens.



Aluminum J1516



Aluminum J1517



Blue 38ER23



White 55JM64

►CHOOSE: Color	Surface Material	Use Location	Maximum Temperature Resistance	Base Type	Dry Time	Coverage Area	Container Size	Container Type	Brand	Item No.
Aluminum, Black	Metal	Exterior, Interior	400 °F	Solvent	1 to 2 hr	250 to 540 sq ft/gal	1 gal	Can	Rust-Oleum	J1515
	Metal	Exterior, Interior	800 °F	Solvent	1 to 2 hr	190 to 515 sq ft/gal	1 gal	Can	Rust-Oleum	J1516
	Metal	Exterior, Interior	1,200 °F	Solvent	1 to 2 hr	250 to 560 sq ft/gal	1 gal	Can	Rust-Oleum	J1517
Aluminum	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER21
	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER22
	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER23
Cast Iron	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER20
	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER32
	Metal	Exterior, Interior	1,200 °F	Solvent	1 to 2 hr	7 to 8 sq ft/can	12 oz	Aerosol	Rust-Oleum	36RD96
Orange	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER26
	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER27
	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER28
White	Cellulose Tile, Cured Plaster, Drywall, Masonry, Metal, Wood	Interior	250 °F	Latex	30 min	150 sq ft/gal	1 gal	Can	INSL-X by Benjamin Moore	55JM64
	Cellulose Tile, Cured Plaster, Drywall, Masonry, Metal, Wood	Interior	250 °F	Latex	30 min	150 sq ft/gal	5 gal	Can	INSL-X by Benjamin Moore	55JM65
Yellow	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER29
	Metal, Steel	Exterior, Interior	2,000 °F	Solvent	1 to 3 hr	12 sq ft/can	11 oz	Aerosol	VHT	38ER31

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**