



Color Additive 19N209



Anti-Skid Additive 6A936



Boiled Linseed Oil 44ZU21



Coating Durability Additive 30RM15



Paint Solidifier 2AJN4



Leveling & Conditioning 44ZU19



39UL63

Paint Additives

■ Exterior, interior use

Color Additives—Mixed into paint bases and floor coatings to tint the paint or coating to a custom color. These paint tints and coating tints enhance the beauty of painted or coated surfaces by adding color.

Anti-Skid Additives—When mixed with epoxy, latex or oil-based paints, stains, or sealers, create a skid-resistant coating for concrete, wood, metal, or fiberglass. Made from aluminum oxide, these additives are frequently used on industrial stairs, decks, and walkways.

Boiled Linseed Oil—Both a thinner for oil-based paints and a coating. As a thinner, it improves the flow and gloss of oil-based paints. As a coating, it creates a shiny hand-rubbed finish on wood and furniture. It increases wood's resistance to watermarks, scratches, and warping.

Coating Durability Additives—Traditionally used to improve pigment wetting and reduce foaming during processing. These additives improve flow and leveling and substrate wetting during application.

Base Type	Color	Coverage Area	Container Size	Brand	Item No.
Anti-Skid Additives					
Oil, Water	Clear	—	16 oz	H&C	38EK69
	Clear	—	19 lb	H&C	38EK72
Polypropylene	Clear	1 lb; 5 gal	1 lb	Rae	19N18
	Clear	1 lb; 5 gal	15 lb	Rae	19N19
Pumice	Off-White	0.5 pt/qt	8 oz	Rust-Oleum	2GXE1
Silica	Off-White	1 lb/gal	1 lb	Rust-Oleum	6A936
	Clear	16 oz/gal	16 oz	Homax	29UR95
Boiled Linseed Oils					
Oil	Amber	80 sq ft	1 gal	Sunnyside	44ZU21
	Amber	400 sq ft	5 gal	Sunnyside	487F10
Coating Durability Additives					
Aluminum Oxide	White	1 lb/gal	1 lb	Rust-Oleum	35J83
Thermoset Polymer Resin	White	0.5 lb/gal	0.5 lb	Rust-Oleum	30RM15
Paint Solidifiers					
Sodium Polyacrylate	Clear	3/4 gal	3.5 oz	Homax	2AJN4
Sodium Polyacrylate, Sodium Potassium Alumina Silicate	White	Absorbs Up to 3 gal	2 L	XSORB	3VY28
	White	Absorbs Up to 25 gal	4 gal	XSORB	3VZA3
Potassium Alumina Silicate	White	Absorbs Up to 38 gal	23 lb	XSORB	21YX75
	White	Absorbs Up to 38 gal	23 lb	XSORB	21YX75
Leveling & Conditioning Additives					
Water	Blue	2 to 6 oz/gal	1 qt	M-1	44ZU19

Floor Chips

■ Interior use

Decorative polymer floor flakes are specially formulated paint aggregates used to enhance the aesthetic qualities of seamless, resin-based chip/flake flooring systems. Sprinkle the chips directly onto the wet epoxy coating, then finish with a clear top coat.

Color	Coverage Area	Container Size	Item No.
Black/Blue/White	0.002 lb/sq ft	1 lb	39UL63
Black/Gray/White	0.002 lb/sq ft	1 lb	39UL68
Black/White	0.002 lb/sq ft	1 lb	39UL66
Blue/White	0.002 lb/sq ft	1 lb	39UL69



Drywall Spray Textures

A full range of wall textures for convenient, invisible repair.

2AUT7



39F173



4HFE7



Ceiling Aerosols

Covers Up Paint—Low-odor, vertical aerosol spray sealer and finish for drop ceilings with water, smoke, and nicotine stains. Nonyellowing flat finish.

Bondex Ceiling Patch—Ready-mixed, latex-based, low-odor patching compound duplicates the look of popcorn (acoustic) ceiling finishes; repairs blemishes, scrapes, and water damage.

DRY TIME AND COVERAGE	
Paint	Patch
Dry Time: 1 hr	24 to 48 hr
Coverage: 12 to 15 sq ft	†

† Dependent on ceiling aggregate.

Color	Net Wt.	Size	Item No.
Covers Up Paint			
White	13 oz	—	4HFE7
Bondex Ceiling Patch			
White	—	1 qt	4HFG1

Description	Base Type	Net Wt. (oz.)	Color	Covers (sq. ft.)	Dry Time	Item No.
Orange Peel Wall Texture	Oil	10 oz	White	50 sq ft	5 min	2AUT7
	Oil	20 oz	White	110 sq ft	5 min	2AUT8
	Oil	25 oz	White, Tinted	125 sq ft	5 min	39F172
	Water	16 oz	Sprays on Blue, Dries White	90 sq ft	30 min	2AUT9
	Water	25 oz	White, Tinted	125 sq ft	30 min	39F173
	Water	25 oz	White, Tinted	75 sq ft	30 min	39F174
Knockdown Wall Texture	Water	25 oz	White	8 sq ft	24 hr	45MV56
Popcorn Ceiling Texture	Water	20 oz	White	110 sq ft	30 min	444F40
Wall Textured Spray Patch	Water	20 oz	White	110 sq ft	30 min	444F42