

Heat Activated Pavement Markings

Envy

Thermoplastic pavement marking paints clearly mark traffic lanes, legends, symbols, and road boundaries on roads, parking lots, and other paved surfaces. They are thicker and more wear resistant than other types of marking paints. These paints are heated and applied to paved surfaces to increase visibility and provide long-term wear. Line rolls come in a variety of colors for varied road and pavement needs. These rolled strips can be applied to any roadway to delin-

Legend	Color		Width	Thickness		Maximum Application Temperature	ltem No.
Pavemen	it Pre-Deteri	nined M	essages				
Handicap	Blue	38"	3-ft	90 mil	_	300 °F	18E570
	Blue/White	45*	45"	90 mil	_	300 °F	18E572
Pavemen	t Line Rolls						
Rolls	Yellow	30-ft	4"	90 mil	32 °F	275 °F	18E661
	Yellow	30-ft	6"	90 mil	32 °F	275 °F	18E667
	Yellow	30-ft	12"	90 mil	32 °F	275 °F	18E669

needs. These rolled strips can be applied to any ro eate the lanes and keep traffic flowing.



Paint Thinners

sunnyside

These liquid paint thinners reduce the viscosity of paint.

General Purpose Paint Thinners—Solvents used to thin or reduce the viscosity of paints to prepare them for spray application or to clean up after their use.

Mineral Spirits—Petroleum-derived clear liquids used as a common organic solvent in cleaning up after painting. Mineral spirits are less expensive than turpentine and thin oil-based paints, stains and varnishes.

Lacquer Thinners—A mixture of solvents able to dissolve a number of different resins or plastics used in lacquer finishes. They clean tools and equipment after a lacquer project.

Materials Remover

Xylene Thinners—Used for thinning paints, enamels, varnishes, and alkyd resins. They are

highly flammable and are recommended for ventilated or exterior use. Toluene paint removers are fast-drying solvents for thinning oil-based paints, varnishes, enamels and alkyd resins.

Xylol Thinners—Used for thinning paints, enamels, varnishes, and alkyd resins. Often specified as a thinner for specialty paints and coatings, xylene is highly flammable and is recommended for ventilated or exterior use.

Water Immersion Coatings—Protective layers that are applied to a material that will be subjected to water or liquid for an extended period of time. Thinners for immersion coatings reduce the viscosity of the coatings so that it can be spray-applied instead of brushed or rolled onto a surface. This is commonly done for surfaces that are not flat or are uneven.

ided for int removers oil-based	RUSTOLEUM RUSTOLEUM 333 333 Marcinet Alexandre Marcinet Alexa		Sunnyside Sunnyside Methods		
l resins. paints,	General Purpose	Mineral Spirits	Lacquer Thinner		
. Often	3JR74	5KPY3	5KPY2		
aints and and is ior use. ective that will extended on coat- ngs so that ushed or evideo for	Autoritation Sunnyside SyleneAlouene Helenearent Constantion SyleneAlouene SyleneAloue	Sunnyside Exercise Market Mark			
nly done for	Xylene/ Toluene	Xylol Thinner 5KPY4	Water Immersion 6H076		
en.	12H847	JRF 14			
15	Strength	Container Container Type Size	ltem Brand No.		

Materials hemoved	Guillania	Juciyu	Type	0126	Diallu	NU.
General Purpose Paint Thinners						
Oil Base Type						
Dirt, Grease	LVP Mineral Spirits		Bottle	1 gal	Sunnyside	499H70
Dirt, Grease	LVP Mineral Spirits	Regular	Pail	5 gal	Sunnyside	499H58
Solvent Base Type				, v	,	
9400 System, Adhesive, Epoxy Coating, Grease, Oil, Urethane Coating	Ethyl 3-Ethoxypropionate, Ethyl Acetate, Methyl Ethyl Ketone	Regular	Can	1 gal	Rust-Oleum	5H949
Alkyd Coating, Epoxy Coating, VOC Compliant Products	Acetone	Regular	Can	1 gal	Rust-Oleum	3JR74
Alkyd Coating, Industrial Enamel, Latex Coating	n-Nonane, Naphtha, Pine oil	Regular	Can	1 gal	Rust-Oleum	5H887
Alkyd Coating, Latex Coating	n-Heptane, Naphtha, Octane, Pine oil	Regular	Can	1 gal	Rust-Oleum	5A261
Dirt, Grease	Acetone, Aliphatic Naphtha	Regular	Can	1 gal	Sunnyside	499H54
Paint, Solvent Based Products	Parachlorobenzotrifluoride	Regular	Can	1 gal	Rust-Öleum	426J32
Water Base Type		· · ·		, v		
Paint	Dipropylene Glycol Monomethyl Ether, Naphtha, p-Chloro-	Regular	Bottle	1 gal	Green Envy	5KPY0
	a,a,a-Trifluorotoluene, Sodium Dioctyl Sulfosuccinate	rioguiai	Bottio	i gui	ditton Entry	010110
Mineral Spirits						
Oil Base Type						
Dirt, Grease	Mineral Spirits	Regular	Can	1 gal	Sunnyside	5KPY3
Dirt, Grease	Mineral Spirits	Regular	Pail	5 gal	Sunnyside	44ZU14

Contain

Sign in to Grainger.com® to see YOUR Pricing and MORE

CONTINUED