

## **Roof Coatings**

Acrylic Roof Coatings are liquid-applied seamless coatings that are sprayed or rolled onto a roof surface. Coatings turn white as they dry and adhere strongly to the areas where they are applied. They work well on pitched or steep-sloped roofs where they reflect sunlight, reducing heat transfer into buildings. These coatings also repel water and moisture for the life of the coating. Acrylic coatings are a short-lifecycle, low-cost roof coating option.

Asphalt Roof Coatings are two-course processes applied to preserve the surface of a roof and it make it durable. Asphalt creates seamless, pliable waterresistant protection and levels irregularities on roof surfaces. The second coating is a protective to coat that repels moisture and UV rays. These coatings can be applied by spray, brush or paint rollers.

Base







Aluminum Coatings help improve buildings' energy efficiency at a lower price than acrylic coatings. These coatings are highly reflective and can lower roof temperatures and repel ultraviolet rays away from the surface.

Silicone Roof Coatings are spray-applied onto a flat roof surface to repair cracks, blisters, and seams. These coatings increase protection from the elements and stop ponding water from seeping into roof substrates and causing leaks. Silicone lasts longer than other roof coatings, standing up to bad weather and high heat throughout its lifecycle.

Roof Accessory Paints are professional-grade roof spray paints that closely match the original color of most roofing materials. They resist fading and protect against rust. For use on fascia, flashing, gutters, soffits, and vent pipes.



Coating 40P312



**Asphalt Roof** Coating 53PZ33



**Aluminum Roof Coating** 35LR67

Henry

Silicone Roof Coating 411M23



Roof Accessory **Paint** 55ER25

	Type	Reflective	Color	Coverage Area	Size	Dry Time	Cure Time	VOC Content	Sub Brand	Brand	No.
	Type nemetive Color Coverage Area Size bly Time Cure Time Voc Coment Sub Brand Brand No.										
	crylic n	No	Grav	50 to 100 sq ft/gal	4.75 gal	4 to 12 hr	24 hr	16 a/L	Kool-Lastick	Kool Seal	4FJK1
		Yes	White	50 to 100 sq ft/gal	4.75 gal	24 hr	24 hr	50 g/L	KUUI-Lasiick	Kool Seal	36MV74
V	Vater -	Yes	White	50 to 100 sq ft/gal	4.75 gal	6 hr	24 hr	Less Than 16 g/L	Blu2White	Kool Seal	4EEZ7
De	oof Coa		vviiite	30 to 100 sq 11/gai	4.75 yai	0 111	24 111	Less IIIaii 10 g/L	DIUZVVIIILE	NUUI Seai	40027
) nu	JUI GUA	No	Gray	100 sq ft/qal	4.75 gal	4 to 24 hr	24 hr	32 g/L	Advanced	Rust-Oleum	55ER58
J		No	White	100 sq ft/gal	0.9 gal	2 to 24 hr	2 to 24 hr	50 g/L	Dura-Brite	Henry	40P313
			White	100 Sq II/gal	0.9 gal	2 to 24 hr	2 to 24 III	50 g/L 50 a/L			40P313 40P311
		No No	White	100 sq ft/gal 100 sq ft/gal		2 to 24 hr	2 to 24 III	50 g/L 50 g/L	Enviro-White Solar-Flex	Henry	40P311 40P315
		No	White	100 sq ft/gal	0.9 gal 4.75 gal	2 to 24 hr	2 to 24 III	50 g/L 50 g/L	Dura-Brite	Henry Henry	40P314
V	Vater -		White	100 Sq II/gal	4.75 gal	2 to 24 hr	2 to 24 III	50 g/L 50 g/L	Enviro-White		40P314 40P312
		No No	White	100 sq ft/gal 100 sq ft/gal	4.75 gal	2 to 24 hr	2 to 24 III	50 g/L 50 g/L	Solar-Flex	Henry	40P312 40P316
			White							Henry	55ER50
		No		100 sq ft/gal	4.75 gal	6 to 24 hr	24 hr	35 g/L		Rust-Oleum	
		Yes	White	50 to 100 sq ft/gal	4.75 gal	6 hr	24 hr	Less Than 16 g/L		Kool Seal	4FJJ9
		Yes	White	100 sq ft/gal	4.75 gal	2 hr	2 to 24 hr			Henry	40P310
K	oof Sea		14/1 11	40.5 (1/ )		0.1	4. 7.				400000
V	Vater -	Yes	White	12.5 sq ft/gal	1 gal	2 hr	1 to 7 day			Henry	40P306
		Yes	White	12.5 sq ft/gal	10 oz	2 hr	1 to 7 day			Henry	40P305
		Roof Coatings									
	olvent	No	Silver	15 to 25 sq ft/gal	1 gal	24 hr	1 to 3 day	359 g/L	Storm Patch	Kool Seal	36MV75
Ro	oof Cen			10 5 61 1					-		
	Oil ·	No	Black	12.5 sq ft/gal	3.5 gal	30 day	30 day	300 g/L	Flashmaster	Henry	35LR65
		No	Black	12.5 sq ft/gal	5 gal	12 to 24 hr	30 day	300 g/L	Flashmaster	Henry	53PZ34
Re	oot Lea	k Repair									
		No	Black	12.5 sq ft/gal	0.9 gal	2 to 24 hr	30 day		Extreme Wet Patch	Henry	40P303
1		No	Black	12.5 sq ft/gal	0.9 gal		30 day	300 g/L	Wet Patch	Henry	40P298
	Oil	No	Black	12.5 sq ft/gal	3.3 gal	_	30 day	300 g/L	Wet Patch	Henry	40P299
		No	Black	12.5 sq ft/gal	10.1 oz		30 day	300 g/L	Wet Patch	Henry	40P297
		No	Black	12.5 sq ft/gal	10.1 oz	2 to 24 hr	30 day	300 g/L	Wet Patch	Henry	40P302
	olvent	No	Black	12.5 sq ft/gal	5 gal	12 hr	30 day	300 g/L	_	Henry	53PZ33
		l Adhesive									
	olvent	No	Black	50 sq ft/gal	5 gal	24 hr	1 to 7 day	300 g/L	_	Henry	35LR66
Ro	oof Sea										
1	Vater	No	Black	3 to 100 sq ft/gal	4.75 gal	6 to 24 hr	1 to 7 day	0 g/L	_	Henry	40P308
		No	Black	100 sq ft/gal	0.9 gal	6 hr	1 to 7 day	0 g/L	_	Henry	40P307
		n Roof Coatin	igs								
Ro	oof Coa										
C.	olvent	No	Gray	40 to 50 sq ft/gal	4.75 gal	24 hr	10 to 12 day	389 g/L	_	Rust-Oleum	55ER55
		INO	Gray	50 sq ft/gal	4.75 gal	24 hr	10 to 12 day	397 g/L	_	Rust-Oleum	55ER39
	Vater	No	Silver	100 sq ft/gal	5 gal	2 to 24 hr	2 to 24 hr	50 g/L	Aqua-Brite	Henry	35LR67
Si	licone	<b>Roof Coating</b>	S		-			-			
	olvent	Yes	White	100 sq ft/gal	1 gal		1 hr	Less Than 10 g/L	Tundra	Kool Seal	411M22
	oof Coa	tings			-			•			
S	olvent	Yes	White	100 sq ft/qal	5 gal	_	1 hr	Less Than 10 g/L	Tundra	Kool Seal	411M23
	oof Sea	lants									
S	olvent	Yes	White	6 sq ft/gal	1.9 gal		48 hr	25 g/L	Pro-Grade	Henry	54EP12
		cessory Paint		tings							
		ch-Up Paints		_							
		No	Bronze	10 to 12 sq ft/can	12 oz	20 min to 1 hr	24 hr	584 a/L	_	Rust-Oleum	55ER25
	0il	No	White	10 to 12 sq ft/can	12 oz	20 min to 1 hr	24 hr	549 g/L	_	Rust-Oleum	55ER26
_					02			- · - g/ L		0104111	







## **Roof Repair Fabrics**

Used for waterproofing and reinforcement, they are generally used as a part of a three-course roof coating application process that includes base coats and finishers (see coatings on this page). These fabrics include fiberglass cloths and polyester-blend fabrics.

Resin Type	Color	Coverage Area	Properties	Brand	No.	
Polyester	White	4 in x 150 ft/roll	Puncture Resistant	Henry	40P309	
Polyester	White	6 in x 300 ft/roll	_	Rust-Oleum	55ER02	
Resin Coated Glass Fabric	Yellow	6 in x 25 ft/roll	Acid Resistant	Henry	40P301	
	White	4 in x 300 ft/roll	_	Rust-Oleum	55ER08	

## **Roof Patching & Repair Products**

hardens, cracks, peels or shrinks.

Container

KOOLSEAL Kool Seal Acrylic Patching Cement—Stops leaks on damp or dry surfaces. Blends in on existing white roofs.

Storm Patch All-Weather Rubberized Cements— Displace water from wet surfaces and create a tight seal.

Flexx Sealer Permanent Leak Repair—Bonds immediately, seals instantly to clean dry surface. Never

Description	Container Type	Size	Color	Item No.			
	tching, Plugging, and Joint Compounds						
Kool Seal Acrylic Patching Cement	Tube	10.5 oz	White	4FJK6			
Kool Seal Acrylic Patching Cement	Can	115 oz	White	4FJK7			
Storm Patch All-Weather Rubberized Cement Patch	Tube	10 oz	Clear	4FJK3			
Storm Patch All-Weather Rubberized Cement Patch	Tube	10.5 oz	Black	4FJK4			
Leak Repair							
Flexx Sealer Leak Repair and Sealer Roll	Roll	2 in x 10 ft	Gray	4FJL1			
Flexx Sealer Permanent Leak Repair Strip	Roll	2 in x 3 ft	White	4FJK8			









