

PAINTING Concrete Patch & Repair



40P317

Henry #1 CHOICE OF PROFESSIONALS Driveway Asphalt and Coating

Asphalt Resurfacer—Fills and seals rough surfaces and cracks in asphalt driveways. Features a 7x rubberized formulation for long life and durability. Stir gel formula applies easily and durably. Stir gel formula applies easily, dries quickly, and reduces tracking.

E-Z Stir Asphalt Filler/Sealer—Do-it-yourself, easy-to-use formula stirs and applies easily. Reinforced for improved traction and durability.

Top-Kote Asphalt Coating—Smooths, preserves, and protects weathered asphalt driveways. Renews and gives a black appearance to surfaces.

Asphalt Pothole Patch—Use this solvent-based asphalt and aggregate compound to fill larger cracks and potholes. All-weather formula requires no mixing.

Asphalt Coating—Brush-applied sealcoat is ideal for home use. Stirs and applies easily.

Description	Container Size	Flash Point	Dry Time	Recoat	Coverage	Item No.
Asphalt Resurfacer	4.75 gal	212°F	4 hr		250 to 500 sq ft	40P317
E-Z Stir Asphalt Filler/Sealer	4.75 gal	212°F	4 hr		250 to 500 sq ft	40P318
Top-Kote Asphalt Coating	4.75 gal	212°F	4 hr		300 to 400 sq ft	40P319
Asphalt Pothole Patch	11 lb	170°F	Immediately After Compacting		2 sq ft x 1 in	40P320
Asphalt Coating	55 gal	212°F	4 hr		2200 to 4400 sq ft	35LR68

Concrete Mixes

■ 50 lb. pail

Formulated with sand, gravel, and cement for repair and building jobs where concrete is more than 2" thick.

21HC53 sets posts and poles easily without blending. Sets in 30 min.

21HC52 includes fibers that help resist cracking due to shrinkage.

21HC54 achieves 5000 psi strength. Also good for use in concrete countertops.

21HC55 is a general purpose concrete mix with a strength of 4000 psi.



21HC54

Description	Meets	Mr. Model	Item No.
Fast Setting Concrete Mix	ASTM C-387 and ASTM C-270	120019	21HC53
Crack Resistant Concrete Mix	ASTM C-387	120018	21HC52
5000 Plus High Strength Concrete Mix	ASTM C-387	120020	21HC54
High Strength Concrete Mix	ASTM C-387	120021	21HC55



39H820



39H819

CRACK-STIX Crack Stix Permanent Concrete & Asphalt Joint & Crack Filler

Easy to use with no mixing: Cut pliable cord to length, hand-pack, and heat with a propane torch. It melts instantly and cures quickly, accepting traffic in less than 20 min. Creates a permanent watertight bond.

Container Size	Coverage	Color	Mr. Model	Item No.
Concrete				
10 lb	125 ft @ 1/2 in x 1/2 in	Gray	2051	39H820
10 lb	225 ft @ 1/4 in x 1/4 in	Gray	2061	30WM10
Asphalt				
8 lb	125 ft @ 1/2 in x 1/2 in	Black	2050	39H819
10 lb	250 ft @ 1/4 in x 1/4 in	Black	2060	30WM09

1632 **GRAINGER**

Find even **MORE** on **Grainger.com**®

Scan. Order. Done.
Details on page A1.



21HC50



52VY64



Concrete Cleaners and Dissolvers

Concrete and Asphalt Cleaner—Mild, acidic liquid used to clean concrete, masonry, and asphalt surfaces. Use to clean existing surfaces prior to making repairs.

Concrete Mortar Disolver—A safe, environmentally-friendly liquid alternative to aggressive acid concrete removers. Used to remove dried on cement, concrete, mortar, or stucco from most surfaces.

Description	Container Size	Item No.
Concrete and Asphalt Cleaner	1 qt	21HC50
Concrete Mortar Disolver	28 oz	52VY64



15F518



Tinted Concrete Mixes

TintCrete Resurfacer—Resurface or patch concrete with this colored resurfacing material. Trowel, broom, or brush onto existing concrete.

TintCrete Patch—Polymer-modified colored mortar formula withstands up to 4500 psi to resist cracks under rugged conditions.

TintCrete Concrete—Repair horizontal or formed areas with pourable colored concrete. Use to patch and repair concrete from 1" to full depth.

Color	Starts to Harden	Mr. Model	Item No.
TintCrete Resurfacer, 50 lb			
Beige	30 min to 1 hr	GRA-DLC-21	15F511
Gray	30 min to 1 hr	GRA-DLC-16	15F520
TintCrete Patch, 50 lb			
Beige	20 to 40 min	GRA-CT40-121	15F512
Black	20 to 40 min	GRA-CT40-151	15F518
Gray	20 to 40 min	GRA-CT40-160	15F521
TintCrete Concrete, 65 lb			
Black	45 min to 1.5 hr	GRA-P38-1510	15F519
Red	45 min to 1.5 hr	GRA-P38-1310	15F516



6Z173



Rockite Expansion Cement

Develops a compression strength of 4500 lb./sq.-in. within 1 hr. For applications such as anchoring bolts, buildings, partitions, machines, appliances, tools, railings, hardware, and posts to concrete and other masonry floors and walls.

Starts to Harden	Container Size	Mr. Model	Item No.
15 min	5 lb	10005	6Z173
	10 lb	10010	6Z174
	50 lb	10051	6Z175



6ZFY3

Polymeric Jointing Sand



For use with concrete pavers, cast stone, and natural stone products in patio, walkway, and driveway applications.

Material fills the joints between pavers, to help prevent weed growth and sand erosion due to rain or water run off.

Color	Container Size	Container Style	Item No.	Pkg. Qty.
Tan	50 lb	Bag	6ZFY3	8
Gray	50 lb	Bag	6ZFY4	8

1-800-GRAINGER (472-4643)