



100% Solids Flexible Joint Sealant

2-component polyurea cures in 90 min. Designed to control joints in mild to severe industrial environments. For interior and exterior use.

Container Size	Coverage	Item No.
9 oz	5.5 sq ft	38W370
22 oz	13.3 sq ft	38W371

4AUX7



39UV63



3EGC5



Concrete Crack Repair

PC Products—2-component epoxy gel works in temps, up to 115°F. Solvent-free and odor-free formula has a working time (20 min. at 75°F); paintable after 4-hr.

Sakrete—39UV52 is a flowable material designed to fill and seal cracks in concrete up to ¼"W and ¼"D. 39UV63 is trowelable and used for filling and sealing cracks in concrete up to 1" wide.

DAP—Self-leveling for horizontal applications; for interior and exterior use.

FlexKrete—Dual Component, 600 ML total when mixed cartridge with static mixing tube.

Titebond—High-performance self-leveling polymer sealant fills contraction/expansion joints and cracks in concrete decks and floors. Low VOC.

Prospec—Clear, non-yellowing, acrylic polymer membrane ideal for curing, sealing, and hardening of concrete, terrazzo, brick, and other cementitious materials.

Item	Application	Size	Full Cure Time	Coverage	Mfr. Model	Item No.
PC Products						
Concrete Rebar and Patch	Use to Anchor Bolts/ Cracks In Concrete	8.6 oz.	4 hr	—	072561	4AUX7
Concrete Rebar and Patch	Cracks In Concrete	102 oz.	4 hr	25.7 sq ft	071021	4AUY2
Epoxy Adhesive	Use to Anchor Bolts/ Rebar and Patch Cracks in Concrete	2.8 oz	4 hr.	4 hr.	070505	25F532
Epoxy Adhesive	Rebar and Patch Cracks in Concrete	1.69 oz	4 hr.	4 hr.	070529	25F533
Sakrete						
Concrete Crack Repair	Concrete Repair	1 qt.	1 day	35 ft @ ¼ in x ½ in	120026	39UV52
Pre-Mixed Concrete Patch	Concrete Repair	1 qt.	2 days	3 sq ft @ ½ in	120547	39UV63
DAP						
Liquid Cement Crack Filler	Repairs Cracks and Surface Defects In Concrete, Self Leveling, Ready-Mixed Formula	1 qt.	1 hr	—	37584	1LYG4
Flexkrete						
Polyurea Sealer, Concrete	Used As A Filler For Joints And Cracks	600mL Cartridges	—	—	FK-PS100 Kit	3EGC5
Titebond						
Self-Leveling Concrete Floor Joint Sealant	Construction/Expansion Joints and Cracks In Concrete Decks and Floors	10.1 oz.	1 day	31 ft @ ¼ in x ¼ in	3191	2GXU1
Tenon						
Sealer	Commercial/Residential, Interior/Exterior, Masonry	1 gal.	4 hr	300 sq ft	120823	487A67
Sealer	Commercial/Residential, Interior/Exterior	5 gal.	4 hr	1500 sq ft	120822	487A68
Prospec						
Sealer	Commercial/Residential, Interior/Exterior	—	4 hr	16,500 sq ft	120824	487A69
Item	Application	For Use With	Mfr. Model	Item No.	Pkg. Qty.	
PC Products						
Static Mixing Nozzle	For Dispensing Concrete And Crack Repair	Mfr. No. 072561	072226	4AUX8	2	



Joint and Crack Repair

1500SL joint and crack repair is a high-performance, one-part, moisture curing, self-leveling sealant for concrete, masonry, or asphalt joints. Non-gassing property makes it ideal for high temperatures and humid conditions. Starts to harden in 2 hr. and fully cures in 3 days. Remains flexible and is resistant to UV rays.

Color	Coverage	Container Size	Mfr. Model	Item No.
Gray	11.2 to 67.4 Linear ft	28 fl oz	GC99902	488H53



453T09



Refracting and Masonry Mortars

Refractory mortars are used for laying fire brick. Temp. range of 40° to 100°F. Masonry mortar is used for tuck pointing mortar joints. Temp. range of 40° to 90°F. Mortars are gray in color.

For Use On Surface Material	Coverage	Container Size	Starts to Harden	Brand	Mfr. Model	Item No.
Refractory Mortar						
Brick,	0.5 cu ft	10 lb	1 hr	Prospec	120913	453T09
Concrete, Stone, Wood	0.13 cu ft	50 lb	1 hr	Akona	104319	453T08
Masonry Mortar						
Masonry	21 sqft @ ½ in, 25 sq ft @ ½ in, 35 sq ft @ ¾ in	50 lb	2.5 hr	JE Tomes	N-3	64UX18

39UV48



1LYG7



Concrete Patching

Sakrete Concrete Patch—Top 'n Bond patcher is a polymer-modified sand and cement repair mortar for resurfacing, patching, and general concrete repairs from featheredge to ½". Requires only the addition of water.

DAP Concrete Patch—Nonshrinking ready-mix dries to hard finish. For interior/exterior use.

Application	Full Cure Time	Container Size	Mfr. Model	Item No.
Sakrete Concrete Patcher				
Concrete Repair	2 days	10 lb	120031	39UV64
Concrete Repair	1 day	50 lb	120032	39UV48
DAP Concrete Patcher				
Patch Cracks and Breaks	1 day	1 gal	31090	1LYG7



Concrete Patching Compound

■ 5499 system

2-component system: must use base and activator. Repairs cracks and damaged areas. No priming required. Accepts light foot traffic in 12 hr. Activator included. 100% solid.



Container Size	Color	Coverage	Item No.
2 gal	Gray	12.5 sq ft @ ½ in	5A279