



15F502



### Fast Set 10-Minute Concrete Repair Compound

Permanently repairs cracks, spalls, concrete and deteriorated concrete. Can be applied in sub-zero temperatures.

15F502 includes 2 pints each of Concrete Mender Parts A and B, 17 lb. of aggregate, plastic trowel, rubber gloves, mixing bucket, and 3 lb. of dry latex concrete resurfacer.

15F504 includes 2 Concrete Mender cartridges, 2 flow controllers, 2 static

mixing tips, 10 lb. of aggregate, plastic trowel, rubber gloves, and 3 lb. of dry latex concrete resurfacer.

15F507 includes Concrete Mender cartridges, 15 flow controllers, and 15 static mixing tips.

Container Size	Mfr. Model	Item No.
1.5 gal	JET-28	15F502
2 Cartridge Kit	JET-2	15F504
12 Cartridge Kit	JET-12	15F507



64UX16



### Concrete Sealers

White liquid is for use in concrete and masonry; dries clear and invisible. Starts to harden in 2 hrs. and cures in 1 to 2 days. Can be re-coated in 1 to 2 days.

Container Style	Container Size	Coverage	Item No.
Bottle	1 gal	100 to 300 sq ft	64UX16
Pail	5 gal	500 to 1500 sq ft	64UX17



### Concrete Repair

**InstaPatch Concrete Repair Kit**—2-component polyurea repair compound cures in less than 15 min. Can be applied in temperatures as low as -5°F. 100% solid.

**TurboKrete Epoxy Repair Kit & Nozzles**—Fast-curing, nonsag epoxy is used for vertical and horizontal repairs. 100% solid.

Description	Coverage	Includes	Item No.
<b>InstaPatch</b>			
Concrete Repair Kit	230 ft @ ¼ in x ¼ in	½ gal Part A and ½ gal Part B	30RK20
<b>TurboKrete</b>			
Epoxy Repair Kit, 9 oz. Cartridge			6DNX5
Static Mixing Nozzle, 3 Nozzles			6DNX6

30RK20



6DNX5



2VRN1

### Loctite PC9410 Magna-Crete

2-component, concrete repair and grouting system. Bonds to most common construction materials.

Container Size	Mfr. Model	Item No.
1 gal	235572	2VRN1
5 gal	235573	2VRN2

**Application**  
Compressive Strength 13,000 PSI, Rapid Setting, Chemically Resistant, Summer and Winter Additives Also Available to Aid Cure Times



6KP53



### TurboKrete Concrete Patching Kit

Repairs large cracks and deep holes. Can accept vehicular traffic in 6 to 8 hr. 3 to 4x stronger than concrete. 100% solid.

Description	Container Size	Coverage	Item No.
Small Kit	4 fl oz (Part B) Activator, 13.1 lb (Part C) Aggregate, 27.5 fl oz (Part A) Base	0.15 cu ft	5XPP2
Large Kit	8 fl oz (Part B) Activator, 26.25 lb (Part C) Aggregate, 55 fl oz (Part A) Base	7.5 sq ft	6KP53



### FlexKrete Concrete Repair and Primer

FlexKrete 102 mortar for long-term repair is 3x harder than concrete. Flex-Prime has excellent wet out properties blocking out moisture, providing deep penetration.



3EGA8

Application	Container Size	Color	Mfr. Model	Item No.
<b>FlexKrete 102 Concrete Repair Compound</b>				
Repair Concrete, Asphalt, Steel, Wood, Fiberglass, Marble, Build Ramps, Seamless Floors, Resurface Concrete, Repair Anchor Bolts, Vertical/Horizontal and Overhead Sites, Non-skid Surface, ADA, Bridge Repair, Drain Repair, Manhole Repair	1 gal	Gray	FK102G-KIT	3XJC3
	5 gal	Gray	FK-102G	3EGA8
	5 gal	Clear	FK-102C	3EGC1
<b>Flex-Prime Concrete Primer, 2-Component</b>				
Use As A Penetrating And Bonding Agent	(2) 1-gal. Jugs	Clear	FK-Primer	3EGC7



1LYG5



39UV65



15F530

### Hydraulic Cements

**Quick Plug**—Stops running water through deep cracks, holes, and imperfections in concrete surfaces, both above and below ground level.

**Hydraulic Cement**—Stops the flow of water through breaks in concrete or masonry walls and floors. Rapid setting with initial set-time of 1 to 3 min. and final set in 3 to 4 min.

**Concrete Foundation Repair Leak Stop, Anchoring**—Quickly stop active leaks, plug holes, repair foundation walls and anchor equipment.

Starts to Harden	Full Cure Time	Container Size	Mfr. Model	Brand	Item No.
<b>Quick Plug Hydraulic Cement</b>					
3 min	28 days	5 lb	14086	DAP	1LYG5
3 min	28 days	10 lb	14090	DAP	10L517
<b>Hydraulic Cement</b>					
3 min	2 days	50 lb	120030	Sakrete	39UV65
<b>Concrete Foundation Repair Leak Stop, Anchoring</b>					
3 min	1 hr	3 lb	C118	Hydro Plug	15F529
3 min	1 hr	10 lb	C120	Hydro Plug	15F530
3 min	1 hr	50 lb	C121	Hydro Plug	15F531



### Anchoring Cements

2-component system for repairing spalled or deteriorating concrete. Can be used for overhead repairs. Solvent-free, high-strength, high-modulus, moisture intensive repair epoxy.

Starts to Harden	Full Cure Time	Container Size	Mfr. Model	Item No.
15 min	4 hr	1 gal	071120	5UXR4