Feature a band with evenly spaced holes

on one end and pins on the other end that

Hard Hat ANSI Classifications

ANSI/ISEA-Z89.1-2014

Describes the impact resistance and electrical

fasten for a comfortable fit.

hard hat.

Pinlock

Impact and Electrical Insulation Classifications

Type I: Reduces the force of impact caused by a blow to the top of hazards. the head only.

of the head.

Class C - Conductive: Provides no protection from electrical

Class G - General: Provides low-voltage protection up to 2.2kV.

insulation properties of the Type II: Reduces the force of impact from a blow to the top or side Class E - Electrical: Provides high-voltage protection up to 20kV.

Hard Hat Suspension Types

Ratchet and Swing-Ratchet

Feature a knob for tightening or loosening the band to customize the fit. Swing-ratchet suspension helmets let the wearer reverse the position of the helmet without removing the suspension frame.

One-Touch and Staz-On

One-Touch have a clip that is squeezed and slid along the band to adjust fit. Staz-On suspension helmets have a band with evenly spaced holes on one end and pins on the other end that fasten to adjust.















General Purpose Hard Hats—Type 1, Class E

Non-vented

Protect against vertical impacts and high-voltage conductors up to 20kV. Used by construction workers, road crews, and other workers as required by OSHA. Front and full brim protect the face from sun, reduce glare, and help shed rain. Full brim protects both the face and neck. See Grainger.com® for available

colors.			Front Brim		Full Brim		
Material	Brand	Series	Accessory Slots	Item No.	Accessory Slots	Item No.	
Pinlock (4-Point)							
Polyethylene	MSA	V-Gard®	Yes	D0311	Yes	D0366	
Polyethylene	Honeywell North	North Zone™	Yes	J5113	_	_	
Polyethylene	Condor	SL	Yes	J5421	_	_	
	Ratchet (4-Point)						
Polyethylene	MSA	V-Gard®	Yes	D0312	Yes	D0367	
Polyethylene	MSA	SmoothDome®	Yes	D0371	_	_	
Polyethylene	MSA	V-Gard®	Yes	H0844	_	_	
Polyethylene	Honeywell North	North Zone™	Yes	J5114	Yes	J6000	
Polyethylene	Condor	SL	Yes	J5422	No	J5423	
Polyethylene	3M	H-800	_	_	No	H3920	
Ratchet (6-Point)							
Polyethylene	Bullard	Classic	_	_	No	E5091	
Ratchet (8-Point)							
	Honeywell Fibre-Metal	SuperEight	Yes	G5189	No	G5183	
Swing Ratchet (8-Point)							
Thermoplastic	Honeywell Fibre-Metal	SuperEight	No	G5190	No	G5184	







General Purpose NFL Hard Hats—Type 1 Class E

U.S. Flag

w/ Eagle

Non-vented

Hats can be printed with the logo and colors of any NFL team. Front brim protects the face from sun, reduces glare, and helps shed rain. Protect against high-voltage conductors up to 20kV and vertical impacts to the top of the head. Used by construction workers, road crews, and other workers as required by Ω SH2 Ω

				Front Brin	1
	Material	Series	CHOOSE: Graphics	Accessory Slots	ltem No.
ı	One-Touch (4-Point)				
ı	Polyethylene	V-Gard®	NFL Team Graphics	Yes	D0375
1			· · · · · · · · · · · · · · · · · · ·		





White w/Large U.S. Flag H0843







White w/Small U.S. Flag H0843

Stripes J5167







Freedom Series V-Gard Hard Hats—Type 1, Class E

Non-vented

MSA

Patriotic hard hats are printed with symbols of national pride, such as flags and eagles. Protect wearers from vertical impacts to the top of the head and high-voltage conductors up to 20kV. See Grainger.com® for available graphics.



J5167

		Front Brim		Full Brim		
Material	Series	Accessory Slots	Item No.	Accessory Slots	Item No.	
Ratchet (4-Point)						
Polyethylene	Freedom Series®	Yes	H0843	No	J5167	