



Self-Retracting Lifelines

NANO-LOK™

- Meet ANSI standards, except Tie-Back

Standard

Light, compact units feature an impact-resistant housing with swiveling anchorage loop and automatic quick-activating arrestor.

45WA80 is designed for welding, grinding, and other high-heat applications. It has flame-resistant Kevlar®/Nomex® fiber webbing and is arc rated APTV 8 cal./cm².

Tie-Back

Units incorporate a 36" tie-back leg, to eliminate the need for a separate anchor connector, tie-off adapter, or scaffold choker. UV-resistant nylon housing.

LE (Leading Edge)

Designed for safety and comfort in foot-level tie-off and sharp-edge applications. Weight-dispersing energy absorber and 360°-rotating connector attach directly to harness, leaving the D-ring open. 2-leg SRLs provide 100% tie-off.

Connectors

Use to secure a Nano-Lok SRL directly to a full-body harness webbing, leaving the back D-ring available.

ULTRA-LOK®

- Meet ANSI standards

Corrosion-resistant stainless steel components with durable polyurethane housing. Antiratcheting, twin disc brake system limits arresting forces.

SEALED-BLOK™

- Meet ANSI and CSA standards

Fully sealed design protects working components, enhances safety, and extends working life.



16V464



19TR88



2UZZ5



3TNE7

SRL Length	No. of Legs	Anchorage Hook Type	Harness Hook Type	Weight Cap.	Mfr. Model	Item No.
Nano-Lok™						
Standard, 2½" Nylon Webbing						
6 ft.	1	Carabiner	Snap Hook	420 lb	3101215	16V464
6 ft.	1	Aluminum Carabiner	Snap Hook	420 lb	3101214	16V465
6 ft.	1	Carabiner	Steel Rebar Hook	420 lb	3101217	16V467
6 ft.	2	Aluminum Rebar Hook	Quick Connect	420 lb	3101277	16V470
Standard 2½" Kevlar®/Nomex Webbing						
6 ft.	1	Carabiner	Snap Hook	420 lb	3101498	45WA80
Tie-Back, 2½" Nylon Webbing						
9 ft.	1	Snap Hook	Quick Connect	420 lb	3101366	46W460
9 ft.	2	Snap Hook	Quick Connect	420 lb	3101374	46W459
LE (Leading Edge) with ¾" Galvanized Cable						
8 ft.	1	Carabiner	Quick Connect	420 lb	3500214	19TR91
8 ft.	2	Carabiner	Swivel Snap Hook	420 lb	3500229	19TR85
8 ft.	1	Snap Hook	Quick Connect	420 lb	3500210	19TR89
8 ft.	2	Snap Hook	Quick Connect	420 lb	3500225	19TR83
8 ft.	1	Aluminum Snap Hook	Aluminum Captive Eye Carabiner	420 lb	3500215	19TR92
8 ft.	1	Aluminum Rebar Hook	Quick Connect	420 lb	3500216	19TR93
8 ft.	2	Aluminum Rebar Hook	Quick Connect	420 lb	3500231	19TR81
8 ft.	1	Steel Rebar Hook	Steel Carabiner	420 lb	3500212	19TR90
8 ft.	2	Steel Rebar Hook	Quick Connect	420 lb	3500227	19TR82
8 ft.	1	Swivel Snap Hook	Snap Hook	420 lb	3500211	19TR87
LE (Leading Edge) ¾" Kevlar®/Galvanized Steel Cable						
9 ft.	1	5K® Snap Hook	Tie-Back	420 lb	3500213	19TR88
9 ft.	2	5K® Snap Hook	Tie-Back	420 lb	3500228	19TR80
Nano-Lok™ Connectors						
For Use with Nano-Lok Single Leg Self-Retracting Lanyards						
—	1	—	—	420 lb	3100088	16V475
For Use with Nano-Lok Twin Leg Self-Retracting Lanyards						
—	—	—	—	420 lb	3100087	16V473
For Use with Nano-Lok Single Leg Self-Retracting Lanyards						
—	—	—	—	420 lb	3100089	16V474
Ultra-Lok®						
¾" dia. Galvanized Steel Cable						
20 ft.	1	Snap Hook	Swivel Snap Hook	310 lb	3504433	2UZZ6
30 ft.	1	Snap Hook	Swivel Snap Hook	310 lb	3504430	2UZZ5
50 ft.	1	Snap Hook	Swivel Snap Hook	310 lb	3504450	2UZZ7
Sealed-Blok™, "¾" Stainless Steel Cable"						
15 ft.	1	Carabiner	Swivel Snap Hook	420 lb	3400827	3TNE7
30 ft.	1	Carabiner	Swivel Snap Hook	420 lb	3400802	3TNF1

Accessories

Each Nano-Lok SRL has an integrated anchorage loop to let you install anchorage connections such as these and leave the harness dorsal D-ring open for other equipment or rescue.



Single Leg
16V475



Twin Leg
16V473



Cab Mount
16V474



DuraTech® Compact Self-Retracting Lifelines

- Meet ANSI standards

SRLs have an internal inertial brake disc system that eliminates the need for an external shock pack. Heavy-duty main spring and abrasion-resistant HPPE webbing deliver long service in the most demanding conditions.



36MF89

SRL Length	No. of Legs	Anchorage Hook Type	Harness Hook Type	Weight Cap.	Mfr. Model	Item No.
6 ft.	1	Aluminum Snap Hook	Steel Carabiner	310 lb	82706SB4	36MF89
6 ft.	1	Aluminum Rebar Hook	Steel Carabiner	310 lb	82706SB5	36MF90
6 ft.	1	Aluminum Rebar Hook	Aluminum Carabiner	310 lb	82706S5	36MF91
6 ft.	1	Steel Rebar Hook	Steel Carabiner	310 lb	82706SB3	36MF88
6 ft.	2	Aluminum Snap Hook	Carabiner	310 lb	82706TB4	36MF94
6 ft.	2	Aluminum Rebar Hook	Carabiner	310 lb	82706TB5	36MF95
6 ft.	2	Steel Rebar Hook	Carabiner	310 lb	82706TB3	36MF93



Rebel Self-Retracting Lifelines

- Meet ANSI standards

Thermoplastic housing is lightweight, compact, and durable. Feature swivel housing, snap hook, and swivel hook. Corrosion-resistant.



6ZLP1

Description	SRL Length	Weight Cap.	Mfr. Model	Item No.
¾" Galvanized Steel Cable	20 ft.	420 lb	3590517	29GA87
	33 ft.	420 lb	3590500	6ZLP1
	50 ft.	420 lb	3590550	6ZLP2
	66 ft.	420 lb	3590590	6ZLP3
¾" Stainless Steel Cable Cable	20 ft.	420 lb	3590504	29GA88
	1" Nylon Strap	11 ft.	3100426	53CV17
1" Polyester Strap	6 ft.	310 lb	3100403	40MC98
	11 ft.	310 lb	3100425	40MC86
	20 ft.	310 lb	3100431	40MC60