



36MW07

36MW12



## Anchorage Connectors

- Tensile strength: 5000 lb., except 3600 lb. for 36MF81

### PASS-THRU ANCHOR

Great for I-beams and other rated structural members. A 3" wear pad provides cut and abrasion resistance.

### SLING ANCHORS

Use with I-beams and other rated structural members. Forged alloy steel hardware.

36MW12 is an economical and lightweight anchor sling with heavy-duty polyester webbing. 19F358 and 36MW08 are excellent in harsh environments, with high-strength cable that provides superior cut/abrasion resistance.

### WIRE HOOK ANCHOR

Squeeze-open anchor is easily installed. For use only in overhead applications.

### SUSPENDED CABLE ANCHOR

Designed to provide a single-person fall arrest or restraint anchor point in surfaces such as steel decking, concrete, and grating. Anchoring plate is 6" x 6" x 1/4".

### CONCRETE ANCHORS

Web Anchor is made for pour-in-place concrete applications. Constructed to resist the abrasion common with rebar form work.

Rotating Bracket models are multiuse anchors featuring a reusable zinc-plated steel anchor plate with an integral 360° self-orienting D-ring.

### BEAM ANCHORS

For use on overhead I-beams.

19F359 has dual aluminum locknut jaws, center D-ring, and aluminum hex bar. Tool-less installation. 36MW10 features heavy-duty steel frame and wheels for temporary or permanent installation on closed-end horizontal beams.

### PARAPET WALL AND WINDOW/DOOR JAMB ANCHORS

Connectors install without fasteners to provide temporary anchorage.

Parapet Wall Anchor is for use on 9" and higher parapet walls, 1/2" to 15" thick. Window/Door Jamb Anchor adjusts to 21" to 51" openings to provide fall arrest/restraint anchorage.



Description	Mfr. Model	Item No.
<b>Pass-Thru Anchor</b>		
Polyester Web Strap with Loop, 4 ft.	7348	36MW07
<b>Sling Anchors</b>		
Single-D Web Choker Strap, 6 ft.	7272	36MW12
Carabiner Sling Anchor, Vinyl Coated Cable, 6 ft.	84202DC	19F358
Carabiner Sling Anchor, 1/4" Galvanized Cable, 4 ft.	84202D4	36MW08
<b>Wire Hook Anchor</b>		
Fits 2" to 3" Pipe Dia.	7402	36MW11
<b>Suspended Cable Anchor</b>		
1/2" dia. Galvanized Steel Cable, 8 1/2 ft.	749485	36MF74
<b>Concrete Anchors</b>		
Web Anchor, 4-ft. with Jacketed Loop and O-Ring	7448	36MW09
Rotating Bracket with D-Ring	7451AC	36MF77
Screw Anchor with Rotating D-Ring Bracket	7451A	36MF75
Expansion Bolt with Rotating D-Ring Bracket	7451C	36MF76
<b>Beam Anchors</b>		
Clamp with Adjustable Width, 3" to 13" Flange Size	7533	19F359
Beam Trolley, Adjustable Width, 3" to 8" Flange Size	7711	36MW10
<b>Parapet Wall and Window/Door Jamb Anchors</b>		
Wall Anchor	7460A	36MF80
Window/Door Jamb Anchor	7465A	36MF81



## Anchorage Connectors

- Meet OSHA and ANSI standards

### PASS-THRU ANCHORS

Smaller D-ring passes through larger D-ring to attach to structural member; can be passed through multiple times to adjust overhead height.

### ROOF ANCHORS

Permanent and reusable anchors are designed for fall protection during maintenance, repair, and construction on pitched and flat roofs.

### MOUNTED D-RING AND D-BOLT ANCHORS

Provide economical fall protection anchorage for installation on structural steel members, in a variety of work environments. D-rings are zinc-plated, except 45J296 is stainless steel.

### BEAM ANCHOR

Easy-to-install anchors can be relocated and reused.



Description	Item No.
<b>Pass-Thru Anchors, Polyester Webbing</b>	
3 ft.	19F392
6 ft.	19F391
8 ft.	30HG92
10 ft.	30HG93
<b>Roof Anchors</b>	
Permanent Double D-Ring Anchor, 17"L	19F390
Permanent Single D-Ring Anchor, 19"L	49CD18
Reusable Hinged Anchor with D-Ring	45J299
D-Ring Steel Anchor Plate	49CD27
Chain Anchor	49CD26
<b>Mounted D-Ring and D-Bolt Anchors</b>	
Mounted D-Ring, Weld-On or Bolt-On, 4 1/2" x 2" Plate with 1/2" Holes	35KU73
Mounted D-Ring, Bolt-On, 4 1/2" x 2" Plate with 1/2" Holes	35KU72
Mounted Stainless Steel D-Ring, Bolt-On, 4 1/2" x 2" Plate with 1/2" Holes	45J296
Permanent D-Ring Bolt Anchor, 1/2" dia., 7/8" Working Thickness	30HG83
Bolt-On D-Ring Anchor, 5/8" dia. Hole	49CD19
<b>Beam Anchor</b>	
Trailing I-Beam Anchor, Adjustable Width 3" to 13"	36MF78