

## Firestop Pillows, Plugs, Wraps & Sheets

Firestop pillows, plugs, wraps, and sheets fit around ducts, cable trays, and pipe openings in walls, ceilings, and floors to prevent fire from moving to an adjoining space. They're often used with fire barrier caulks and putties to complete the seal. Pillows, plugs and blocks, sheets, and gaskets include an intumescent material that expands to seal the space when it's subjected to high heat.

Firestop pillows fit around irregularly shaped openings in fire-rated barriers to seal gaps and prevent smoke and flame from moving to adjoining spaces. Plugs and blocks install in pipe collars, wall openings, and other areas areas to seal large openings between spaces. They can be penetrated to

pass through cable and wire while maintaining the seal. Plugs install in round openings while blocks are rectangular in size.

Wraps, strips, and tape protect critical equipment from damage caused by heat and fire. Wraps protect pipes, ducts, and cables from damage caused by heat and fire. Strip wraps around pipes to seal openings before caulk or sealants are applied. Tape secures sheets and wraps to maintain fire ratings.

**Sheets** are cut to fit irregular shapes to cover large openings.

**Gaskets** fit inside compatible electrical panels and switch and outlet cover plates. They're easier and quicker to install than putties.

Fire	Resist	ant	&
Reta	rdant	Trea	tments

Fire (Flame)-resistant intumescent coatings are applied to walls and structural materials such as steel, wood, and oriented strand board (OSB) to prevent the flame from spreading to adjoining areas. The coating is painted onto the surface and can be used to create a fire-rated barrier. Fire-resistant coatings won't ignite when exposed to flame and high heat.

Container Size	Container Type	Std.	Brand	ltem No.	Pkg. Qty.
<b>Fire Resistant Intu</b>	mescent Coatings For	Walls and Structures			
5 gal	Pail	ASTM E-119, ASTM E-84	Fireguard by Shield	45EK82	1
55 gal	Drum	ASTM E-119, ASTM E-84	Fireguard by Shield	45EK83	1
<b>Fire Retardant Coa</b>	tings for Fabric				
22 oz	Spray Bottle	NFPA 701	Fireguard by Shield	45EK74	6
32 oz	Spray Bottle	_	Cold Fire	8AWT0	1
5 gal	Pail	NFPA 701	Fireguard by Shield	45EK75	1
55 gal	Drum	NFPA 701	Fireguard by Shield	45EK76	1
<b>Fire Retardant Coa</b>	tings For Wood		· ·		
22 oz	Spray Bottle	ASTM E-84, NFPA 255, UL 723	Fireguard by Shield	45EK77	6
1 gal	Juq	ASTM E-84, NFPA 255, UL 723	Fireguard by Shield	45EK78	1
1 gal	Jug	ASTM E-84, NFPA 255, UL 723	Fireguard by Shield	45EK79	4
5 gal	Pail	ASTM E-84, NFPA 255, UL 723	Fireguard by Shield	45EK80	1
55 gal	Drum	ASTM E-84, NFPA 255, UL 723	Fireguard by Shield	45EK81	1

Scan. Order. Done. Details on page A1.



Overall	Overall	Overall	Fire	Fire Resistance			Item	Pka.
Height	Length	Width	Rating	Туре	Interlocking	Brand	No.	Qty.
Firestop F Pillows	Pillows							
2 in	9 in	6 in	3 hr	Intumescent	No	3M	1MN79	1
2 in	9 in	6 in	3 hr	Intumescent	No	3M	1MN80	1
2 in	9 in	5 in	3 hr	Intumescent	Yes	3M	5PB34	1
2 in	9 in	6 in	3 hr	Intumescent	Yes	3M	5PB35	1
3 in	9 in	6 in	3 hr	Intumescent	No	3M	1MN81	1
3 in	9 in	6 in	3 hr	Intumescent	Yes	3M	5PB36	1
4 in 4 in	9 in 9 in	1 in 2 in	4 hr 4 hr	Intumescent Intumescent	No	STI STI	3PA71 3PA72	1
6 in	9 in	2 in	4 hr	Intumescent	No	STI	3PA73	1
6 in	9 in	3 in	4 hr	Intumescent	No	STI	3PA74	1
<b>Firestop</b>	Plugs & Bl	ocks				-	-	
Plugs								
0.5 in	4 in	5.2 in	2 hr	Fitted Barrier	Not Applicable		413W19	4
3.1 in	3 in	3 in	2 hr	Intumescent	No	STI	5GKD4	1
3.1 in	4.64 in	4.64 in	2 hr	Intumescent	No	STI	5GKD5	1
3.13 in Blocks	2 in	4 in	2 hr	Fitted Barrier	Not Applicable	3M	413W18	4
2.36 in	8 in	5.12 in	2 hr	Fitted Barrier	Not Applicable	3M	413W16	12
2.36 in	39 in	5.12 in	2 hr	Fitted Barrier	Not Applicable		413W17	3
Overall	0.	erall	Fire	Fire Resis			Item	Pkg.
Length		'idth	Rating	Туре		Brand	No.	Qty.
Firestop V	Vraps, Str	ips & Tape						
Wraps								
2 ft		2 in	4 hr	Intumes		3M	3BE40	1
8.2 ft		.5 in	3 hr	Intumes		3M	6VEE5	1
12 ft		.5 in	4 hr	Intumes		STI	1XTJ1	1
20 ft 25 ft		.5 in 8 in	2 hr 2 hr	Endothe Endothe		3M 3M	23TM24 5GKA6	1
25 IL 50 ft		4 in	2 111	Endothe		3M	6MKL2	1
Tapes	2	4 111	_	Eliuotile	IIIIC	3101	UWIKLZ	
18 ft	2	in N	ot Rated	Intumes	cent Me	etacaulk	783XR2	1
30 ft		2 in	4 hr	Intumes		STI	4MM48	1
Strips								
40 ft		2 in	3 hr	Intumes	cent	3M	2JDF5	5
<b>Firestop S</b>	heets							
Sheets								
3 ft		2 ft	4 hr 4 hr	Intumes		3M	3BE38	1
3 ft 3 ft		3 ft 3 ft	4 nr 4 hr	Intumes		3M 3M	3BE39 2JDG3	1
3 ft		3 ft	4 III 4 hr	Intumes		etacaulk	49ZY64	1
3 ft		4 in	4 hr	Intumes		STI	6LE18	1
3 ft		6 in	4 hr	Intumes		STI	6LE19	1
28 in		33 ft	4 hr	Intumes		3M	3BE37	1
28 in		6 in	4 hr	Intumes		STI	6LE17	1
52 in	2	8 in	4 hr	Intumes	cent	3M	2JDH1	1
		Overall	Fire		sistance		Item	Pkg.
Usage Lo		Length	Ratir	ng Ty	rpe E	Brand	No.	Qty.
Firestop G Double (								
Recepta		4 in	3 h	r Intum	escent Me	etacaulk	49ZY49	1
Double (	Gang	_	3 h	r Intum	escent Me	etacaulk	49ZY51	1
Swite		1 01 in	3 h				49ZY46	1
Electrica Electrica		1.81 in 3.69 in	3 h			etacaulk etacaulk	492Y46 49ZY47	1
Single G		5.09 111	3 h			etacaulk	492147 49ZY48	1
Recepta Single G		_						
Single G		4 in	3 h	r Intum	escent Me	etacaulk	49ZY50	1

Fire



45EK82



8AWT0

1764 **GRAINGER**®

Find even MORE on Grainger.com®

1-800-GRAINGER (472-4643)



Fire-retardant coatings for fabric prevent the fabric from burning when exposed to flame.

Shleid Industries, Inc.

Fire-retardant coatings for wood prevent wood from burning when exposed to flame. Fire retardant is applied to a surface to prevent it from igniting.