DOOR CLOSURE TYPE

Safety cabinets keep dangerous liquids organized, labeled, and separate from work areas. All include warning/content labels.

Consider the following when selecting a cabinet:

- Federal, state, and local compliance requirements
- Hazardous chemical flash point

OSHA COMPLIANCE:

The combined total of Category I, 2, 3 and 4 liquids should not exceed 60 gal.

FLASH POINT GUIDE FOR OSHA:

Category 1 and 2 Flammables - Below 73.4°F Category 3 Flammables - At or Above 73.4°F/At or Below 140°F

Category 4 Flammables - Above 140°F/At or Below 199.4°F

NFPA 30 COMPLIANCE:

The combined total of all Class I, II, and III liquids should not exceed 120 gal.

FLASH POINT GUIDE FOR NFPA 30:

Class I Flammables - Below 100°F Class II Combustibles - 100° to 139°F

Class III Combustibles - 140°F and above

Safety Cabinet Information

DOOR CLOSURE TYPES:

Manual requires a worker to close the door.

Self-closing shuts automatically when the door is released to meet NFPA 1 fire code standards.

DOOR STYLES:

Single hinged has one door.

Double hinged has two narrow doors to allow doors to be fully opened in a smaller space.

Single bi-fold folds in the middle when open to take up less floor space.

Four hinged has four doors to allow doors to be fully opened individually.

MATERIALS:

Steel is powder-coated to resist corrosion. Polyethylene is suitable for highly aggressive liquids and has no metal parts to corrode.

Wood laminate resists corrosion from harsh acids. It keeps cabinet contents cooler longer than steel cabinets, which transfers heat to the cabinet interior.

CABINET TYPES:

Standard-height are 35" or taller and do not have a toe kick. **Slimline** are 24" wide or less to fit into smaller spaces.

Undercounter have a recessed toe kick to allow workers to stand comfortably in front of the cabinet.

Countertop are small enough to fit on most workbenches (less than 35" high) to keep items at eye level and easily accessible.

Stackable have a footprint that fits onto an existing base so cabinet capacity can be safely expanded without using more floor or countertop space.

Wall-mount have mounting holes in the back of the cabinet to allow them to be hung on a wall without drilling holes that can damage the integrity of the cabinet.

Drum safety storage do not have shelves in the lower portion of the cabinet to accommodate large containers such as 30and 55-gallon drums.

Combination standard and drum storage safety have two distinct storage areas that store small- to moderate-sized containers and 55-gallon drums.

IBC (Intermediate Bulk Containers) tote safety lockers have a large sump capacity to contain spills and help meet compliance requirements. Heavy duty construction supports the weight of the container and its contents.

Aerosol safety storage have shelves with cutouts to accommodate standard-sized aerosol cans.



Standard Wood Laminate 1AG24 (Contents not included.)



Undercounter Steel 8XCN1





Acids & Corrosives **Safety Cabinets**

- Blue color For small container storage, except 13M568
- holds 1 drum Steel cabinets include leveling feet
- For indoor use
- FM approved and meet International Fire Code and NFPA 1 standards
- Jamco steel cabinets are FM approved and meet UFC 79 standards



45UW92

Standard Polvethylene





Countertop Stackable Steel

These cabinets store acids and corrosives and protect them from hazards and help contain spills that can contaminate the worksite. They also prevent the contents from igniting in the event of a fire and have chemical-resistant coatings to protect surfaces from spills and leaks. Modular Justrite steel cabinets are Quik-Assembly, polyethylene cabinets offer lockable doors that open 180° and adjustable shelves.

> Additional shelves create extra storage space or replace damaged shelves. Match the brand of shelf and cabinet together along with the storage capacity.

							OLUGUI	SELF-
		Door					MANITAL	CLOSING
Storage	Ext. Dim.	Handle		No of	No. of		Item	Item
		Type	Look Tuno	Shelves		Brand	No.	No.
Cap.*	(W x D x H)		Lock Type	Sileives	DOOLS	Drailu	NU.	NU.
	d Safety Cabinet, Si	ngie ningea						
Polyethy		in Molded-In	Dadlaskabla	0	1	Foolo	AELIWOS	
12 gal	18 in x 22 in x 36		Padlockable	2		Eagle	45UW86	
Standard Safety Cabinets, Double Hinged								
Steel			I/		_	L	AUTVZ	AUTVO
30 gal	43 in x 18 in x 44	in .	Keyed/Padlockable		2	Justrite	4HTY7	4HTY8
30 gal		Recessed	Keyed	1	2	Jamco	36WJ06	49R171
45 gal	43 in x 18 in x 65	_{in} Pull Handle	Keyed/Padlockable	2		Justrite	4HTY9	9GMP6
_45 gal			Keyed	2	2	Jamco	36WJ07	49R172
Steel								
55 gal	34 in x 34 in x 65	in Recessed	Padlockable	1	2	Justrite	13M568	_
	011111111111111111111111111111111111111	" Pull Handle	1 daloonabio			ouotiito	10111000	
Steel								
_60 gal	34 in x 34 in x 65		Keyed/Padlockable		2	Justrite	4HTZ1	4HTZ2
_90 gal	43 in x 34 in x 65	in Pull Handle	Keyed/Padlockable	2	2	Justrite	13M571	13M574
Wood La								
23 gal	36 in x 22 in x 35 ¾		Keyed	1	2	Justrite	102XD0	
32 gal	42 in x 18 in x 60	III	Keyed	2	2	Justrite	1AG24	
	d Safety Cabinet, Fo	our Hinged						
Polyethy	/lene							
48 gal	36 in x 22 in x 72		Padlockable	8	4	Eagle	45UW92	_
	d Slimline Safety Ca	binets, Single	Hinged					
Steel								
12 gal	23 in x 18 in x 35	in	Keyed	- 1	- 1	Jamco	36WJ03	515X81
12 gal	23 ½ in x 18 in x 35	in Booogad	Keyed/Padlockable	1	1	Justrite	_	4KPX3
15 gal			Keyed/Padlockable	1	- 1	Justrite	786V99	786VA0
18 gal	23 in x 18 in x 44	in Full Hallule	Keyed	_	1	Jamco	515X64	515X82
24 gal	23 in x 18 in x 65	in	Keyed	3	1	Jamco	36WJ05	515X83
	unter Safety Cabine	ets, Double Hin	ged					
Steel	•	,						
00 00	25 in v 20 in v 25	Recessed	Variad/Dadlaskable	1	0	luotrito	4VNF4	OVCNI
22 gal	35 in x 22 in x 35	In Pull Handle	Keyed/Padlockable	; 1	2	Justrite	1YNF4	8XCN1
Polyethy	/lene							
	36 in x 23 ½ in x 35	in Molded-In	Padlockable	1	2	Justrite	102XE3	_
	top Safety Cabinets							
Steel		, , , , , , , , , , , , , , , , , , , ,						
4 gal	17 in x 17 in x 22	in Recessed	Keved/Padlockable	1	1	Justrite	1YNH8	13M526
6 gal	23 in x 18 in x 22			0	1	Jamco	515X63	515X80
Polyethy								
4 gal	18 in x 18 in x 22	in Molded-In	Padlockable	2	1	Eagle	45UW81	
Counter	top Stackable Safet	v Cabinets. Do	uble Hinged					
Steel		, ,	.					
12 gal	43 in x 18 in x 18	in Recessed	Keyed/Padlockable	1	2	Justrite	4HTY4	102XK1
17 gal	43 in x 18 in x 24		Keyed/Padlockable		2	Justrite	4HTY6	102XK6
	or Use With	Dim (W F	Load	alas	Mate	rial.	Duand	Item
Capin	et Storage Cap.	Dim. (W x D)) Cap. C	olor	Mate	riai	Brand	No.
AUUILION	al Shelves	14 in v 10 i	2216 0	ilvor	Cto		Luctrito	407VC0
C and 40	4 gal	14 in x 13 i		ilver	Stee		Justrite	40ZX69
o gai, 12	gal, 18 gal, 24 gal	20 in x 14 1/4		ilver	Stee		Jamco	786VA8
12 ga	ıl, 15 gal, 22 gal	19 ¾ in x 14		ilver	Stee		Justrite	13M431
	15 gal	22 in x 15 i		ilver	Ste		Justrite	40ZX70
	23 gal	34 in x 17 i			Vood La		Justrite	40ZX64
	23 gal	34 in x 20 ½		Blue	Polyeth		Justrite	48LY18
3	0 gal, 45 gal	39 ¾ in x 14 ⅓		ilver	Ste		Jamco	786VA9
	32 gal	40 in x 14 i	n 125 lb V	/hite V	Vood La	minate	Justrite	40ZX63

* Code states that not more than 60 gal. may be Class I and Class II liquids.