

Anchorage Connectors

 Tensile strength: 5000 lb., except 3600 lb. for 36MF79 and 36MF81

Pass-Thru Anchor—Great for I-beams and other rated structural members. A 3" wear pad provides cut and abrasion resistance.

Sling Anchors—Use with I-beams and other rated structural members. Forged alloy steel hardware.

36MW12 is an economical and lightweight anchor sling with heavy-duty polyester webbing. 19F358 and 36MW08 are excellent in harsh environments, with high-strength cable that provides superior cut/abrasion resistance.

Wire Hook Anchor—Squeeze-open anchor is easily installed. For use only in overhead applications.

Suspended Cable Anchor—Designed to provide a single-person fall arrest or restraint anchor point in surfaces such as steel decking, concrete, and grating. Anchoring plate is 6" x 6" x ½".

Concrete Anchors—Web Anchor is made for pour-inplace concrete applications. Constructed to resist the abrasion common with rebar form work.

Rotating Bracket models are multiuse anchors featuring a reusable zinc-plated steel anchor plate with an integral 360° self-orienting D-ring.

Adjustable Rotating SRD Anchor—Fall arrest/restraint anchor with 360° rotation mounts to wood or metal roofs or steel decking to extend the capability of personal cable self-retracting devices (SRDs, sold separately). Connection D-ring allows attachment of horizontal or vertical lifeline systems.

Beam Anchors—For use on overhead I-beams.

36MF78 has nylon slider pads and ratcheting design with thumb latches. 19F359 has dual aluminum locknut jaws, center D-ring, and aluminum hex bar. Tool-less installation. 36MW10 features heavy-duty steel frame and wheels for temporary or permanent installation on closed-end horizontal beams.

Parapet Wall and Window/Door Jamb Anchors— Connectors install without fasteners to provide temporary anchorage.

Parapet Wall Anchor is for use on 9" and higher parapet walls, $\frac{1}{2}$ " to 15" thick. Window/Door Jamb Anchor adjusts to 21" to 51" openings to provide fall arrest/restraint anchorage.

Description	Mfr. Model	Item No.
Pass-Thru Anchor	Model	140.
Polyester Web Strap with Loop, 4 ft.	7348	36MW07
Sling Anchors		
Single-D Web Choker Strap, 6 ft.	7272	36MW12
Carabiner Sling Anchor, Vinyl Coated Cable, 6 ft.	84202DC	19F358
Carabiner Sling Anchor, 1/4" Galvanized Cable, 4 ft.	84202D4	36MW08
Wire Hook Anchor		
Fits 2" to 3" Pipe Dia.	7402	36MW11
Suspended Cable Anchor		
½" dia. Galvanized Steel Cable, 8½ ft.	749485	36MF74
Concrete Anchors		
Web Anchor, 4-ft. with Jacketed Loop and O-Ring	7448	36MW09
Rotating Bracket with D-Ring	7451AC	36MF77
Screw Anchor with Rotating D-Ring Bracket	7451A	36MF75
Expansion Bolt with Rotating D-Ring Bracket	7451C	36MF76
Adjustable Rotating SRD Anch	or	
11"L x 11"W x 8"D with Rear-Mounted D-Ring	7395A	36MF79
Beam Anchors		
Clamp with Adjustable Width, 3" to 13" Flange Size	7533	19F359
Beam Trolly, Adjustable Width, 3" to 8" Flange Size	7711	36MW10
Parapet Wall and Window/Door Jamb Anchors		
Wall Anchor	7460A	36MF80
Window/Door Jamb Anchor	7465A	36MF81