



Anchorage Connectors

■ Meet OSHA and ANSI standards, except 2UZE8 does not meet ANSI

Tie-Off Adapters—Anchor a fall protection device to overhead locations. Steel Cable Choker 2UZF5 has dual O-ring pass-thru.

Roof Anchors—Solid anchorage without damaging roof. 39AL05, for membrane and built-up roofs, has a swiveling anchorage ring. Base plate is 16"W x 16"H.

D-Ring Anchor—For permanent anchorage connection.

Concrete Anchors—For vertical or overhead/ceiling surface applications. 3TNH9 has quick-release button for instant anchor removal.

Beam Anchors—Fixed Anchor 2UZD7 works horizontally and slides to provide horizontal mobility. 2UZE6 provides horizontal mobility and fits I-beam flanges.

Description	Mfr. Model	Item No.
Tie-Off Adapters		
Polyester Web Strap, 3 ft.	1003000	2UZE1
Polyester Web Strap, 6 ft.	1003006	2UZE2
Steel Cable Choker, 4 ft.	5900550	2UZF5
Roof Anchors		
Reusable - Hinged with (20) 16D Nails	2103676	2UZE8
Reusable - Bracket with Chain and D-Ring	2103673	2UZE7
Concrete Roof Top Anchor	2100133	39AL05
D-Ring Anchor		
With Anchorage Plate	2101630	2UZE5
Concrete Anchors		
Temporary Anchor Strap	2100050	2UZE3
Reusable D-Ring	2104560	2UZD7
Reusable D-Ring with 5 Bolts	2104561	2UZD8
Reusable with Quick-Connect Release	2100085	3TNH9
Beam Anchors		
Fixed, Fits 2 1/2" to 12" Flange	2108406	2UZD4
Trolley, Fits 3" to 8" Flange	2103143	2UZE6



Anchorage Connectors

Cross-Arm Anchors—Wrap around I-beams and other structures. Web straps have a D-ring that slips through a web loop or D-ring. Cross-Arm Chain 3ZL96 is great for harsh environments. Meet applicable OSHA, ANSI, and CSA standards.

Beam Hook Anchor—Large snap hook and D-ring accommodate the connecting device.

Roof Anchors—Reusable roof anchors are for use on steep-pitched or flat wood surfaces. Permanent roof anchors are for use on wood members and sheathing. Meet applicable OSHA and ANSI standards. 5PB32 and 1RK97 are CSA Certified.

Roof Posts—Stainless steel construction with plated steel wiring. Meet applicable OSHA and ANSI standards.

Mounted D-Bolt Anchors—For permanent anchorage connection. Meet applicable OSHA and ANSI standards. 4RC55 is CSA Certified.

Description	Mfr. Model	Item No.
Cross-Arm Anchors		
Polyester Web Strap with Loop, 6 ft.	T7314/6FTAF	5WG66
Polyester Web Strap, 6 ft.	8183/6FTGN	K3347
Chain, 6 ft.	440/6FT	3ZL96
Beam Hook Anchor		
Steel Hook with Adjustable 20-ft. Extension Pole	475/	4RC58
Roof Anchors		
Reusable with Screws	RA20-1/	36FF26
Permanent Mount with 2 D-Rings (For Single User)	RA40/	5PB32
Reusable - Bracket with Chain and O-Ring for Steep-Pitched or Flat Surfaces	RA30-1/	1RK97
Roof Posts		
For Membrane and Built-up Roofs	X10030	5RRD9
For Standing Seam Roofs	X10002	19D203
Mounted D-Bolt Anchors		
5/8" dia., 4" Working Thickness	416/	4RC55
5/8" dia. with Concrete Expansion Anchor	417C/	5SRR2