For more MIG Consumables go to Grainger.com and search for "mig consumables".

## Honeywell MILLER

## Miller Revolution™ Full-Body Harnesses

- Meet ANSI, and CSA standards
- Tensile strength: 6000 lb.
- Capacity: 400 lb.

Durable harnesses have flexible, 2-sided polyester webbing with contrasting color. Shape retention memory and independent upper- and lower-torso adjustments make them comfortable enough to wear all day. Web finials' clip-on design organizes webbing after proper adjustment. Highly visible encapsulated pack protects label. Stand-up D-ring allows easy attachment. Back shield conforms to most body shapes, keeps back D-ring in proper position, and minimizes impact from snap hooks and self-retracting lifelines. Cam buckle permits 1-handed adjustment or release simultaneous with shoulder strap (except 2KUC2 has friction buckle shoulder straps). PivotLink™ Connection rotary design allows harnesses to move with the body. Provides attachment point for belts, tools, and accessories. Fall indicators take the guesswork out of when to take harnesses out of service. Flexible belt pads on 5PA95 to 5PA98 minimize absorption and maintain optimal air circulation during

Revolution™ Construction—Designed to meet the durability requirements for construction applications while providing all-day comfort. Feature back and shoulder padding and modular accessory attachment system.

Revolution™ Arc-Rated—Insulated against electrical shock, with fire-retardant Kevlar® webbing and leather under all hardware. 1XEN8 and 3PRU1 have front rescue loops. 3PRU1 has pad and removable belt. For more Arc-Rated products, see page 1725.

**Revolution™ Vinyl-Coated**—Ideal for dirty environments such as petrochemical and water treatment plants. Resists physical deterioration resulting from exposure to a variety of liquids and maintains overall performance level.

Relief Step™ Safety Device—Allows suspended worker to stand up in harness to enhance blood circulation and prevent suspension trauma after a fall. Small, lightweight unit attaches to any full-body harness.

	D-Ring			ckles*			Mfr.	Item
Back	Front	Side	Shoulder	Leg	Chest	Size	Model	No.
Revolution								
Yes	No	No	CB	QC	QC	L/XL	RDT-QC/UBK	K3287
Yes	No	No	CB	TB	QC	L/XL	RDT-TB/UBK	K3294
Revolution	™ with Pa	ıd						
Yes	No	Yes	CB	QC	QC	L/XL	RDT-QC-DP/UBK	K3290
Yes	No	Yes	CB	TB	QC	L/XL	RDT-TB-DP/UBK	K3296
Revolution™ with Pad and Removable Belt								
Yes	No	Yes	CB	QC	QC	L/XL	RDT-QC-BDP/UBK	K3289
Yes	No	Yes	CB	TB	QC	L/XL	RDT-TB-BDP/UBK	K3295
Revolution	™ Constru	ıction						
Yes	No	No	CB	MB	MB	L/XL	R10CN-MB/UGN	K3278
Yes	No	No	CB	TB	MB	L/XL	R10CN-TB/UGN	K3280
Revolution™ Construction with Pad and Removable Belt								
Yes	No	Yes	CB	MB	MB	L/XL	R10CN-MB-BDP/UGN	K3279
Yes	No	Yes	CB	TB	MB	L/XL	R10CN-TB-BDP/UGN	K3281
Revolution™ Arc-Rated								
Web Loop	No	No	CB	QC	QC	L/XL	RKNAR-QC/UBK	K3298
Web Loop	No	No	CB	QC	QC	L/XL	RKNARRL-QC/UBK	K3300
Yes	No	Yes	CB	QC	QC	L/XL	RKNARRL-QC-BDP/UBK	K3301
Revolution	™ Vinyl-C	oated						
Yes	No	No	FB	TB	MB	L/XL	RPC-TB/UGN	2KUC2
Relief Step	™ Safety	Device						
Relief Step	) <sup>TM</sup>						9099X/1	5PB18
Accessorie	s							
Universal	Belt Attacl	nment Cl	ip				RIA-C2/1	5PB13
Stretchable Tool Holder 9077X							9077X	5PB17
Tool Belt v	/Pad and	Attachm	ent Clips				RIA-B2/	5PB14
* CB = cam	buckle; F	B = frict	ion buckle;	MB = r	nating bu	ickle; QC	= quick connect; TB = tong	ue buckle.





Revolution™ Harness with Pad and Removable Belt K3295



**Revolution**<sup>™</sup> Construction Harness K3278



Relief Step™

5PB18



Safety Device (Harness Sold Separately)

Tool Belt 5PB14

## **Body Belt**

Belt can be used for personal restraint applications that do not require fall arrest, or pair with a nonbelted full-body harness for work positioning applications. Polyester web with 4" reinforced waist pad, removable heavy-duty tongue-buckle belt, and 2 side D-rings.



## **Body Belts**

Polyester web belts have a tongue buckle and provide users with positioning alternatives when fall arrest is not required.



F8634

Description	►CHOOSE: Fits Waist Size	Mfr. Model	Item No.
Single D-Ring	S, M, L, XL	123N	F8634
Single D-Ring with Back Pad	S, M, L, XL, 2XL	3NA	E1709
Single D-Ring	2XL	123N/XXLBK	F8634