

36MF89



## DuraTech® Compact Self-Retracting Lifelines

- Meet ANSI standards

SRLs have an internal inertial brake disc system that eliminates the need for an external shock pack. Heavy-duty main spring and abrasion-resistant HPPE webbing deliver long service in the most demanding conditions.

SRL Length	No. of Legs	Anchorage Hook Type	Harness Hook Type	Weight Cap.	Mfr. Model	Item No.
6 ft.	1	Aluminum Snap Hook	Steel Carabiner	310 lb	82706SB4	36MF89
6 ft.	1	Aluminum Rebar Hook	Steel Carabiner	310 lb	82706SB5	36MF90
6 ft.	1	Aluminum Rebar Hook	Aluminum Carabiner	310 lb	82706S5	36MF91
6 ft.	1	Steel Rebar Hook	Steel Carabiner	310 lb	82706SB3	36MF88
6 ft.	2	Aluminum Snap Hook	Carabiner	310 lb	82706TB4	36MF94
6 ft.	2	Aluminum Rebar Hook	Carabiner	310 lb	82706TB5	36MF95
6 ft.	2	Steel Rebar Hook	Carabiner	310 lb	82706TB3	36MF93

## Rebel™ Self-Retracting Lifelines



- Meet ANSI standards

Thermoplastic housing is lightweight, compact, and durable. Feature swivel housing, snap hook, and swivel hook. Corrosion-resistant.



6ZLP1

Description	SRL Length	Weight Cap.	Mfr. Model	Item No.
3/16" Galvanized Steel Cable	20 ft.	420 lb	3590517	29GA87
	33 ft.	420 lb	3590500	6ZLP1
	50 ft.	420 lb	3590550	6ZLP2
	66 ft.	420 lb	3590590	6ZLP3
3/16" Stainless Steel Cable	20 ft.	420 lb	3590670	6ZLP4
	20 ft.	420 lb	3590504	29GA88
1" Nylon Strap	11 ft.	310 lb	3100426	53CV17
1" Polyester Strap	6 ft.	310 lb	3100403	40MC98
	11 ft.	310 lb	3100425	40MC96
	20 ft.	310 lb	3100431	40MC60



## Contractor Self-Retracting Lifelines

- Meet ANSI standards

Inertial brake limits deceleration distance. Glass-filled reinforced nylon housing with independent alloy steel frame is rugged yet lightweight. Alloy steel double-locking carabiner and load-indicating swivel carabiner.

Dyneema® is a registered trademark of DSM IP Assets B.V.



19F365

Line Material	Weight Cap.	L	Mfr. Model	Item No.
Galvanized Steel	310 lb	30 ft.	727630	19F365
Galvanized Steel	310 lb	50 ft.	727650	19F366



19F384

19F388



19F385



45J286



## Polyester Web Shock-Absorbing Lanyards

- Meet ANSI standards, except Heavy User Internal Shock Absorber models

For use as the connecting deceleration element of a personal fall-arrest system.

**Standard Internal Shock Absorber**—Feature a continuous-length, internal energy-absorbing material jacketed with a durable tubular web. Include impact indicator.

**Heavy User Internal Shock Absorber**—Additional internal

energy-absorbing material limits fall arrest forces experienced by users between 310 and 400 lb. (including tools and equipment).

**Tie-Back**—Pack-style shock absorber has tie-back D-ring.

**Elastic**—Expand and contract with wearer's movements to reduce potential entanglements and tripping hazards.

**Choker Loop**—Provide lightweight, secure attachment to the harness D-ring.

Max. Working Length	No. of Legs	Locking Anchorage Connection Hook Type	Locking Harness Connection Hook Type	Weight Cap.	Item No.
<b>Standard Internal Shock Absorber</b>					
6 ft	1	Snap	Snap	310 lb	19F382
6 ft	1	Rebar	Snap	310 lb	19F383
6 ft	2	Rebar	Snap	310 lb	19F384
<b>Heavy User Internal Shock Absorber</b>					
6 ft	1	Snap	Snap	425 lb	45J289
6 ft	2	Snap	Snap	425 lb	45J291
6 ft	1	Rebar	Snap	425 lb	45J290
6 ft	2	Rebar	Snap	425 lb	45J292
<b>Tie-Back</b>					
6 ft	1	Snap	Snap	310 lb	19F388
6 ft	2	Snap	Snap	310 lb	19F389
<b>Elastic</b>					
4 ft 6 in to 6 ft	1	Snap	Snap	310 lb	19F385
4 ft 6 in to 6 ft	2	Snap	Snap	310 lb	19F386
4 ft 6 in to 6 ft	1	Rebar	Snap	310 lb	45J282
4 ft 6 in to 6 ft	2	Rebar	Snap	310 lb	19F387
<b>Choker Loop, Standard</b>					
6 ft	1	Snap	Choke	310 lb	45J286
6 ft	1	Rebar	Choke	310 lb	45J287
6 ft	2	Rebar	Choke	310 lb	45J288
<b>Choker Loop, Elasticated</b>					
4 ft 6 in to 6 ft	1	Snap	Choke	310 lb	45J283
4 ft 6 in to 6 ft	1	Rebar	Choke	310 lb	45J284
4 ft 6 in to 6 ft	2	Rebar	Choke	310 lb	45J285