

1-800-GRAINGER (472-4643)

Find Gas Abbreviation information on page 1800.



6XFLO

V-Cal Calibration
Station
6UAV4INDUSTRIAL
SCIENTIFIC

Ventis MX4 Multi-Gas Detectors

- 95dB audible, bright LED and vibrating alarms
- DSX Docking Station and iNet compatible
- Backlit LCD

True portability with multi-gas detection in single-gas size. Configured for non-pump applications or with an integral pump for sample draw applications. Available with a tough, safety orange overmold for visibility of the instrument in dark environments. Detectors with diffusion include calibration cup. Detectors with pump include calibration tubing and sample tubing. All detectors include desktop charger and rechargeable batteries.

DSX Docking Stations—Maintenance stations provide easy gas detector bump tests and calibration, with automated record-keeping to help preserve compliance data.

Cloud-Connected 44ZC35 offers automatic schedule tracking with email alerts and notifications about worker exposure and instrument use and service needs.

Standalone 44ZC37 automatically detects calibration gas type and expiration date when a cylinder is connected. It can automatically print bump and calibration certificates to a USB direct-connect printer (sold separately).

V-Cal Calibration Stations—Allow for quick and easy calibration or function (bump) testing of the monitor. Stand-alone operation; PC not required.

Description	Mfr. Model	Item No.
Detectors with Diffusion		
CO, H2S, LEL, O2, Lithium-Ion/12hr., Black	VTS-K1231100101	6XFK9
CO, H2S, LEL, O2, Lithium-Ion/12 hr., Orange	VTS-K1231101101	6XFLO
CO, H2S, LEL, O2, Lithium-Ion/20 hr., Black	VTS-K1232100101	6UAU6
CO, H2S, LEL, O2, Lithium-Ion/20 hr., Orange	VTS-K1232101101	6UAU7
H2S, LEL, O2, SO2 Lithium-Ion/20 hr., Black	VTS-K5232100101	6UAU8
H2S, LEL, O2, SO2 Lithium-Ion/20 hr., Orange	VTS-K5232101101	6UAU9
Detectors with Pump		
H2S, LEL, O2, SO2, Lithium-Ion/20 hr., Black	VTS-K5232110101	6UAV0
H2S, LEL, O2, SO2, Lithium-Ion/20 hr., Orange	VTS-K5232111101	6UAV1
CO, H2S, LEL, O2, Lithium-Ion/20 hr., Black	VTS-K1232110101	6UAU4
CO, H2S, LEL, O2, Lithium-Ion/20 hr., Orange	VTS-K1232111101	6UAU5
Replacement Sensors		
O2	17134461	5JNL5
H2S	17134479	5JNL6
CO	17134487	5JNL7
CH4, LEL	17134495	5JNL8
NO2	17134503	6UAX1
SO2	17143595	6UAX2
DSX Docking Stations		
1 Cloud-Connected with 3 Gas Inlet Ports	18109327-131	44ZC35
Standalone with 3 Gas Inlet Ports	18109327-031	44ZC37
V-Cal Calibration Stations for Detectors with Diffusion		
Single Unit	18108631-00	6UAV4
V-Cal Calibration Stations for Detectors with Pump		
Single Unit	18108631-10	6UAV5
Accessories		
Replacement Battery Kit, AA Alkaline/8 hr., Black	VTSB-301	6UAV9
Replacement Battery Kit, AA Alkaline/8 hr., Orange	VTSB-311	6UAW0
Replacement Battery Pack, Li-Ion/12 hr., Black	VTSB-101	6UAW1
Replacement Battery Pack, Li-Ion/12 hr., Orange	VTSB-111	6UAW2
Replacement Battery Pack, Extended Range Li-Ion/12 hr With Pump / 20 hr Without Pump, Black	VTSB-201	6UAW3
Replacement Battery Pack, Extended Range Li-Ion/12 hr With Pump / 20 hr Without Pump, Orange	VTSB-211	6UAW4
Single Unit Battery Charger	18108191	6UAW5
Single Unit Charger w/Datalink Cable	18108209	6UAW6
Single Unit Automotive Vehicle Battery Charger, 12VDC	18108651	6UAW7
Single Unit Truck Mount w/12VDC Adapter Vehicle Battery Charger	18108652	6UAW8
Single Unit Truck Mount, Hard Wired Vehicle Battery Charger, 12VDC	18108653	6UAW9
6-Unit Battery Charger	18108650-0	6UAX0

Detector
1TAL1Confined
Space Kit
1TAW3INDUSTRIAL
SCIENTIFICiBrid MX6 Multi-Gas Detectors
and Confined-Space Kits

- 95dB audible alarm
- DSX Docking Station and iNet compatible

Readings are shown on a high-visibility full-graphic LCD. Feature 5-way navigation button and concussionproof overmold housing. Each includes calibration cup with tubing, belt clip, carrying case, and desktop charger.

Confined-Space Kit—Contains detector, sampling pump with 10 ft. of tubing, Li-ion 36-hr. battery, single unit charger, spare alkaline battery pack, calibration cup with tubing, calibration gas and regulator, and carrying case.

DSX Docking Stations—Gas detector maintenance stations provide easy bump tests and calibration, with automated record-keeping to help preserve compliance data.

Cloud-Connected 44ZC38 can automatically track bump test and calibration schedules, and send email alerts and notifications about worker exposure and instrument use and service needs.

Standalone 44ZC42 automatically detects calibration gas type and expiration date when a cylinder is connected. It can automatically print bump and calibration certificates to a USB direct-connect printer (sold separately).

Description	Mfr. Model	Item No.
Detectors with Diffusion		
CO, H2S, LEL, O2, Alkaline/10-1/2 hr.	MX6-K1230301	1TAL1
CO, LEL, O2, Alkaline/10-1/2 hr.	MX6-K1030301	1TAL3
H2S, LEL, O2, Alkaline/10-1/2 hr.	MX6-K0230301	1TAL2
LEL, O2, Alkaline/10-1/2 hr.	MX6-K0030301	1TAL4
Detectors with Pump		
CO, H2S, LEL, O2, PID, Lithium-Ion/36 hr	MX6-K123R211	1TAL6
CO, CO2, LEL, O2, Lithium-Ion/36 hr	MX6-R1030211	1TAL7
Confined-Space Kit		
CO, H2S, LEL, O2, PID, Lithium-Ion/36 hr	MX6KIT-K123R211	1TAW3
Replacement Sensors		
LEL	17124975-K	1TAN2
O2	17124975-3	1TAN1
H2S	17124975-2	1TAN9
CO	17124975-1	1TAL8
CH4, IR	17124975-N	1TAN4
CO2, IR	17124975-Q	1TAN5
PID, VOC	17124975-R	1TAN3
DSX Docking Stations		
1 Cloud-Connected with 3 Gas Inlet Ports	18109329-131	44ZC38
Standalone with 3 Gas Inlet Ports	18109329-031	44ZC42
Accessories		
Motorized Sample Draw Pump	18106765	1TAT3
Charger w/Datalink Cable	18107094	1TAN9
Vehicle Battery Charger, 12VDC	18107011	1TAT1
5-Unit Battery Charger, 120VAC	18107136	1TAT2
Replacement Battery Kit, AA Alkaline, 10½ hr.	17131046-3	1TAN6
Replacement Battery Pack, Li-ion, 36 hr.	17131038-2	1TAN8

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**

1801