



3**Z**V09











break panel, and labels.









35GX42 35GX45









Window Indoor/ **Cabinet Color** Description Cap Surface Mount Galvanized Steel 18 ¾6 in 22 ¾ in 24 ¾ in 30 ¾ in 2 to 2.6 lb 3ZV09 Acrylic Acrylic Acrylic Rectangular with Cam Lock 5 lb 10 lb 20 lb White White Indooi 3ZV10 3ZV11 Indoor Indoor and Break Glass Hamme 3ZV12 **Cold-Rolled Steel** 17 ¹⁵/₁₆ in 23 5% in 25 9/₁₆ in 25 9/₁₆ in 30 ¹/₁₆ in 5 lb 10 lb Cream Cream Indoo 35GX42 Rectangular with 35GX43 Indooi Magnetic Catch Door 20 lb 20 lb 30 lb 5 lb Cream Cream 35GX44 35GX45 Indooi Indooi Trapezoid with Magnetic Tempered Glass Catch Door Tempered Glass Cream Indooi 35GX46 Tempered Glass Tempered Glass 17 ¹⁵/₁₆ in 23 5/₈ in Indooi Indooi Cream Cream Rectangular with Cam Lock and Break Glass Handle Cream White Tempered Glass Indoo 35GX50 Rectangular with Continuous Hinge Stainless Steel 10 lb Tempered Glass 26 ½ in Potter Roemer 40LU35 Indooi Rectangular with Continuous Hinge 10 lb Tempered Glass 27 in Stainless Steel Indoor Potter Roemer 40LU19 16 in 23 ½ in 29 in 24 in Indoor, Outdoor Indoor, Outdoor Indoor, Outdoor Indoor, Outdoor 5 lb 10 lb Red Jonesco Rectangular with Left- or Right-Hand Opening Plastic Black/Red Plastic Black/Red Jonesco 20 to 30 lb Plastic Polystyrene Rectangular with Cam Lock and Break Glass Hammer 404K13 404K15 10 lb 20 lb 23 1/4 in 28 1/2 in Indoor, Outdoo Indoor, Outdoo Semirecessed Galvanized Steel
Rectangular with Cam Lock
and Break Glass Handle Tempered Glass 20 ¾ in 26 ¾ in 5 lb 10 lb Tempered Glass White Indooi 1RK38 **Cold-Rolled Steel** 5 lb 10 lb Tempered Glass White Indoor Potter Roemer 40LU31 Rectangular with Continuous Hinge Break Glass 26 ¾ in White Indoor Potter Roemer 40LU32

Cabinets accommodate most common sizes of fire extinguishers and provide easy access in an emergency. High-impact, crystal Polystyrene cabinets are dent-proof and cannot rust. Offer UV-resistant cabinet,

404K13

35GX49



40LU35





Rectangular with Cam Lock

and Break Glass Handle Stainless Steel





20 lb

10 lb

3JLR6 has a rubber strap

Cap.

Fire Extinguisher Brackets Easy-to-mount brackets secure fire extinguishers in a prominent location so they are accessible in

an emergency. All bracket straps are metal, except

Cylinder Dia

5 in 4½ in

28 in

Tempered Glass 26 ¾ in Stainless Steel

Cream

Color

Tempered Glass



Indoor

Indoor



Potter Roemer 40LU23

35GX47



3.	JMY5		
		7	1
	5		1
	40H	503	



35WT39



1RK29



Box Type Bracket				
10 lb	5 in	Black	Amerex	3JLR4
20 lb	7	Black	Amerex	3JMY5
Heavy-Duty Brack				
10 lb	5 in to 5 ¼ in	Black	Buckeye	35WT39
15 lb	6 ½ in to 7 ¼ in	Black	Buckeye	35WT40
30 lb	7 in to 8 in	Black	Buckeye	35WT45
Marine/Vehicle Bi				
5 lb	51/4 in	Black	Kidde	5T906
10 lb	51/4 in	Black	Kidde	5T909
20 lb	7 in	Black	Kidde	5T908
Running Board Bra	acket			
20 lb	_	Black	Badger	40H503
30 lb	_	Black	Badger	40H504
Strap Bracket				
2.5 lb	3% in	Red	Buckeye	35WT37
2.75 lb	_	Red	Badger	40H509
5 lb	41/4 in	Red	Buckeye	35WT38
5 lb	3 in to 4 1/4 in	Red	Amerex	3JLR6
13 lb	4 1/4 in to 6 1/4 in	Red	Amerex	3JMY6
30 lb	6 ½ in to 8 in	Red	Amerex	3JMY7
Vehicle/Marine/Av	viation Bracket			
2.5 lb	3 in	Red	Amerex	3JMY9
2.5 lb	3 in	Red	Amerex	13J016
5 lb	41/4 in	Red	Amerex	13J017
Vehicle Bracket				
5 lb	E in	Dlask	Dodgor	CAIME

Black



Fire Extinguisher Covers

Meet OSHA requirements

13J017

High-visibility, vinyl-coated red covers have a clear plastic window. Hook-and-loop selfadhering nylon fasteners help to keep the covers in place.

Cap.	Fits Tank Dia.	Fits Tank H	Item No.
5 to 10 lb.	5 in	23 in	4T176
15 to 30 lb.	9 in	27 in	4T177



Emergency Escape Ladders

Wall Bracket 2 ½ to 2 5 lb

Lightweight steel ladders provide a fire escape route through an open window for floors above ground level. They store compactly and deploy quickly, attach to most window sills. Anti-slip rungs provide a safe descent, tested up to 1000 lb. Discard after single use.



Badge Kidde

6A.IW5

L	Features	For Use With	ltem No.
13 ft	Tangle-Free, One-Time Use	2-Story Structures	4XP76
25 ft	Tangle-Free, One-Time Use	3-Story Structures	4XP77