Scan. Order. Done. Details on page A1.





#### UL 2034 Listed

85dB horn sounds when sensor detects high levels of CO. Select models feature visual alert when alarm needs replacement. Operating temp.: 40° to 100°F.

Battery-Powered CO Alarms-User-friendly detectors have easyaccess battery compartments. 3YNJ3 has a battery lockout system.

Plug-In CO Alarms—6AJW6 has tamper-resist feature that sounds a constant alarm if unit is unplugged or comes loose from wall outlet. 2FTN5 and 20JK12 include a 6-ft. extension cord for table or shelf mounting.

Plug-In Combination CO and Explosive Gas Alarm—Unit also detects methane or propane gas. Includes extension cord for table or shelf mounting.

Interconnectable CO Alarms—When interconnected with smoke alarms, 1XTH1 and 1XTH2 feature two different sounding patterns to differentiate smoke and carbon monoxide warnings. 2FTN2 features latching alarm indication and a locking mechanism to prevent theft of battery or unit.

	Digital	Hush	Mfg.		Mfr.	Item		
Description	Readout	Button	Warranty	Brand	Model	No.		
Battery-Powered CO Alarms								
9V	No	Yes	10 yr Limited	BRK	CO250B	5KCY4		
(2) AA	No	No	7 yr Limited	Kidde	9C05-LP2	12G545		
(3) AA	No	No	7 yr Limited	Kidde	KN-COB-B-LP	3YNJ3		
(3) AA	Yes	No	7 yr Limited	Kidde	KN-COPP-B-LPM	12G547		
(2) AA with Front-Load Battery Access	Yes	Yes	7 yr Limited	First Alert	CO410	2FTN1		
Sealed Lithium Ion	No	No	10 yr Limited	Kidde	C3010	40H496		
Sealed Lithium Ion	Yes	No	10 yr Limited	Kidde	C3010-D	40H497		
(2) AA with Front Load Battery Access	No	Yes	7 yr Limited	First Alert	CO400B	2FTL9		
(3) AA	Yes	No	7 yr Limited	Kidde	KN-COPP-B-LS	3YNJ4		
Plug-In CO Alarms with 9V Battery Backup								
120VAC	No	No	5 yr Limited	Kidde	KN-COB-DP2	6AJW6		
AC Front Load Battery Access	Yes	Yes	7 yr Limited	First Alert	1039746	2FTN5		
AC Front Load Battery Access	No	Yes	7 yr Limited	First Alert	CO605B	2FTN4		
120VAC, 9V	Yes	Yes	10 yr	Kidde	KN-COPP-3	20JK12		
Plug-In Combination CO and Explosive Gas Alarm with 9V Battery Backup								
120VAC	Yes	No	7 yr Limited	Kidde	KN-COEG-3	1RK40		
Interconnectable CO Alarms with 9V Battery Backup								
120VAC	No	No	5 yr Limited	Kidde	KN-COB-IC	1XTH1		
120VAC	Yes	No	5 yr Limited	Kidde	KN-COP-IC	1XTH2		
120VAC with Side-Load Battery Access	No	Yes	10 yr Limited	BRK	C05120BN	2FTN2		



### SYSTEM SENSOR

# **Carbon Monoxide Alarm**

4-wire detector is designed for system operation. Operates on most industry security and fire alarm control panels. Features RealTest technology, which allows detector to be tested with CO gas. Mounts to single-gang electrical box. 85dB horn. Operating temp.: 32° to 104°F. 12/24VDC. UL Listed.

Inc	ludes	Mfr. Model	lte No
Optional Dr	ywall Anchors	5CGZ7	5CG
1832	GRAIN	<b>IGER</b> ®	

Detection Method u. GZ7 Ionization and Photoelectric Smoke Alarm SART 9V 1.0 GRAINGER



#### SAFEAWAKE Smoke Alarm Aid

F

F

I

SafeAwake Smoke Alarm Aid works in tandem with, and is activated by traditional, audible smoke alarms to improve fire safety for elderly and hard-of-hearing populations. When an alarm sounds, the SafeAwake is triggered to flash a bright light and set off its own loud, low-frequency audible alarm that can be heard by the hearing impaired. It also sets off a motorized bed shaker to wake up slumbering residents. Easy setup makes it an excellent choice for homes, hotels, hospitals, senior residences, and independent and assisted living facilities. With automatic shutoff and restart, turn-on indicator light, test button, and battery backup (batteries included). UL Listed.



# Smoke Detector Testers

Functional testers for commercial and residential smoke detectors do not contaminate or discolor detectors or ceilings, and will not damage plastics or leave a smoky residue. Convenient aerosol can makes testing easy and safe. UL Listed.

Description	Brand	No.
Smoke Check	_	8XZH8
CRC Smoke Test	CRC	3VG75

Find even MORE on Grainger.com®

Mfr.

Mode

49H879

1-800-GRAINGER (472-4643)