



**Wall Blanket
5T498**



**Portable Screen—4 Screens
Shown (Sold individually.)
5T512**



**Portable Screens
19MP55**



**Overhead Sound Baffle
3TPT6**



**Acoustical
Ceiling Tile
420T48**



**Decorative
Fabric Panel
4RC06**



Noise Absorbers

- Sound Seal products meet ASTM E84 Class I Fire Rating;
Auralex Portable Screens meet the CAL 117 Standard

Eliminate noise and echo in industrial and community environments.

Wall Blanket—Abrasion-resistant fiberglass blanket has one quilted side and is impervious to dirt, grease, and solvents. Mounts on walls, ceilings, or anywhere with hard reflective surfaces. Edges are sewn and finished. Also has 4 grommets for easy installation.

Portable Screens—Use screens individually or in groups to form partial noise enclosures. 19MP54 and 19MP55 each include 2 panels and 2 round base stands. 19MP55 is sized to fit on a desk. 5T512 offers an absorber curtain quilted on one side with a reinforced vinyl barrier on the other and a powder-coated tubular steel frame stand.


Overhead Sound Baffle—Standard economy baffle has a smooth casing.

Acoustical Ceiling Tiles—Designed to replace existing grid ceiling tiles. Feature a black matte facing attached to a yellow, rigid fiberglass board.

Decorative Fabric Panels—Ready-to-mount panels feature fabric-covered 6- to 7-lb. density fiberglass core that provides maximum noise absorption. Mount easily to walls, partitions, or any flat surface.

L	W	Thickness	Color	NRC Rating	Brand	Item No.	Pkg. Qty.
Wall Blanket							
8 ft	4 ft	1 in	Gray	0.75	Sound Seal	5T498	1
Portable Screens							
2 ft	2 ft	3 in	Gray/	—	Auralex	19MP55	2
4 ft	2 ft	3 in	Black	—	Auralex	19MP54	2
8 ft	4 ft	1 in	Gray	0.75	Sound Seal	5T512	1
Overhead Sound Baffles							
2 ft	4 ft	1.5 in	White	1.13	Sound Seal	3TPT6	10
Acoustical Ceiling Tiles							
48 in	24 in	2 in	Black	1.15	Sound Seal	420T48	3
Decorative Fabric Panels							
2 ft	2 ft	1 in	Gray	0.75	Sound Seal	1VDR2	1
2 ft	2 ft	1 in	Blue	0.75	Sound Seal	1VDR4	1
2 ft	2 ft	1 in	Neutral	0.75	Sound Seal	1VDR6	1
4 ft	2 ft	1 in	Gray	0.75	Sound Seal	4RC06	1
4 ft	2 ft	1 in	Blue	0.75	Sound Seal	4RC05	1
4 ft	2 ft	1 in	Neutral	0.75	Sound Seal	1VDT7	1

**Convuluted
Foam Sheets
19MP18**



**Flat K-Foam Roll
3TPU1**



**Quilted
Absorber Roll
1VDL9**



Acoustic Foam Sheets and Quilted Absorber Rolls

Can be easily cut into custom sizes and applied to most surfaces.

Convuluted Foam Sheets—Open-cell cone-shape polyurethane foam. Provide greater absorption to surface areas than flat foam. Ideal for low- to mid-range frequency sound absorption. Resist oil, alkali, and mild acids. Not for use near open flame or sparks. Sound Seal sheets temp. range: -45° to 250°F.

Flat K-Foam Roll—2-lb. density, open-cell flat polyurethane foam provides excellent absorption over a broad frequency range. Not for use near open flame or sparks. Aluminized Mylar-faced roll is impervious to water, dust, and oils, and is cleanable. Resistant to moisture and lubricants. Temp. range: -20° to 120°F.

Quilted Fiberglass Absorber Rolls—Aluminized facing is abrasion-resistant and impervious to water, dust, oils, grease, and most solvents. Rolls easily attach to walls or other surfaces. Temp. range: -30° to 250°F. 1VDL9 is used for most broad-band noise problems, and 1VDP5 is for noise levels higher in low-frequency bands.

- Meet ASTM E84 Class I Fire Rating

L	W	Thickness	Color	NRC Rating	Brand	Item No.	Pkg. Qty.
Convuluted Foam Sheets							
2 ft	2 ft	2 in	Gray	0.8	Auralex	19MP19	12
2 ft	2 ft	4 in	Gray	1.1	Auralex	19MP20	6
27 in	54 in	1 in	Gray	0.7	Sound Seal	5T492	4
27 in	54 in	2 in	Gray	0.8	Sound Seal	5T493	4
27 in	54 in	3 in	Gray	0.85	Sound Seal	5T494	4
8 ft	4 ft	2 in	Gray	0.7	Auralex	19MP18	2
Flat K-Foam Roll							
10 ft	54 in	1 in	Charcoal	0.55	Sound Seal	3TPU1	1
Quilted Fiberglass Absorber Rolls							
25 ft	48 in	1 in	Gray	0.75	Sound Seal	1VDL9	1
25 ft	48 in	2 in	Gray	0.8	Sound Seal	1VDP5	1