## **Booster Fire Hoses**

connect to the water source and a nozzle.

Thread


Red color

Hose

Inside

Hoses have a smaller diameter than standard attack hoses to combat smaller fires. They generally require

Item



Item

ARMORED 4

150 ft

Item





## Pin Rack & Reel Fire Hoses

Fitting

White color

Hose Type Single Jacket

Fire hoses install in buildings close to standpipes to connect to the building's water supply. Fittings on each end of the hose connect to the water source and a nozzle.

Coupling Lug Style Rocker

Max. Working

Pressure

at 70°F 300 psi

.lacket

Tuhe

| Hose<br>Inside Dia. | Thread<br>Type | Fitting<br>Material | Coupling<br>Lug Style | Max. Working<br>Pressure<br>at 70°F | Jacket<br>Material | Tube<br>Material | 50 ft<br>Item<br>No. | 75 ft<br>Item<br>No. | 100 ft<br>Item<br>No. |
|---------------------|----------------|---------------------|-----------------------|-------------------------------------|--------------------|------------------|----------------------|----------------------|-----------------------|
| Single Jack         | et             |                     |                       |                                     |                    |                  |                      |                      |                       |
| 1 ½ in              | NST            | Aluminum            | Rocker                | 250 psi                             | Polyester          | Polyester        | 3ATP1                | 3ATP2                | 3ATP3                 |
| 1 ½ in              | NST            | Aluminum            | Rocker                | 250 psi                             | Polyester          | EPDM             | 3EUJ5                | _                    | 3EUJ6                 |
| 1 ½ in              | NST            | Brass               | Rocker                | 250 psi                             | Polyester          | Polyester        | 1FEL2                | 1FEL3                | 1FEL4                 |
| 1 ½ in              | NST            | Brass               | Rocker                | 250 psi                             | Polyester          | EPDM             | 1FEL5                | _                    | 3ATP5                 |
| 2 ½ in              | NST            | Aluminum            | Rocker                | 250 psi                             | Polyester          | EPDM             | 3EUJ7                | _                    | 3EUJ8                 |
| 2 ½ in              | NST            | Brass               | Pin                   | 250 psi                             | Polyester          | Polyester        | 3ATP4                | _                    |                       |
| 2 ½ in              | NST            | Brass               | Rocker                | 250 psi                             | Polyester          | EPDM             | 1FEL6                | _                    | 3ATP6                 |
| <b>Double Jac</b>   |                |                     |                       |                                     |                    |                  |                      |                      |                       |
| 1 ½ in              | NST            | Aluminum            | Rocker                | 400 psi                             | Polyester          | EPDM             | 4YLJ9                | _                    | 4YLK3                 |
| 1 3/4 in            | NST            | Aluminum            | Rocker                | 400 psi                             | Polyester          | EPDM             | 4YLK1                | _                    | 4YLK4                 |
| 2 ½ in              | NST            | Aluminum            | Rocker                | 400 psi                             | Polvester          | EPDM             | 4YLK2                | _                    | 4YLK5                 |



| Nozzle<br>Spray<br>Pattern | Body<br>Material     | Handle<br>Type       | Inlet<br>Size  | Activation<br>Method       | Max.<br>Flow Rate | Max.<br>Pressure   | Brand            | GHT<br>Item<br>No. | NH<br>Item<br>No. | NPSH<br>Item<br>No. | NST<br>Item<br>No. |
|----------------------------|----------------------|----------------------|----------------|----------------------------|-------------------|--------------------|------------------|--------------------|-------------------|---------------------|--------------------|
| Solid Bore                 | e Nozzies            | 0                    | 2/ 1           |                            | 10                | 100 :              |                  | 0.0.0004           |                   | 0.0.000             |                    |
|                            |                      | Standard<br>Standard | 3/4 in<br>1 in | Constant on<br>Constant on | 18 gpm<br>28 gpm  | 100 psi<br>100 psi | Moon             | 6ANW1              | 6ANV6             | 6ANW2<br>6ANV5      |                    |
|                            |                      | Standard             | 1 1/4 in       | Constant on                | 41 gpm            | 100 psi            | American         | _                  | _                 | 6ANV7               | _                  |
| Solid<br>Stream            | Brass                | Standard             | 1 ½ in         | Shutoff<br>Handle          | 75 gpm            | 100 psi            | Amendan          | _                  | 6APP6             | 6APP5               | _                  |
|                            |                      | Standard             | 1 ½ in         | Constant on                | 85 gpm            | 100 psi            |                  | _                  | 6AKC5             | 6AKC4               | _                  |
|                            |                      | Standard             | 2 in           | Constant on                | 94 apm            | 100 psi            | Moon             |                    | _                 | 6ANV8               | _                  |
|                            |                      | Standard             | 2 ½ in         | Constant on                | 168 gpm           | 100 psi            | American         | _                  | 6ANW0             | 6ANV9               | _                  |
| Adjustabl                  | e Gallonage No       | ozzles               |                |                            |                   | ·                  |                  |                    |                   |                     |                    |
|                            | Aluminum             | Pistol               | 1 ½ in         | Shutoff<br>Handle          | 125 gpm           | 100 psi            | Moon<br>American | _                  | 6APT5             | _                   | _                  |
| Fog                        | Brass                | Standard             |                | Twist                      | 130 gpm           | 100 psi            |                  | _                  | _                 | 6AKC1               | 6AKC2              |
| rog                        | DIASS                | Standard             |                | Twist                      | 280 gpm           | 100 psi            |                  | _                  | _                 | _                   | 6AKC3              |
|                            | Plastic              | Standard             | 3/4 in         | Twist                      | 35 gpm            | 100 psi            | _                | 6AKC6              | _                 | _                   | _                  |
|                            |                      | Standard             | 1 ½ in         | Twist                      | 80 gpm            | 100 psi            |                  | _                  | _                 | 6AKC7               | 6AKC8              |
| Single Ga                  | llonage Shutof       |                      |                |                            |                   |                    |                  |                    |                   |                     |                    |
|                            | Aluminum             | Pistol               | 1 in           | Twist                      | 25 gpm            | 300 psi            |                  |                    | 41H473            | 41H472              |                    |
|                            | Alullillulli         | Pistol               | 1 ½ in         | Twist                      | 60 gpm            | 300 psi            | Moon<br>American | _                  | 41H475            | 41H474              | _                  |
| Solid                      |                      | Pistol               | 1 in           | Twist                      | 25 gpm            | 300 psi            |                  | _                  | 41H480            | _                   | _                  |
| Stream                     | Plastic/<br>Aluminum | Pistol               | 1 ½ in         | Twist                      | 60 gpm            | 300 psi            |                  |                    | 41H481            | _                   |                    |
|                            |                      | Standard             | 1 in           | Twist                      | 25 gpm            | 300 psi            |                  |                    | 41H478            | _                   |                    |
|                            |                      | Standard             | 1 ½ in         | Twist                      | 60 gpm            | 300 psi            |                  | _                  | 41H479            | _                   | _                  |
|                            | Pressure Nozz        |                      |                |                            |                   |                    |                  |                    |                   |                     |                    |
| Adjustable                 | -                    | Standard             | 3/4 in         | Twist                      | 22 gpm            | 200 psi            |                  | 41H482             |                   |                     |                    |
|                            | Aluminum             | Pistol               | 1 in           | Twist                      | 24 gpm            | 100 psi            |                  |                    | 41H468            | 41H467              |                    |
|                            | Plastic              | Pistol               | 1 ½ in         | Twist                      | 60 gpm            | 100 psi            |                  |                    | 41H470            | 41H469              |                    |
| Fog                        |                      | Standard             | 1 in           | Twist                      | 25 gpm            | 600 psi            |                  |                    |                   | 41H477              |                    |
| . 09                       |                      | Standard             | 3/4 in         | Twist                      | 8 gpm             | 100 psi            |                  | 4KR35              |                   |                     |                    |
|                            |                      | Standard             | 1 in           | Twist                      | 22 gpm            | 100 psi            |                  |                    |                   | 4KR32               |                    |
|                            |                      | Standard             | 1 ½ in         | Twist                      | 75 gpm            | 100 psi            | Moon             | -                  |                   | 4KR34               | 4KR33              |
| Solid<br>Stream            | A1                   | Standard             | 3/4 in         | Twist                      | 24 gpm            | 100 psi            | American         | 6APP7              | CADDO             | CADDO               |                    |
|                            | Aluminum             | Standard             | 1 in           | Twist                      | 24 gpm            | 100 psi            |                  |                    | 6APP9             | 6APP8               |                    |
|                            |                      | Standard             | 1 ½ in         | Twist                      | 60 gpm            | 100 psi            |                  |                    | 6APTO             | 6APT1               |                    |
|                            | Brass                | Standard             | 1 in<br>2 in   | Twist<br>Twist             | 36 gpm<br>108 gpm | 100 psi            |                  |                    | 6ANV3             | 6ANV2<br>6ANV4      |                    |
|                            |                      | Standard<br>Standard | 3/4 in         | Twist                      |                   | 100 psi<br>100 psi |                  |                    |                   | 6ANW6               |                    |
|                            | Polycarbonate        |                      | 1 in           | Twist                      | 8 gpm<br>22 gpm   | 100 psi            |                  |                    | 6ANW5             |                     |                    |
|                            |                      | Standard             |                | Twist                      | 150 gpm           | 100 psi            |                  | =                  | 6APN5             | =                   |                    |



Solid bore nozzles create a single stream of water without the ability to adjust water flow or pattern. They generally have a longer water stream than other nozzles. Adjustable gallonage nozzles allow the firefighter operating the hose to directly control the amount of water coming out of the nozzle. Single gallonage nozzles don't allow water flow to be adjusted at the nozzle. Flow is only adjustable at the source. Constant pressure nozzles maintain a consistent spray pattern as water pressure within the hose fluctuates. They sometimes produce lower water flows than other nozzles. Gaskets install in solid bore nozzles to create a watertight seal that prevents leakage.

| Inside Dia.<br>Nozzle Gask | Outside Dia. | Thickness | Brand      | No.   |
|----------------------------|--------------|-----------|------------|-------|
| 1 5/16 in                  | 1 15/16 in   | ½ in      |            | 6ANW9 |
| 1 5/16 in                  | 1 % in       | 1/8 in    | Moon       | 6ANW8 |
| 6 1/16 in                  | 7 1/8 in     | 1/4 in    | American   | 6APP4 |
| 1 13/16 in                 | 2 5/16 in    | 3/16 in   | Allicitali | 6APN7 |
| 2 ½ in                     | 3 ¾16 in     | 3/16 in   |            | 6APN9 |





## Fire Hydrant & Standpipe Caps & Plugs

Caps and plugs for fire hydrants and standpipes keep pipes and water supplies free from dirt, trash, and debris that can affect water flow.

| Size                              | Thread<br>Type | Tightening<br>Method | Brand         | Item<br>No. |  |  |  |  |
|-----------------------------------|----------------|----------------------|---------------|-------------|--|--|--|--|
| Brass Fire Hose & Hydrant Caps    |                |                      |               |             |  |  |  |  |
| 1 ½ in                            | NPSH           | Rocker Lug           | _             | 6AKE0       |  |  |  |  |
|                                   | NH             | Pin Lug              | Moon American | 6APA4       |  |  |  |  |
| Plastic                           | Fire Hose &    | Hydrant Caps         |               |             |  |  |  |  |
| 1 ½ in                            | NH             | Rocker Lug           | Moon American | 6APH1       |  |  |  |  |
|                                   | NH             | Rocker Lug           | Moon American | 6APH2       |  |  |  |  |
| 2 ½ in                            | Universal      | Rocker Lug           | Moon American | 6APH3       |  |  |  |  |
|                                   | Universal      | Hex                  | Moon American | 6APH4       |  |  |  |  |
| Brass Fire Hose & Hydrant Plugs   |                |                      |               |             |  |  |  |  |
| 1 ½ in                            | NH             | Pin Lug              | Moon American | 6APA5       |  |  |  |  |
| 2 ½ in                            | NH             | Pin Lug              | Moon American | 6APA6       |  |  |  |  |
| Plastic Fire Hose & Hydrant Plugs |                |                      |               |             |  |  |  |  |
| 1 ½ in                            | NH             | Rocker Lug           | Moon American | 41H522      |  |  |  |  |
| 2 1/2 in                          | NH             | Bocker Lug           | Moon American | 41H523      |  |  |  |  |





## Wrenches open and close fire hydrants. They also attach and

remove hoses and adapters from hydrants.

| For<br>Use On                                       | For<br>Fitting Size                        | Brand         | Item<br>No. |  |  |  |  |
|---|--|---------------|-------------|--|--|--|--|
| Adjustable Hydrant                                  |  |               |             |  |  |  |  |
| Hex   | 1½ in to 3 in                              | _             | 6AKC0       |  |  |  |  |
| Pentagon; Square; Navy<br>Slot; Pin; Rocker         | Fits all nut sizes,<br>1/4 to 41/2 in lugs | Moon American | 3LX25       |  |  |  |  |
| Pentagon; Pin; Rocker                               | Less than 1¾ in                            | Moon American | 20JP20      |  |  |  |  |
| Navy Slot; Pin; Rocker                              | - Fits all nut sizes                       | Moon American | 6ANU9       |  |  |  |  |
| Storz; Pentagon; Square;<br>Navy Slot; Pin; Rocker, | 1/4 to 41/2 in lugs                        | Moon American | 6ANV0       |  |  |  |  |
| Hole Type Spanner                                   |  |               |             |  |  |  |  |
| Hole  | 3/4 in and 1 in                            | Moon American | 41H487      |  |  |  |  |
| Spanner   |  |               |             |  |  |  |  |
| Pin; Rocker   | 3/4 in to 3 in                             | Moon American | 6ANU8       |  |  |  |  |

