

Find more information on Anti-Slip Tape and Treads on page 1878.



**Anti-Slip Treads**

Treads prevent slips, trips, and falls and allow for uniform placement on surfaces. The level of traffic determines the tape durability and grit level needed on the tread's abrasive backing. 4HY92 and 12E817 glow in the dark. All treads are for use in both indoor and outdoor applications, except 3EYK4 and 3EYK7 are for indoor use only.

Imperial Tape WxL	Tape Thickness	Grit Size	Tape Adhesive Material	Performance Temp. Range	Specialty Environment Applications	Specifications Met	Brand	Item No.	Pkg. Qty.
<b>Heavy Traffic, Very Coarse</b>									
<b>Solid, Black</b>									
3 in x 24 in	42 mil	46	Acrylic	-40 °F to 220 °F	—	MIL	Wooster Flex-Tred	12E940	50
3 in x 24 in	46.9 mil	20 to 40	Rubber	-40 °F to 220 °F	—	ADA, OSHA	Sure-Foot Master Stop	31AP77	12
3 in x 24 in	109.4 mil	10 to 20	Rubber	-40 °F to 220 °F	—	ADA, OSHA	Sure-Foot Master Stop	31AP62	24
5 1/2 in x 5 1/2 in	37 mil	46	Acrylic	-40 °F to 220 °F	—	ADA, NFPA, OSHA	Wooster Flex-Tred	452D69	50
6 in x 24 in	6.7 mil	24	Rubber	40 °F to 175 °F	Oily and Muddy	ADA, MIL, OSHA	3M Safety Walk	2JDA9	25
6 in x 24 in	41 mil	46	Rubber	-20 °F to 175 °F	Oily and Muddy	ADA, NFSA, OSHA	—	12E854	25
6 in x 24 in	41 mil	46	Rubber	-20 °F to 175 °F	Oily and Muddy	ADA, NFSA, OSHA	—	12E853	50
6 in x 24 in	41 mil	46	Acrylic	-40 °F to 220 °F	—	ADA, NFPA, OSHA	Wooster Flex-Tred	452D76	10
6 in x 24 in	41 mil	46	Acrylic	-40 °F to 220 °F	—	ADA, NFPA, OSHA	Wooster Flex-Tred	452D75	50
6 in x 24 in	52 mil	46	Acrylic	-20 °F to 150 °F	Chemical	ADA, NFSA, OSHA	—	12E827	10
6 in x 24 in	54 mil	20	Acrylic	-10 °F to 210 °F	—	MIL	Military Grade FlexTred Flex-Tred	53XX14	50
6 in x 24 in	46.9 mil	10 to 20	Rubber	-40 °F to 220 °F	—	ADA, OSHA	Sure-Foot Master Stop	31AP66	24
12 in x 48 in	34 mil	46	Acrylic	-40 °F to 220 °F	—	ADA, NFPA, OSHA	Wooster Flex-Tred	452D81	1
<b>Solid, Clear</b>									
6 in x 24 in	44 mil	46	Acrylic	-40 °F to 220 °F	—	ADA, NFPA, OSHA	Wooster Flex-Tred	452D88	10
<b>Solid, Gray</b>									
3 in x 24 in	38 mil	46	Acrylic	-40 °F to 220 °F	—	ADA, NFPA, OSHA	Wooster Flex-Tred	452D68	50
<b>Solid, White</b>									
3/4 in x 12 in	37 mil	46	Acrylic	-40 °F to 220 °F	—	ADA, NFPA, OSHA	Wooster Flex-Tred	452D77	400
<b>Striped, Black/Yellow</b>									
6 in x 24 in	—	46	Acrylic	-40 °F to 220 °F	—	ADA, ASTM, MIL	Wooster Flex-Tred	1AJZ1	10
<b>Medium Traffic, Coarse</b>									
<b>Solid, Black</b>									
3/4 in x 24 in	28 mil	60	Rubber	40 °F to 175 °F	—	ANSI, NFSA, MIL	3M Safety Walk	2JFK6	50
3/4 in x 24 in	28 mil	60	Rubber	40 °F to 175 °F	—	NFSA	Ability One SKILCRAFT	52CA61	50
5 1/2 in x 5 1/2 in	28 mil	60	Rubber	40 °F to 175 °F	—	ANSI, NFSA, MIL	3M Safety Walk	2JCZ8	50
5 1/2 in x 5 1/2 in	28 mil	60	Rubber	40 °F to 175 °F	—	NFSA	Ability One SKILCRAFT	52CA62	50
5 1/2 in x 5 1/2 in	36 mil	60	Rubber	40 °F to 175 °F	—	NFSA	Ability One SKILCRAFT	52CA79	50
6 in x 24 in	28 mil	60	Rubber	40 °F to 175 °F	—	NFSA	Ability One SKILCRAFT	52CA63	50
6 in x 24 in	30 mil	60	Rubber	40 °F to 175 °F	—	ANSI, NFSA, MIL	3M Safety Walk	5AN41	50
6 in x 24 in	36 mil	60	Rubber	40 °F to 175 °F	—	ANSI, NFSA, MIL	3M Safety Walk	6BV20	50
6 in x 24 in	36 mil	60	Rubber	40 °F to 175 °F	—	NFSA	Ability One SKILCRAFT	52CA80	50
6 in x 24 in	42 mil	60	Acrylic	-20 °F to 220 °F	—	ADA, NFSA, OSHA	—	3EYH1	10
6 in x 24 in	80 mil	60	Rubber	40 °F to 175 °F	—	—	Ability One SKILCRAFT	5MM74	1
<b>Solid, Clear</b>									
6 in x 24 in	35 mil	60	Rubber	40 °F to 150 °F	—	ANSI, NFSA, MIL	3M Safety Walk	54DF21	50
<b>Solid, White</b>									
6 in x 24 in	28 mil	50	Acrylic	-20 °F to 150 °F	Mop Friendly	ADA, NFSA, OSHA	Condor	4HY92	10
<b>Solid, Yellow</b>									
6 in x 24 in	29 mil	60	Rubber	40 °F to 175 °F	—	NFSA	Ability One SKILCRAFT	52CA57	50
6 in x 24 in	33 mil	60	Acrylic	-20 °F to 150 °F	Chemical	ADA, NFSA, OSHA	Condor	12F876	10
6 in x 24 in	33 mil	60	Acrylic	-20 °F to 150 °F	Chemical	ADA, NFSA, OSHA	—	12E821	50
6 in x 24 in	36 mil	60	Rubber	40 °F to 175 °F	—	NFSA	Ability One SKILCRAFT	52CA74	50
<b>Striped, Black/Yellow</b>									
6 in x 24 in	32 mil	60	Acrylic	-20 °F to 150 °F	Chemical	ADA, NFSA, OSHA	Condor	12E824	10
6 in x 24 in	36 mil	60	Rubber	40 °F to 150 °F	—	ANSI, NFSA	3M Safety Walk	54DF11	50
<b>Message—Caution, Black/Yellow</b>									
6 in x 24 in	32 mil	60	Acrylic	-20 °F to 150 °F	Chemical	ADA, NFSA, OSHA	—	448K62	10
6 in x 24 in	32 mil	60	Acrylic	-20 °F to 150 °F	Chemical	ADA, NFSA, OSHA	—	12E825	24
<b>Message—Watch Your Step, Black/Yellow</b>									
6 in x 24 in	32 mil	60	Acrylic	-20 °F to 150 °F	Chemical	ADA, NFSA, OSHA	Condor	12E826	24
<b>Light Traffic, Fine</b>									
<b>Solid, Black</b>									
6 in x 24 in	28 mil	80	Rubber	-20 °F to 175 °F	Chemical	ADA, NFSA, OSHA	Condor	4TF28	50
2 in x 24 in	28 mil	80	Rubber	-20 °F to 200 °F	Chemical	ADA, NFSA, OSHA	—	12E773	50
<b>Striped, Black</b>									
6 in x 24 in	28 mil	80	Rubber	-20 °F to 175 °F	Chemical	ADA, NFSA, OSHA	—	12E817	24
<b>Wet and Barefoot Traffic, Non-Abrasive</b>									
<b>Solid, Black</b>									
6 in x 24 in	45 mil	Proprietary	Rubber	40 °F to 175 °F	Wet and Humid	ADA, ANSI, ASTM, NFSA, OSHA	3M Safety Walk	2JDC5	50
4 in x 16 3/4 in	12.7 mil	20	Rubber	Not Rated	—	—	—	448K72	1
<b>Solid, White</b>									
3/4 in x 7 1/2 in	27 mil	Proprietary	Acrylic	-20 °F to 220 °F	Wet and Humid	ADA, NFSA, OSHA	Condor	3EYK7	12
3/4 in x 17 in	23 mil	Proprietary	Acrylic	50 °F to 175 °F	Wet and Humid	ADA, ASTM, OSHA	3M Safety Walk	6B782	50
16 in x 33 1/2 in	27 mil	Proprietary	Acrylic	-20 °F to 220 °F	Wet and Humid	ADA, NFSA, OSHA	Condor	3EYK4	1