

## BRADY Master

## **Valve Lockouts**

**Gate Valve Lockouts**—Fit most roundhandle gate valves. Nonadherent plastic construction resists chemicals and hot/cold temperatures. Brady models' knockout feature accommodates OS&Y or "rising stem" gate valves.

Adjustable Ball Valve Lockouts— 3TAP3, 2VU39, 3TAP1, and 3TAP2 can also be used to lock valves open on pipes from ½" to 1¼" dia. 4EMY9 lockout is suitable for tight locations near pipes.

**Universal Ball Valve Lockout**—Pouchstyle with strapping and locking mechanism. Design removes handle and conceals valve stem, eliminating reactivation.

## Standard Ball Valve Lockouts-


Designed for locking out quarter-turn ball valves with flat "dog-leg" handles. 1-pc. devices fit all major brand ball valves.

Universal Valve Lockouts—Single device locks out most ball, butterfly, and gate valves. Industrial-grade steel and nylon construction is chemical- and corrosion-resistant.

Plug Valve Lockouts—Compact and easy to use, effective for difficultto-secure plug valves. Fit most manually-actuated plug valves. Durable and tamper resistant.

**Butterfly Valve Lockouts**—Solventand chemical-resistant. Resist cracking and abrasion.

**Gas Valve Lockouts**—Protect against accidental valve opening. 2CJN2 fits all pressurized gas valves up to 3" dia. and works with valve guard in place.










48KV21 2CJJ9









41F336

Fits Handle	Max.	Max. No.				Item
Size	Shackle Dia.	of Padlocks	Color	Temp. Range	Brand	No.
Standard Ball Valve Lockouts						
_	9/32 in	8	Red	-40° to 248° F	Brady	5T820
	9/32 in	1	Red	_	Master Lock	20JE33
_	9/32 in	1	Red	_	Master Lock	20JE34
	5∕16 in	0	Red	-40° to 194° F	Brady	44ZL09
_	5∕16 in	0	Red	-40° to 194° F	Brady	44ZL13
1/4 in to 1 in	3∕8 in	6	Red	-30° F to 350° F	Brady	3AD54
11/4 in to 3 in	9∕32 in	8	Red	-30° F to 350° F	Brady	5T821
11/4 in to 3 in	3% in	7	Red	-30° F to 350° F	Brady	5AT47
6½ in to 9½ in	3⁄8 in	2	Red	-40° to 302° F	Brady	8CPV0
10 in to 13 in	3/8 in	2	Red	-40° to 302° F	Brady	8CRJ7
Universal Valve Lockouts with 8-ft. Metal Cable						
1 in	9∕32 in	1	Red	0° to 250° F	Brady	5TA89
13/4 in	9/32 in	1	Red	0° to 250° F	Brady	5TA86
Universal Valve Lockouts with 8-ft. Nylon Cable						
1 in	9∕32 in	1	Red	0° to 250° F	Brady	5TA87
13/4 in	%₂ in	1	Red	0° to 250° F	Brady	5TA88
Plug Valve Lockouts						
7/8 in	7⁄8 in	1	Red	-25° to 200° F	Brady	4TWF7
15/16 in to 13/8 in	1 % in	1	Red	-25° to 200° F	Brady	4TWF8
1¾ in to 2⅓ in	3% in	1	Red	-25° to 200° F	Brady	4TWF9
2¾6 in to 2½ in	3% in	1	Red	-25° to 200° F	Brady	4TWG1
Butterfly Valve Lockouts						
1/8 in to 21/2 in Thickness	19⁄64 in	4	Red	-20° to 140°F	Brady	41F336
2 in to 4 in Thickness	19⁄64 in	4	Red	-20° to 140°F	Brady	41F337
Universal		0	Red	-40° to 200°F	Master Lock	20JE16
Universal	5/16 in	4	Red	-40° to 200°F	Master Lock	20JE17
Gas Valve Lockouts						
11/4 in	3/8 in	1	Red	-50° to 350° F	Brady	3NRN5
3 in	5∕16 in	2	Red	-50° to 350° F	Master Lock	2CJN2