

Max. door opening up to 180°

 Includes self drilling screws and hardware

Door

Closers have cast iron cylinders, forged steel arms, all-weather fluids, and double heat-treated pinions that help provide long life cycle. Powder-coated finish. Self-tapping/ self-reaming screws, and peel-andstick templates help ensure accurate installation.

1261 Series can be mounted hinge side, top jamb, or parallel arm on either right or left swinging doors. Nonsized cylinder is adjustable for interior doors to 4 ft. 6" and exterior doors to 3 ft. 6". Does not include

1461 Series can be mounted hinge side, top jamb, or parallel arm on either right or left swinging doors. Nonsized cylinder is adjustable for

interior doors to 5 ft, and exterior doors to 4 ft.

4011 Series models are mounted hinge side; specify left or right handed. Nonsized cylinder is adjustable for interior doors to 4 ft. 6" and exterior doors to 3 ft. 6". Tested for 10,000,000 cycles without failure.

4040 Series can be mounted hinge side, top jamb, or parallel arm on either right or left swinging doors. Nonsized cylinder is adjustable for interior doors to 5 ft. and exterior doors to 4 ft. Tested for 10,000,000 cycles without failure.

4111 Series are mounted parallel arm: specify left or right handed. Nonsized cylinder is adjustable for interior doors to 4 ft. 6" and exterior doors to 3 ft. 6". Tested for 10,000,000 cycles without failure.

Housing Length	Housing Depth	Housing Height	CHOOSE: Finish	CHOOSE: Door Handing	Item No.
LCN 1261					
9 15/16 in	2 % in	1% in	Sprayed Aluminum, Dark	Non-Handed	H4241
9 15/16 in	2 % in	11//s in	Bronze Powder Coat	Non-Handed	H4242
LCN 1461					
12 1/4 in	2 3/8 in	2 in	Corouged Aluminum Dorle	Non-Handed	H4243
12 1/4 in	2 3/8 in	2 in	Sprayed Aluminum, Dark Bronze Powder Coat	Non-Handed	H4244
12 1/4 in	2 3/8 in	2 in	Biolize Fowder Goat	Non-Handed	H4245
LCN 4011					
12 1/4 in	2 1/4 in	3½ in	Sprayed Aluminum	Left Hand, Right Hand	H4246
12 1/4 in	2 1/4 in	31/2 in	Dark Bronze Powder Coat	Left Hand, Right Hand	H4247
12 1/4 in	2 1/4 in	3½ in	Dark Bronze Powder Goat	Left Hand, Right Hand	H4249
LCN 4040					
12 1/4 in	2 1/4 in	3½ in	Dark Bronze Powder Coat	Non-Handed	22RC23
LCN 4111					
12 1/4 in	2 1/4 in	3½ in	Sprayed Aluminum, Dark	Left Hand	H4260
12 1/4 in	2 1/4 in	3½ in	Bronze Powder Coat	Right Hand	H4261

FALCON. LCN.

Door Closers

- Max. door opening up to 180°
- Includes self drilling screws and hardware
- Nonhanded

Closers have cast aluminum cylinders, stamped steel arms, all-weather fluids, and heat-treated pinions. Adjustable for general speed, latch speed, and backcheck. Closers are nonhanded and can be mounted hinge side, top jamb, or parallel arm on either right or left swinging doors. Nonsized cylinder is adjustable 1 through 5.



SC61 Series has a Norton 1600 Series Footprint. SC71 Series has a full body. SC81 Series is low profile.

Aum Tune	Housing	Housing	Housing	CHOOSE: Finish	Item
Arm Type	Length	Depth	Height	FIIIISII	No.
Falcon SC61					
Parallel	9 ½16 in	3 1/8 in	3∕4 in	- Sprayed Aluminum, Dark	H4262
Parallel	9 ½16 in	3 1/8 in	3∕4 in	- Bronze Powder Coat	H4263
Parallel	9 ½16 in	3 1/8 in	3∕4 in	Biolize i owder coat	H4264
Parallel	9 ½16 in	3 1/8 in	3⁄4 in	Dark Bronze Powder Coat	H4265
Falcon SC71					
Parallel	13 % in	2 1/8 in	3¾ in	Caravad Aluminum Dark	H4267
Parallel	13 5/8 in	2 1/8 in	3¾ in	 Sprayed Aluminum, Dark Bronze Powder Coat 	H4268
Top Jamb	13 5/8 in	2 1/8 in	3¾ in	- Biolize Fowder Goat	H4266
Falcon SC81					
Parallel	12 ½ in	2 1/4 in	3/4 in	Sprayed Aluminum, Dark	H4269
Parallel	12 ½ in	2 1/4 in	3/4 in	Bronze Powder Coat	H4270
Falcon SC91					
Parallel	6 ½ in	2 ¾ in	17/8 in	Spraved Aluminum, Dark	H4271
Parallel	6 ½ in	2 ¾ in	1% in	Bronze Powder Coat	H4272
LCN SC61					
Parallel	9 1/16 in	3 1/s in	3/4 in	Sprayed Aluminum	H4265



Powered Door Operators

(Pull) Side 5EU12

- Nonhanded
- Acceptable for fire and smoke barrier doors

Low-energy operators function as standard spring-force closers during close cycles, when door is opened manually, or if power is lost or turned off. Holdopen time is adjustable from 0 to 30 sec. If door is obstructed, motor stops and the door closes with standard closer. Include 2 radio-frequency wall switches powered by 9V batteries, 6" x 6" face plates with Americans with Disabilities (ADA) logo, and built-in 1.1A power supply. Connect to wall outlet. Rated 120VAC, 60 Hz.

Ideal for doctors' offices, retirement facilities, schools, churches, and other applications where noise may be a concern.

Arm Type	Housing Length	Housing Depth	Housing Height	Max. Door Opening	Finish	Item No.
Heavy-Duty, 5700 Series						
Slide Track, Stop (Push) Side - Includes Radio Frequency Wall Switches	29 in	4 % in	51⁄4 in	180°	Aluminum Painted	5EU13
Hinge (Pull) Side,	29 in	4 % in	51/4 in	180°		5EU12
Slide Track - Includes Radio Frequency Wall Switches	29 in	4 5% in	51⁄4 in	180°	-Dark Bronze-	4AVD2
Double Lever - Includes Radio Frequency Wall Switches	29 in	4 5⁄8 in	51⁄4 in	180°	Painted	4AVD3
Heavy-Duty, 5800 Series	1					
Parallel, Regular - Includes Door Opening Solution, Narrow Stile Push Plates	8 in	2 ½ in	9 in	95°	Black	48ZD73
Parallel, Regular - Includes 3 in Square Push Plates, Door Opening Solution	8 in	2 ½ in	9 in	95°	Painted	48ZD74



Exit Devices, Grade 1 ■ Fit doors 1¾" to 2¼" thick up to 7-ft, high

VON DUPRIN

For heavy traffic applications. Use on flush and wide-stile doors.

Description	Finish	Item No.
22 Series Touch Bar Exit Devices		
Exit Device, Exit Only, Rim, 3-Ft.	Lacquer	4WY55
Exit Device, Exit Only, Rim, 4-Ft.	Lacquer	2RJ50
Exit Device, Exit Only, Surface Vertical Rod, 3-Ft.	Lacquer	4WY56
Exit Device, Exit Only, Surface Vertical Rod, 4-Ft.	Lacquer	2RJ51
Exit Device, Alarm Type Horn, 3-Ft.	Aluminum	1RAL8
Exit Device Trim, Knob	Aluminum	4WY57
Alarm Exit Device Kit	Aluminum	1RAL5
Exit Device Trim, Lever	Unfinished	407L95
99 Series Touch Bar Exit Devices		
Exit Device Trim, Night Latch	Sprayed Duranodic	2RJ64
Exit Device Trim, Electric Latch Retraction	Satin Chrome	1RAL3
Exit Device, Exit Only, Rim, 3-Ft.	Satin Chrome	4WY59
Exit Device, Exit Only, Rim, 4-Ft.	Satin Chrome	2RJ56
Exit Device, Exit Only, Surface Vertical Rod, 3-Ft.	Satin Chrome	4WY60
Exit Device, Exit Only, Surface Vertical Rod, 4-Ft.	Satin Chrome	2RJ57
Exit Device Trim, Dummy	Satin Chrome	4WY62
Exit Device Trim, Night Latch	Satin Chrome	4WY63
Exit Device Trim, Pull, Entrance by Thumbpiece	Satin Chrome	4WY64
Exit Device Trim, Lever	Satin Chrome	5VRE5
Alarm Exit Device Kit	Satin Chrome	1RAL7
99 Series Conversion Kit		
EL Conversion Kit, 24VDC, 3-Ft.		1RAK8
88 Series Crossbar Exit Devices		
Exit Device, Exit Only, Mortise, Right Hand Reverse	Satin Chrome	4AZY1
Exit Device, Exit Only, Heavy-Duty Rim	Satin Chrome	4AZY2
Backplate Conversion Kit for use with Nos. 4AZY2 and 4AZY8	Dull Chromium	5VRF6
Exit Device, Mortise, Night Latch Trim	Satin Chrome	407L91
Exit Device, Mortise, Night Latch	Satin Chrome	407L92
Alarmed Device		
Guard-X, Battery Powered for Alarm Device	Aluminum	4WY65