

1-800-GRAINGER (472-4643)



## Noise Absorbers

- Sound Seal products meet ASTM E84 Class I Fire Rating; Auralex Portable Screens meet the CAL 117 Standard

Eliminate noise and echo in industrial and community environments.

**Wall Blanket**—Abrasion-resistant fiberglass blanket has one quilted side and is impervious to dirt, grease, and solvents. Mounts on walls, ceilings, or anywhere with hard reflective surfaces. Edges are sewn and finished. Also has 4 grommets for easy installation.

**Portable Screens**—Use screens individually or in groups to form partial noise enclosures. 19MP54 and 19MP55 each include 2 panels and 2 round base stands. 19MP55 is sized to fit on a desk. 5T512 offers an absorber curtain quilted on one side with a reinforced vinyl barrier on the other and a powder-coated tubular steel frame stand.

**Overhead Sound Baffle**—Standard economy baffle has a smooth casing.

**Acoustical Ceiling Tiles**—Designed to replace existing grid ceiling tiles. Feature a black matte facing attached to a yellow, rigid fiberglass board.

**Decorative Fabric Panels**—Ready-to-mount panels feature fabric-covered 6- to 7-lb. density fiberglass core that provides maximum noise absorption. Mount easily to walls, partitions, or any flat surface.



Wall Blanket  
5T498



Portable Screen—4 Screens  
Shown (Sold individually.)  
5T512



Portable Screens  
19MP55



Overhead Sound Baffle  
3TPT6





Acoustical  
Ceiling Tile  
420T48



Decorative  
Fabric Panel  
4RC06

| L                               | W     | Thickness | Color      | NRC Rating | Brand      | Item No. | Pkg. Qty. |
|---------------------------------|-------|-----------|------------|------------|------------|----------|-----------|
| <b>Wall Blanket</b>             |       |           |            |            |            |          |           |
| 8 ft                            | 4 ft  | 1 in      | Gray       | 0.75       | Sound Seal | 5T498    | 1         |
| <b>Portable Screens</b>         |       |           |            |            |            |          |           |
| 2 ft                            | 2 ft  | 3 in      | Gray/Black | —          | Auralex    | 19MP55   | 2         |
| 4 ft                            | 2 ft  | 3 in      | Black      | —          | Auralex    | 19MP54   | 2         |
| 8 ft                            | 4 ft  | 1 in      | Gray       | 0.75       | Sound Seal | 5T512    | 1         |
| <b>Overhead Sound Baffles</b>   |       |           |            |            |            |          |           |
| 2 ft                            | 4 ft  | 1.5 in    | White      | 1.13       | Sound Seal | 3TPT6    | 10        |
| <b>Acoustical Ceiling Tiles</b> |       |           |            |            |            |          |           |
| 48 in                           | 24 in | 2 in      | Black      | 1.15       | Sound Seal | 420T48   | 3         |
| <b>Decorative Fabric Panels</b> |       |           |            |            |            |          |           |
| 2 ft                            | 2 ft  | 1 in      | Gray       | 0.75       | Sound Seal | 1VDR2    | 1         |
| 2 ft                            | 2 ft  | 1 in      | Blue       | 0.75       | Sound Seal | 1VDR4    | 1         |
| 2 ft                            | 2 ft  | 1 in      | Neutral    | 0.75       | Sound Seal | 1VDR6    | 1         |
| 4 ft                            | 2 ft  | 1 in      | Gray       | 0.75       | Sound Seal | 4RC06    | 1         |
| 4 ft                            | 2 ft  | 1 in      | Blue       | 0.75       | Sound Seal | 4RC05    | 1         |
| 4 ft                            | 2 ft  | 1 in      | Neutral    | 0.75       | Sound Seal | 1VDT7    | 1         |

Convuluted  
Foam Sheets  
19MP18



Flat K-Foam Roll  
3TPU1



Quilted  
Absorber Roll  
1VDL9



## Acoustic Foam Sheets and Quilted Absorber Rolls

Can be easily cut into custom sizes and applied to most surfaces.

**Convuluted Foam Sheets**—Open-cell cone-shape polyurethane foam. Provide greater absorption to surface areas than flat foam. Ideal for low- to mid-range frequency sound absorption. Resist oil, alkali, and mild acids. Not for use near open flame or sparks. Sound Seal sheets temp. range: -45° to 250°F.

**Flat K-Foam Roll**—2-lb. density, open-cell flat polyurethane foam provides excellent absorption over a broad frequency range. Not for use near open flame or sparks. Aluminized Mylar-faced roll is impervious to water, dust, and oils, and is cleanable. Resistant to moisture and lubricants. Temp. range: -20° to 120°F.

**Quilted Fiberglass Absorber Rolls**—Aluminized facing is abrasion-resistant and impervious to water, dust, oils, grease, and most solvents. Rolls easily attach to walls or other surfaces. Temp. range: -30° to 250°F. 1VDL9 is used for most broadband noise problems, and 1VDP5 is for noise levels higher in low-frequency bands.

- Meet ASTM E84 Class I Fire Rating

| L  | W     | Thickness | Color    | NRC Rating | Brand      | Item No. | Pkg. Qty. |
|--|-------|-----------|----------|------------|------------|----------|-----------|
| <b>Convuluted Foam Sheets</b>            |       |           |          |            |            |          |           |
| 2 ft                                     | 2 ft  | 2 in      | Gray     | 0.8        | Auralex    | 19MP19   | 12        |
| 2 ft                                     | 2 ft  | 4 in      | Gray     | 1.1        | Auralex    | 19MP20   | 6         |
| 27 in                                    | 54 in | 1 in      | Gray     | 0.7        | Sound Seal | 5T492    | 4         |
| 27 in                                    | 54 in | 2 in      | Gray     | 0.8        | Sound Seal | 5T493    | 4         |
| 27 in                                    | 54 in | 3 in      | Gray     | 0.85       | Sound Seal | 5T494    | 4         |
| 8 ft                                     | 4 ft  | 2 in      | Gray     | 0.7        | Auralex    | 19MP18   | 2         |
| <b>Flat K-Foam Roll</b>                  |       |           |          |            |            |          |           |
| 10 ft                                    | 54 in | 1 in      | Charcoal | 0.55       | Sound Seal | 3TPU1    | 1         |
| <b>Quilted Fiberglass Absorber Rolls</b> |       |           |          |            |            |          |           |
| 25 ft                                    | 48 in | 1 in      | Gray     | 0.75       | Sound Seal | 1VDL9    | 1         |
| 25 ft                                    | 48 in | 2 in      | Gray     | 0.8        | Sound Seal | 1VDP5    | 1         |

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**