



Traffic Barricades and Accessories

- Meet MUTCD and NCHRP 350, except 3YVX4, 20PF67, 20PF54, 3LUU8, and 1EKT5
 - 13P868 and 13P869 are ADA Compliant to MUTCD
- High-Intensity tape provides higher reflectivity than Engineer Grade.

Barricades—Used on highways and municipal roads, or as warning devices around potentially dangerous areas. Feature recessed and replaceable panels. Polypropylene construction. Accommodate flashing barricade lights, sold separately, this page.

Type 1—Single-striped panel has a 12" x 24" reflective top panel and a 4" x 24" nonreflective bottom panel.

Type 2—Two striped reflective panels are 8" x 24" on top and bottom.

Narrow Vertical Barricades—Easy to fold and transport.

Barricade Systems—All-plastic construction. For use in road closure situations where complete coverage is needed.

Type 3—Complete barricade system with three striped reflective panels; 6FGL0 8" x 48", 3LWG1 8" x 96", and 7Y499 8 1/4" x 48".

Barricade Weight Ballast—1EKT5 provides 4-lb. weight to barricade leg. 2KCX2 includes 2 arrow panels and hardware to convert a traffic barricade into a directional barricade.

A-Frame and P-Cade Legs—Used to protect workers in work zones and around manholes, and to cordon off restricted areas and parade routes. P-Cade Legs provide a continuous, obstruction-free guidance system. Lower rail will not trap canes. I-Beam is sold separately. An additional I-Beam can be mounted in the lower section of A-Frames for increased visibility. Weighted models include two 5-lb. inserts per leg.

I-Beams—Exterior-grade PVC provides year-round, all-weather durability.

Description	Tape Color	Frame Color	H	W	Panel L	Item No.
Barricades						
Engineer Grade						
Type 1	Orange/White	White	40 in	24 in	24 in	1EKT3
High-Intensity						
Type 1	Orange/White	White	40 in	24 in	24 in	1EKV9
Vinyl						
Type 1, P-Cade Legs	Orange/White	White	40 in	40 in	72 in	13P868
Type 1, P-Cade Legs	Orange/White	White	40 in	40 in	96 in	13P869
Engineer Grade						
Type 2	Orange/White	White	40 in	24 in	24 in	1EKT4
Type 2, Sand Fillable Ballast	Orange/White	White	45 in	24 in	24 in	3UTY4
High-Intensity						
Type 2	Orange/White	White	40 in	24 in	24 in	1EKW1
Type 2, Sand Fillable Ballast	Orange/White	White	45 in	24 in	24 in	3UTY5
Narrow Vertical Barricades						
Nonreflective						
Type 1, Sidewalk Closed	Black/Yellow	White	44 in	12 in	—	6FGK9
Type 1, Striped Panel, N-Cade Legs	Orange/White	White	44 in	12 1/2 in	24 in	13P872
Type 1, Mowing	Orange/Black	Yellow	36 in	24 in	24 in	13P877
School Crossing	Lime/Black	Yellow	45 in	13 in	—	3YVX4
Engineer Grade						
Type 1, Striped Panel, N-Cade Legs	Orange/White	White	36 in	12 in	12 in	1EKT6
Unrated, Keep Left/with Arrow, A-Frame	White	White	45 in	25 in	24 in	20PF67
Unrated, Men Working, N-Cade Legs	White	White	45 in	13 in	12 in	20PF54
Unrated, Do Not Enter, N-Cade Legs	Yellow	Yellow	45 in	13 in	12 in	3LUU8
Barricade Systems						
Engineer Grade						
Type 3	Orange/White	White	66 in	48 in	—	6FGL0
Type 3	Orange/White	White	60 in	96 in	96 in	3LWG1
Type 3	Orange/White	White	64 in	48 in	48 in	7Y499
Barricade Accessories						
Barricade Weight Ballast						
Type 1, A-Frame Leg, Weighted	—	Black	2 in	2 in	—	1EKT5
P-Cade Leg	—	White	40 1/2 in	29 in	—	3LWE1
I-Beam	—	White	40 1/2 in	29 in	—	1EKT7
I-Beam	—	White	8 in	60 in	72 in	3LWF7
I-Beam	Orange/White	Orange	8 in	2 in	72 in	1EKT8
I-Beam	Orange/White	Orange	8 in	2 in	—	8YJ6



Flashing Barricade Lights

- Meet MUTC and ITE Specifications

Durable polycarbonate lenses with LED lamps. Light settings vary from steady burn to flashing to Off (see table). Photocell activates light from dusk to dawn and helps conserve battery power. Handle on 48TL08 makes it easy to move.



493Y05



35T130



48TL08

Power Source	Includes	Head Dia.	Color	Light Setting	Flashes/Minute	Lamp Life	Brand	Item No.
Battery	(4) D Batteries	7 in	Amber/Yellow Case	Flashing, Off, Steady Burn	60 to 120	100,000 hr	Tapco	493Y04
Battery	(4) D Batteries	7 in	Amber/Orange Case	Flashing, Off, Steady Burn	60 to 120	100,000 hr	Tapco	493Y05
Battery	(4) D Batteries	7 in	Amber/Gray Case	Flashing, Off, Steady Burn	60 to 120	100,000 hr	Tapco	493Y06
Solar	Mounting Bolt and Tool	7 1/2 in	Amber	Flashing, Steady Burn	60	60 hr	—	12R462
Solar	Mounting Bolt and Tool	7 1/2 in	Red	Flashing, Steady Burn	60	120 hr	—	35T130
Solar	Bolt and Switch Pin, LED Bulb	7 1/2 in	Amber	Flashing, Off	55	20,000 hr	—	26K992
Solar	Bolt and Switch Pin, LED Bulb	3 5/32 in	Red	Flashing, Steady Burn	60	20,000 hr	—	45EG65
Solar	Battery	7 in	Red	Flashing, Steady Burn	65	20,000 hr	—	489N94
Solar	Rechargeable Battery, Handle	7 1/4 in	Blue	Flashing	60	43,800 hr	Railhead Gear	48TL08