



Search and Rescue Helmets



- Thermoplastic shell material
- Fits hat size 6½ to 8
- Front brim helmets meet ANSI/ISEA Z89.1-2009; Modern style helmets meet NFPA 1971-2007

Front brim helmets have a low-profile design that provides protection without limiting freedom of movement in confined spaces. Feature an ABS inner shell and a foam impact liner and crown cushion.

Modern style helmets feature thermal and impact protection, a low center of gravity, and increased headroom for a more comfortable fit. The Sure-Lock

ratchet headband adjusts easily with the turn of a knob. U-Fit System has 12 custom comfort settings, and the 4-pt. nylon crown straps and crown pad allow for a more balanced fit. Unique Quick-Attach blade system allows easy attachment and removal of blade-mounted faceshield or blade-mounted goggles. Additional adjustment points allow for a customized fit and interface with an SCBA. Ripstop Nomex ear/neck protector and 3-pt. chinstrap with quick-release buckle. Absorbent cotton brow pad is fire resistant and removable.

Style	Chin Strap	Suspension	Includes	►CHOOSE: Color	Mr. Model	Item No.
Front Brim	Quick Release 3-Point	Standard Sure-Lock Ratchet Headband	8-Point Ratchet Suspension and 2-Point Chinstrap, Vinyl Brow Pad	Red	A2R	38XZ92
				White	A2W	38XZ96
				Yellow	A2Y	38YA02
Modern	Nomex Quick Release and Postman Slide	4-Point Sure-Lock Ratchet	Quick-Attach 4 in Faceshield	Black, White, Red, Yellow, Blue, Orange, Lime-Yellow	URX	G8579



Class II and Class III Rescue Harnesses

Feature sturdy lightweight nylon webbing harnesses and triple locking pompier hook with 2 in side opening gate.

541NYC AND 544FR SERIES CLASS II

- Meet NFPA 1983

Designed for fire service personnel. A sliding D-ring attachment point allows for use with escape systems. 541NYC Series features adjustable, color-coded leg straps. Choose left or right side harness opening to accommodate all types of bunker pants. 544FR Series flame-resistant harnesses are made of 1¾ in W Kevlar webbing with Kevlar thread. Can be worn as an internal harness when paired with compatible bunker pants, or externally with loops on outside.

Note: Measure waist over bunker pants to determine proper size selection.

543CH SERIES CLASS III

- Meet NFPA 1983

For rescue-only operations. Excellent mobility and functionality for lowering yourself or others as a rescuer, for use with an escape system, for rescuing a wearer, and more. 5 load-bearing attachment points. Feature front and back forged steel D-rings and aluminum carabiner. Adjustable, color-coded friction leg straps provide easy donning and size adjustment. Shoulder strap buckles.

►CHOOSE: Fits Waist Size	Pompier Hook	Side Opening	Item No.
541NYC Series Class II			
30 in to 44 in, 36 in to 50 in, 44 in to 56 in	Aluminum	Left	H8825
		Right	H8826
	None	Left	H8829
		Right	H8830
544FR Series Class II			
34 in to 40 in, 36 in to 50 in, 46 in to 56 in	None	Right	H8841
Fits Waist Size	►CHOOSE: Height Range	Side Opening	Item No.
543CH Series Class III			
30 in to 44 in	From 5 ft. to 5 ft. 5 in.	Left	H8837
36 in to 50 in	From 5 ft. 3 in to 6 ft.	Left	H8838
44 in to 56 in	From 5 ft. 5 in to 6 ft. 6 in	Left	H8839



541NYC Series
H8825



544FR Series
H8841



543CH Series
H8837



Cordex Rappelling Gloves

High-quality leather construction gloves feature neoprene cuffs with hook-and-loop closure and carabiner hole. Cordex Gloves have breathable stretch nylon back. Cordex Plus Gloves have reinforced palms and leather back with stretch nylon.

Description	►CHOOSE: Size	►CHOOSE: Color	Mr. Model	Item No.
Cordex	XS, S, M, L, XL	Beige, Black	K52	G4833
Cordex Plus	XS, S, M, L, XL	Beige, Black	K53	E4992



Beige
G4833



52TD42

60XH67

3NGF2



Connectors and Hardware

Carabiners—Carabiner with triact-lock automatic locking feature is for frequent manipulations. Use carabiner with screw lock for occasional manipulations or where foreign material could jam the automatic locking system. Both have a pear shape that is practical for easily connecting multiple items.

Rope Termination Plates—Plates provide a way to attach a rope lifeline to a fall-rated anchor point so the rope can be used as a lifeline. A fall-rated carabiner attaches one end of the plate to the anchor point and the rope threads through the other end. Rope termination points provide a temporary tie-off without using a knot that can reduce the strength of the rope.

Swivels—Prevent rope twisting when the load is turning. 35ZM16 has a large opening to attach to pulleys and lanyards. Meet NFPA 1983.

Description	Color	Brand	Mr. Model	Item No.
Carabiners				
William, Triact-Lock	Black	Petzl	M36A TLN	52TD42
Go, Screw-Lock	Bright	Petzl	P15	13D953
Spirit, No Lock	Silver	Petzl	M53 S	13D946
Rope Termination Plates				
For 3-strand Twisted Synthetic Ropes, ½ in to ¾ in Kernmantle	Blue	Falltech	8349	60XH67
For Rescue Ropes	Red	MSA	SRIW1000	60UJ41
Swivels				
Swivel, 2-Person Load	Black/Red	Petzl	P58 L	3NGF2
Gated Swivel	Black	Petzl	P58 SO	35ZM16