



**MOON**American, Inc.™

## Plain Brass Hose Nozzles

▪ Max. pressure: 100 psi  
Straight-stream flow; not adjustable.  
For use on fire hose racks and reels and other industrial applications.

Activates By	Inlet Size	Waterway	Thread Type	Brand	Item No.
Constant On	¾ in	¼ in	GH	Moon American	6ANW1
	¾ in	¼ in	NPSH	Moon American	6ANW2
	1 in	¾ in	NH	Moon American	6ANV6
	1 in	¾ in	NPSH	Moon American	6ANV5
	1 ¼ in	¾ in	NPSH	Moon American	6ANV7
Shutoff Handle	1 ½ in	¾ in	NH	—	6AKC5
	1 ½ in	¾ in	NPSH	—	6AKC4
	2 in	¾ in	NPSH	Moon American	6ANV8
	2 ½ in	¾ in	NH	Moon American	6ANW0
	2 ½ in	¾ in	NPSH	Moon American	6ANV9
Shutoff Handle	1 ½ in	½ in	NH	Moon American	6APP6
	1 ½ in	½ in	NPSH	Moon American	6APP5



**6APP5**

**MOON**American, Inc.™ **ELKHART** BRASS

## Industrial Fog Nozzles

▪ Max pressure: 100 psi  
▪ Straight-stream, twist-to-activate nozzles  
**6APP7, 6APTO** and **6APT1**—Compact, lightweight aluminum nozzles have a powder-coated finish and a thick rubber bumper. Suitable for industrial washdown, forestry, and irrigation applications.

**15Z194**—Polycarbonate nozzle with rigid base. Helps combat blazes in refineries, chemical plants, office complexes, and other industrial locations. Designed for Class C hazards and for use on blazes 10 ft. or more from live electrical equipment and/or circuits up to 250,000V.



Inlet Size	Thread Type	Flow Rate	Finish	Brand	Item No.
¾ in	GH	10 to 24 gpm	Aluminum	Moon American	6APP7
	NH	10 to 24 gpm	Aluminum	Moon American	6APP9
1 in	NPSH	10 to 24 gpm	Aluminum	Moon American	6APP8
	NH	20 to 60 gpm	Aluminum	Moon American	6APT0
1 ½ in	NPSH	20 to 60 gpm	Aluminum	Moon American	6APT1
	NH	75 gpm	Polycarbonate	Elkhart Brass	15Z194

**MOON**American, Inc.™

## Heavy-Duty Industrial Fog Nozzles

▪ Max. pressure: 100 psi  
Recommended for high-volume service demands. Straight-stream, twist-to-activate nozzles can deliver fog stream in 30°, 60°, and 90° patterns. Bronze construction with a bumper.

Inlet Size	Thread Type	Flow Rate	Std.	Brand	Item No.
1 in	NH	36 gpm	—	Moon American	6ANV3
1 in	NPSH	36 gpm	—	Moon American	6ANV2
1 ½ in	NPSH	130 gpm	UL Listed	—	6AKC1
1 ½ in	NST	130 gpm	UL Listed	—	6AKC2
2 in	NPSH	108 gpm	—	Moon American	6ANV4
2 ½ in	NST	205 gpm	UL Listed	—	6AKC3



**MOON**American, Inc.™

## Thermoplastic Hose Nozzles

▪ Max. pressure: 100 psi  
Twist-to-activate nozzles for washdown, dust suppression, or any other application where adjustable fog nozzles are needed to disperse water.



Inlet Size	Body Material	Thread Type	Flow Rate	Std.	Item No.
<b>Moon American, Fire Hose Nozzles</b>					
¾ in	Polycarbonate	NPSH	8 gpm	—	6ANW6
1 in	Polycarbonate	NH	22 gpm	—	6ANW5
2 ½ in	Polycarbonate	NH	150 gpm	UL Classified	6APN5
<b>Approved Vendor, Fire Hose Nozzles</b>					
¾ in	Plastic	GHT	35 gpm	—	6AKC6
1 ½ in	Plastic	NPSH	80 gpm	—	6AKC7
1 ½ in	Plastic	NST	80 gpm	—	6AKC8
<b>Dixon Valve &amp; Coupling, Fire Hose Nozzles</b>					
¾ in	Polycarbonate	NPSH	30.9 gpm	FM Approved	6CLV9
1 in	Polycarbonate	NPSH	30.9 gpm	FM Approved	6CLW0
1 ½ in	Polycarbonate	NPSH	75 gpm	—	6CLW1

Inlet Size	Body Material	Thread Type	Flow Rate	Item No.
<b>Moon American, Spray Nozzles</b>				
¾ in	Polycarbonate	GHT	8 gpm	4KR35
1 in	Polycarbonate	NPSH	22 gpm	4KR32
1 ½ in	Polycarbonate	NPSH	75 gpm	4KR34
1 ½ in	Polycarbonate	NST	75 gpm	4KR33

<b>Moon American, Nozzle Gaskets</b>				
1 ½ in	Nozzle Gasket, EDPM, For Use With 4RK34			6ANW8
1 ½ in	Nozzle Gasket, EDPM, For Use With 4RK33			6ANW9

**MOON**American, Inc.™

## Forestry Nozzles

Twist-to-activate nozzle for use in woodland environments.

**Break-Apart Nozzles**—Pistol grip.

**Jet and Fan Nozzle**—Bale handle grip.



Inlet Size	Body Material	Max. Pressure	Thread Type	Flow Rate	Spray Pattern	Std.	Item No.
<b>Break-Apart Nozzles</b>							
1 in	Aluminum	100 psi	NH	10-24 gpm	Fog/Straight Stream	—	41H468
1 in	Aluminum	100 psi	NPSH	10-24 gpm	Fog/Straight Stream	—	41H467
1 ½ in	Aluminum	100 psi	NH	20-60 gpm	Fog/Straight Stream	—	41H470
1 ½ in	Aluminum	100 psi	NPSH	20-60 gpm	Fog/Straight Stream	—	41H469
<b>Jet and Fan Nozzle</b>							
¾ in	Aluminum	200 psi	GH	22 gpm	Straight Stream/Fan	—	41H482
<b>Nozzle with Shut Off</b>							
1 in	Aluminum	600 psi	NPSH	10-25 gpm	Fog	NSN 4210-01-165-6603	41H477