

speco technologies



## Quick-Install Speaker Assembly

- 90 dB sensitivity
- 70/25V pigtail leads
- 8 ohm impedance

Lay-in ceiling mount system replaces a standard 24" x 24" ceiling tile. Polypropylene woofer, mylar tweeter. Includes a 2-ft L drop ceiling crossbar rail.



Watt (RMS)	Max. Wattage	Frequency Response	Woofer Dia.	Tweeter Dia.	Overall H	Overall W	Overall Length	Item No.
30 W	60 W	50Hz to 20,000Hz	8 in	¾ in	23 in	23 in	6 in	2KJY1

Edwards Signaling

speco technologies



## Horn Speakers

Designed for telephone and microphone paging in loud environments, both indoors and out. Mounting brackets and hardware included.

### Explosionproof Audible Signal

**Multitone Horn**—Has a 55-tone capability and internal volume control.

### Hazardous Location Multitone

**Horn**—Includes a 55-tone capability. For use in dusty and hazardous areas where a distinctive alert is required. For Division 2 locations.

**36H458**—An amplified weatherproof PA speaker; designed for applications that can benefit by not having a dedicated amplifier.

**Universal RMS Driver**—Features built-in line transformers.

**Transformer**—Works with most brands of horn speakers. Flange mount.



ABS Plastic  
3CWU8



ABS Plastic  
3CWX2



Aluminum  
2KJW2



Aluminum  
2KJW3

Impedance	Sensitivity	Max. Wattage	Watt (RMS)	Frequency Response	Overall H	Overall W	Overall Length	Encl. Material	Brand	Item No.
<b>Multi-Tone Horn - Explosionproof Audible Signal</b>										
—	90 dB	—	—	—	11 ¼ in	11 ¼ in	18 ½ in	Cast Aluminum	Edwards Signaling	13T112
<b>Multi-Tone Horn - Hazardous Location, 24VDC</b>										
—	110 dB	—	—	—	15 in	8 ½ in	8 in	Cast Zinc	Edwards Signaling	13T111
<b>Paging Speakers</b>										
8 ohm	107 dB	40 W	30 W	400Hz to 6kHz	9 1/16 in	6 5/16 in	11 in	ABS Plastic	—	3AXC9
8 ohm	107 dB	25 W	15 W	400Hz to 6kHz	9 1/16 in	6 5/16 in	11 in	ABS Plastic	—	3AXC8
<b>PA Horns</b>										
8 ohm	105 dB	15 W	10 W	250 to 15,000Hz	6 in	6 in	6 in	Aluminum	Speco Technologies	3CWU7
8 ohm	110 dB	30 W	15 W	200 to 15,000Hz	4 in	6 in	8 in	ABS Plastic	Speco Technologies	3CWX1
8 ohm	105 dB	15 W	10 W	300 to 15,000Hz	5 in	5 in	5 in	ABS Plastic	Speco Technologies	3CWU8
8 ohm	120 dB	32 W	15 W	250 to 15,000Hz	11 in	6 ½ in	13 in	ABS Plastic	Speco Technologies	3CWX2
<b>PA Weatherproof Horn</b>										
3-16 ohm	—	20 W	—	500Hz-5kHz	—	—	—	—	Speco Technologies	36H458
<b>PA Weatherproof Speakers</b>										
8 ohm	110 dB	25 W	15 W	200Hz to 15,000Hz	8 in	8 in	8 in	Aluminum	Speco Technologies	2KJW2
8 ohm	110 dB	25 W	15 W	200Hz to 15kHz	5 in	8 in	8 in	Aluminum	Speco Technologies	2KJW3
8 ohm	105 dB	15 W	6 W	300Hz to 15kHz	5 1/4 in	5 1/4 in	6 in	ABS Plastic	Speco Technologies	2KJW6
8 ohm	105 dB	30 W	15 W	450Hz to 15,000Hz	8 in	8 in	9 in	Aluminum	Speco Technologies	2KJW4
8 ohm	120 dB	30 W	20 W	250Hz to 16,000Hz	8 in	11 in	10 1/4 in	ABS Plastic	Speco Technologies	2KJW5
<b>Universal RMS Driver (70V)</b>										
16 ohm	112 dB	100 W	80 W	300 to 5000Hz	7 in	3 1/4 in	—	Aluminum	Speco Technologies	3CWU5
<b>Transformer</b>										
—	—	—	—	—	1 1/4 in	1 5/8 in	2 5/8 in	—	Speco Technologies	2KJP4

speco technologies



## Amplifiers and Tuner

**PA Amplifiers**—Provide power to paging and music address systems. **2KJU4**—On-hold feature assures customers hear supplied music or dialogue.

### PA Amplifiers with Multiple Zones

Allow different or same audio sources to be played in different rooms simultaneously.

**PA Amplifier with AM/FM Tuner**—Works with most amplifiers to play radio broadcasts. Includes 30 presets.



2KJU4



49CA21



2KJT7

Output Watts	Inputs	Output	Includes	Item No.
<b>PA Amplifiers</b>				
30 W	(2) Mics, Auxiliary, Telephone Paging	70/25V	Music On Hold Feature with Separate Level Control	2KJU4
15 W	(1) Auxiliary, (2) Mics	4/8/16 Ohms, 70/25V	—	36H471
30 W	2 Mics and 1 Auxiliary	4/8/16 Ohms, 70/25V	—	36H472
120 W		25/70V	AC Power Cord, IR Remote Control, Rack Mounting Brackets	49CA18
120 W		25/70V	AC Power Cord, AM Antenna, IR Remote Control, Rack Mounting Brackets	49CA19
120 W		25/70V	AC Power Cord, AM Antenna, CD, IR Remote Control, Rack Mounting Brackets, USB	49CA20
60 W	(3) Auxiliary Stereo RCA, (3) Mic XLR, 1-RS-232, Telephone	25/70V	AC Power Cord, IR Remote Control, Rack Mounting Brackets	49CA21
60 W		25/70V	AC Power Cord, AM Antenna, IR Remote Control, Rack Mounting Brackets	49CA22
60 W		25/70V	AC Power Cord, AM Antenna, CD, FM Antenna, IR Remote Control, Rack Mounting Brackets, USB	49CA23
240 W	(3) Auxiliary Stereo RCA, (3) Mic XLR, 1-RS-232, AM Antenna	70V	AC Power Cord, IR Remote Control, Module Bay, Rack Mounting Brackets	49AH98
240 W	Press Terminal, FM Antenna BNC, Telephone Terminal	70V	AC Power Cord, IR Remote Control, Rack Mounting Brackets, Tuner Module	49AH99
240 W	(1) AM Antenna (Press Terminal), (1) FM Antenna (BNC), (1) Telephone (Terminal), (3) Auxiliary (Stereo RCA), (3) Mics (XLR)	4/8 Ohms (Non-Zoned), 70V (Zoned)	AC Power Cord, AM Antenna, FM Antenna, IR Remote Control, Rack-Mountable Brackets	49NU92
<b>PA Amplifiers with Multiple Zones</b>				
260 W	(1) EQ/Mix, (1) Telephone Paging, (3) Auxiliary, (5) XLR Mics	4/8/16 Ohms, 70/25V	Music On Hold Feature with Separate Level Control	2KJU6
40W	(2) RCA, (3) XLR 7/16 in, Combination	160 W	—	3CWR5
<b>PA Amplifier with AM/FM Tuner</b>				
30 W	(1) Auxiliary, (1) Telephone, 2 XLR Connections	25/70V	30 Presets	2KJT7