Master AHIF

Key-Controlled Scrolling Combination Padlocks

4-digit resettable combination
General security

Padlocks open by turning a scrolling mechanism to the correct combination but can also be opened using a key if a user forgets the combination. They are typically used in schools. Control keys are sold separately and must match the control key code specified by the padlock.

Vertical Shackle Clearance	Horizontal Shackle Clearance	Shackle Dia.	Dial Color	Dial Location	Lock Body Material	Lock Body Color	Body Width	Body Thickness	Control Key Code	Brand	Item No.	
Standard Shackle												
Hardened Steel Shackle Material												
1 in	1 in	5/16 in	Gold	Bottom	Brass	Gold	2 in	15/16 in	P569	Master Lock	4HY70	
Steel Shackle Material												
63/64 in	25/32 in	15/64 in	Silver	Side	Zinc Die-Cast	Black	1 49/64 in	3/4 in	AP050	ABUS	14J899	
Long Shackle												
Hardened Steel Shackle Material												
2 1/4 in	1 in	5∕16 in	Gold	Bottom	Brass	Gold	2 in	15/16 in	P225	Master Lock	3KJJ2	



Standard Hardened Steel Shackle Steel Shackle 4HY70



Standard

Long Hardened Steel Shackle

Brand	Item No.		
Master Lock	4HY71		
ABUS	16P022		
Master Lock	3JYV7		
	Master Lock ABUS		

Master Lock



Luggage Padlocks

Standard shackle
General security
Resettable

Padlocks secure access to personal property in luggage, briefcases, and travel bags. They open by turning a scrolling mechanism to the correct combination, and they don't require a key. 2RUF9 Password Plus uses letters, numbers, and symbols for custom passwords. 38W808 and 38W810 are TSA-approved and have a side window for viewing the combination, so TSA screeners can inspect and relock baggage without damaging the lock.



Password Plus Hardened Steel Shackle Cylindrical Lock Body 2RIIF9



TSA-Accepted Steel Square Lock Body 38W810



Steel Shackle Gold Rectangular **Lock Body** 1XRW6



Standard Steel Shackle Rectangular Black **Lock Body** 4FG14

Vertical Shackle Clearance	Horizontal Shackle Clearance	Shackle Dia.	Dial Color	Dial Location	Padlock Body Shape	Lock Body Material	Lock Body Color	Body Width	Body Thickness	No. of Digits	Brand	ltem No.
Hardened Steel S	Shackle Material											
1 1/8 in	1 ¾ in	1/4 in	Black	Front	Cylindrical	Zinc Die-Cast	Silver	2 ½ in	1 in	5	Master Lock	2RUF9
Steel Shackle Ma	aterial											
3/4 in	1/2 in	1/8 in	Silver	Side	Square	Zinc Die-Cast	Silver	1 3/16 in	5⁄8 in	3	Master Lock	38W810
3/4 in	9/16 in	3∕16 in	Gold	Side	Rectangular	Brass	Gold	1 ¾16 in	3/8 in	4	_	1XRW6
7∕8 in	7⁄8 in	1/4 in	Silver	Side	Rectangular	Aluminum	Silver	1 9/16 in	9/16 in	4	Master Lock	6MCR4
7∕8 in	3⁄8 in	3∕16 in	Silver	Side	Rectangular	Zinc Die-Cast	Black	1 ¾16 in	½ in	3	Master Lock	4FG16
11/ ₁₆ in	3% in	1/8 in	Silver	Side	Rectangular	Zinc Die-Cast	Black	13/16 in	3/8 in	3	Master Lock	4FG15 *
11/ ₁₆ in	3/8 in	1/8 in	Silver	Side	Rectangular	Zinc Die-Cast	Black	13/16 in	3⁄8 in	3	Master Lock	4FG14
55/64 in	²³ / ₆₄ in	1/8 in	Silver	Side	Rectangular	Aluminum	Black	57/64 in	17/32 in	3	ABUS	5JKR8
63/64 in	35/64 in	13/64 in	Silver	Side	Rectangular	Aluminum	Red	1 39/64 in	11/16 in	4	ABUS	5JKU4
1 in	9/16 in	3∕16 in	Silver	Side	Rectangular	Aluminum	Silver	1 3/16 in	½ in	3	Master Lock	6MCR3
1 ½ in	5% in	1/8 in	Silver	Front	Rectangular w/Rounded Corners	Zinc Die-Cast	Blue	1 ¾16 in	½ in	3	Master Lock	38W808





Cable Locks, Security Cables, and Security Chains

anchor point and lock with a key, combination, or both. They are used with items that cannot be secured with a padlock. Vinyl coating helps prevent scratching, 6JD76 and 6JD75 have integrated locks.

Security Cables—Flexible cables wrap around large or bulky items like fences and are secured with a padlock. 3NY54 and 3UU68 Python patented locks hold cable at any position.

Cable Locks—Flexible cables wrap around equipment and an Braided steel wire cable has looped ends for use with U-locks or padlocks. Vinyl coated.

> Security Chains—Tough chains are secured with a padlock to restrict access to high-value items. They are enclosed in a nylon sleeve that protects the chain from damage.

Removable Steel Shackle Padlock-U-shaped lock has double-locking hardened steel removable shackle, heavy-duty cable and chain, and 7-pin tubular cylinder.

Cah	le Lock T	vne	Cable Lengt			le Material	Weathe Resistan		Key Type		Brand	Item No.	Pkg. Qty.
Cable Locks		,,,,		5	0.0.		11001014		.,,,,		J. uu		u.y.
Fixed Lengt	th Cable I	_ocks	6 ft	3/8	in Bra	aided Steel	Yes	Di	fferent	Ma	ster Lock	3NY54	1
Fixed Lengt	th Cable I	_ocks	6 ft	3/8	in Bra	aided Steel	Yes		Alike	Ma	ster Lock	3UU68	1
Fixed Lengt	th Cable I	_ocks	6 ft	3/8	in Bra	aided Steel	Yes	Di	fferent	Ma	ster Lock	6JD76	1
Fixed Lengt	th Cable I	_ocks	5 ft	3/8		aided Steel	Yes	Combination		Master Lock		6JD75	1
Fixed Lengt			6 ft	5/16		aided Steel	Yes	Alike		Master Lock		4EZN6	3
Adjustable			6 ft	25/64		Steel	No	Different		ABUS		19YM73	11
Adjustable	Length C	able Locks	6 ft	25/64	in	Steel	No Differer		fferent	ABUS		19YM75	11
Cable Style	Cable Length	Cable Diameter	Cable Material	Weather Resistant	Brand	ltem No.	Chain Length	Chain Diameter	Chain Material	Chain Finish	Weathe Resista		Item No.
Security Ca							Security Ch						
Coiled	72 in	3% in	Steel	Yes	Master Lock	6JD72	2 ft	1/4 in	Steel	Zinc	Yes	ABUS	3PCE4
Coiled	72 in	1/4 in	Steel	Yes	Master Lock		2 ft	5∕16 in	Steel	Zinc	Yes	ABUS	3PCE5
Coiled	180 in	¾ in	Steel	Yes	Master Lock	38W815	2 ft	3⁄8 in	Steel	Zinc	Yes	ABUS	3PCE6
Straight	8 ft	5∕16 in	Steel	Yes	ABUS	14Z344	2 ft	½ in	Steel	Zinc	Yes	ABUS	3PCE7
Straight	6 ½ ft	²⁵ / ₆₄ in	Steel	Yes	ABUS	14Z345	10 ft	1/4 in	Steel	Zinc	Yes	ABUS	3PCF4
	16 ½ ft	²⁵ / ₆₄ in	Steel	Yes	ABUS	14Z346	10 ft	5∕16 in	Steel	Zinc	Yes	ABUS	3PCF5
Straight	32 ¾ ft	²⁵ / ₆₄ in	Steel	Yes	ABUS	14Z347	10 ft	3% in	Steel	Zinc	Yes	ABUS	3PCF6
							10 ft	½ in	Steel	Zinc	Yes	ABUS	3PCF7
Body Height		n Thicl	kness	ertical Shac Clearance		izontal Clearance	Shackle Width	Shackle Diameter	Weathe Resistar		Key Type	Brand	Item No.
Removable Steel Shackle Padlock, General Security													
2 13/16 in	3 15/16	in 1	9/8"	2 in	1	5/8 in	1 5/8 in	1/2 in	No	Di	fferent	Master Lock	6JD74





Removable Steel Shackle **Padlock** 6JD74