



## **InVid**

# **Hybrid Video Recorders**

Video compression format: H265/H264

These recorders allow you to have both analog and IP systems running at the same time on the same system. This technology is a great addition to an already established security system for your business or facility. This enables you to upgrade your surveillance system to IP equipment at your own pace, according to your budget. Include central management software disk, mouse, power cord, power supply, remote, remote control, and SATA cables. Resolution: Analog Channel: 5MP Lite@10 fps, 4MP Lite/1080P@ 15 fps (NTSC) 1080P Lite/720P/WD1/D1@/30 fps (NTSC). IP Channel: 30 fps (NTSC)

No. of Analog	No. of IP	Included Hard	Max. Frames	Video Evport Function	December Mades	u u	w		Item
	Camera Inputs	Drive Size	per Second	Video Export Function	Recording Modes	H	W	D	No.
12V DC @ 4 A									
16	8	2 TB	480 fps			45 mm	268 mm	268 mm	61KR76
16	8	4 TB	480 fps	External HDD, Internal HDD, Network, USB	Continuous, Motion, Schedule,	45 mm	268 mm	268 mm	61KR79
16	8	6 TB	480 fps			45 mm	268 mm	268 mm	61KR81
16	8	8 TB	480 fps			45 mm	268 mm	268 mm	61KR84
16	8	12 TB	480 fps			45 mm	268 mm	268 mm	61KR85
16	8	16 TB	480 fps			45 mm	268 mm	268 mm	61KR86
16	8		480 fps			45 mm	268 mm	249 mm	61KR74
12V DC @ 2 A									
8	4	2 TB	240 fps		Continuous, Motion, Schedule, Continuous, Schedule, Smart Recording	45 mm	249 mm	249 mm	61KR75
8	4	4 TB	120 fps	External HDD, Internal HDD, Network, USB		45 mm	249 mm	249 mm	61KR78
8	4	8 TB	240 fps			45 mm	249 mm	249 mm	61KR83
8	4		240 fps			45 mm	249 mm	249 mm	61KR71
4	2	2 TB	120 fps			45 mm	249 mm	249 mm	61KR73
4	2	4 TB	120 fps			45 mm	249 mm	249 mm	61KR77
4	2	6 TB	120 fps			45 mm	249 mm	249 mm	61KR80
4	2	8 TB_	120 fps			45 mm	249 mm	249 mm	61KR82
4	2	500 GB	120 fps			45 mm	249 mm	249 mm	61KR72
4	2		120 fps			45 mm	249 mm	249 mm	61KR70











## Video Surveillance Pan-Tilt-Zoom Controllers

Security camera controllers allow you to manage a number of surveillance cameras. They're compatible with many video management systems and designed to control pan-tilt-zoom cameras (also known as PTZ cameras) capable of remote directional and zoom control.

Description	Camera Inputs	Display Type	Power Supply	Brand	ltem No.
Keyboard Controller	32	Speed Dome	Included	Speco Technologies	36K084
Digital Keyboard	_	_	350 mA	Bosch	45LA11
PTZ Keyboard	Variable	LCD	12V DC	LTS	48ZV55
PTZ Joystick/Keyboard	Variable	LCD	12V DC @ 0.5A	LTS	404N51















#### Video Surveillance Monitors

Universal color monitors for use with security cameras, network video cameras, DVRs, quad splitters, multiplexers, and other video devices.

### **PORTABLE LCD TEST MONITOR**

Headphone jack allows audio testing. Video/audio connector: RCA with BNC plug adapter. Includes 12VDC power supply, 4-hr. rechargeable battery, charger, video cable, and carrying case.

#### **LED MONITORS WITH VGA**

Feature full high-definition LED panels with multiple inputs including VGA, AV, USB, and HDMI. Designed for 24/7 applications with standard vesa pattern on the back for wall mounting. Includes built-in speakers.

#### **LED MONITORS WITH VGA AND BNC OUTPUT**

- Display up to 16.7 million colors
- VGA (D-Sub 15 pins) and BNC video output

Flat-panel screen features backlit LCD and built-in stereo speakers. Required for high-resolution surveillance. Includes regulated 12VDC, 5A power supply. VESA compatible.

	Screen	Line				Cabinet		Item
	Size	Resolution	Н	W	D	Color	Brand	No.
	Portable	rtable LCD Test Monitor						
	4 in	480 x 234	5 ¼ in	6 in	3 in	Black	Speco Technologies	6LU93
	LED Moni	tors with VGA						
	21 ½ in	1920 x 1080	15 1/32 in	22 in		Black	Vitek	56HA14
	21 ½ in	1920 x 1080	16 13/64 in	20 5/16 in	2 13/32 in	Black	Speco Technologies	33RL96
LED Monitors with VGA and BNC								
	17 in	1280 x 1024	15 23/64 in	15 ½ in	2 49/64 in	Black	Tatung	34KJ75
	17 in	1280 x 1024	14 7/64 in	15 1/8 in	7 13/16 in	Black	Invid Tech	451V41

1968