



**Cylindrical Standard 24U106**



**Keypad Starter Package 24U117**



**Keypad 24U119**



**Cylindrical Standard 24U108**



**Exit Device 24U114**



**Keypad Starter Package 24U116**



**Wireless Control Panel 24U120**

## Trilogy Networkx Networking Locks, Grade 1

- Key for manual override
- Weather-resistant; Operating temp.: -31° to 151°F
- Brushed chrome finish

Networked door access control systems eliminate door-to-door programming and audit trail retrieval by communicating wirelessly via 802.11B/G or Ethernet. No wires to run and no access panel or power supplies to install. Feature automatic schedules, event logs, and support for 2000 doors and 5000 existing proximity ID cards/badges.

### PIN/ID CARD CONTROL

Programmable Locks 24U106 to 24U113 have built in HID proximity card reader, full-metal digital key pad, integral bidirectional radio, batteries, and serial number ID card. Starter Kit 24U117 includes NET-DKPAK and NET-PDKPAK controller and keypad. Keypad 24U119 supports 3 to 6 digit numeric PIN codes and prox ID card users (virtually all HID format proximity technology ID cards, fobs, and credentials).

### CODE ONLY

Programmable Locks 24U108 to 24U111 have full-metal digital keypad for code only use. Starter Kit 24U116 includes NET-DKPAK and NET-PDKPAK controller and keypad. Keypad 24U118 supports 3 to 6 digit numeric PIN codes.

### ACCESSORIES

Control Panel 24U120 includes circuit board with onboard flash memory and 12V power supply with transformer and rechargeable back-up battery. Supports 2 of any combination of NETDK or NETPDK keypads plus 2 Wiegand devices. Special 2-door mode allows 2 keypads and/or 2 Wiegand devices to separately control 2 doors. Ceiling or wall mount. 1 antenna and 6VAC transformer included.

Description	Hand	Keying	Max. User Codes	Mfr. Model	Item No.
<b>Programmable Lock, PIN/ID Card Control</b>					
Cylindrical	Nonhanded	Standard	5000	PDL6100 US26D	24U106
Cylindrical	Nonhanded	Small Format Interchangeable Core	5000	PDL6100IC US26D	24U107
Mortise	Right	Standard	5000	PDL6500CRR US26D	24U112
Mortise	Left	Standard	5000	PDL6500CRL US26D	24U113
Von Duprin Exit Device	Nonhanded	Standard	5000	ETPONS1G/26DV99	24U115
Keypad Starter Package	—	Standard	5,000	NETPSKPAK US26D	24U117
Keypad Only	—	—	5,000	NETPDK US26D	24U119
<b>Programmable Lock, Keypad Control, Code Only</b>					
Cylindrical	Nonhanded	Standard	5000	DL6100 US26D	24U108
Cylindrical	Nonhanded	Small Format Interchangeable Core	5000	DL6100IC US26D	24U109
Mortise	Right	Standard	5000	DL6500CRR US26D	24U110
Mortise	Left	Standard	5000	DL6500CRL US26D	24U111
Von Duprin Exit Device	Nonhanded	Standard	5000	ETDLNS1G/26DV99	24U114
Keypad Starter Package	—	—	5,000	NETDKPAK US26D	24U116
Keypad Only	—	—	5,000	NETDK US26D	24U118
<b>Accessories</b>					
Wireless Control Panel	—	—	—	NETWORKXPANEL	24U120
Proximity ID Fobs, Pkg. of 10	—	—	—	ALHID1346	1HYC1
Adhesive Proximity Tags, Pkg. of 10	—	—	—	ALHID1391	1HYC2
Proximity ID Cards, Pkg. of 100	—	—	—	ALHID1326	1HYB9



**Programmable Lock, Single-Sided, Satin Chrome**



**Programmable Lock, Double-Sided**



**Narrow-Stile**



## Trilogy Keyless Electronic Control Locks, Grade 1

- Key override; standard core (included) or SFIC cylinder (not included, sold on Grainger.com)
- Operating temp.: -31° to 151°F except 3ZM80, 3ZM83, and 3ZM81

Easily replace keyed locks with these electronic access control locks. Compatible with most doors that have a standard knob set. Fingertip-programmable keypad allows up to one hundred 3- to 5-digit codes. DL2700-series locks can create a 3-tiered hierarchy of custom codes: 1 master, 10 managers, 90 standard codes, and three 1-time-use codes. Low battery alert. Include 5 AA batteries (up to 150,000 cycles), except 3CCK6, which includes 2 lithium batteries (80,000 cycles). Double-sided models are for code control on both sides of the door.

Description	Finish	Weather Resistant	Key Override Options	Mfr. Model	Item No.
<b>Programmable Lock, Code Control</b>					
Single-Sided	Satin Chrome	No	Standard SC1 Keyway	DL2700 US26D	3ZM80
Single-Sided	Satin Chrome	No	Small Format Interchangeable Core	DL2700IC US26D	3ZM83
Single-Sided	Satin Chrome	Yes	Standard SC1 Keyway	DL2700WP US26D	6JD79
Single-Sided	Satin Chrome	Yes	Small Format Interchangeable Core	DL2700WPIC US26D	6JD80
Single-Sided	Bright Brass	No	Standard SC1 Keyway	DL2700 US3	3ZM81
Double-Sided	Satin Chrome	Yes	Standard SC1 Keyway	DL5200 US26D	3CCK7
Double-Sided	Satin Chrome	Yes	Small Format Interchangeable Core	DL5200IC US26D	3CCK8
<b>Narrow Stile, Exit Devices, Programmable Lock, Code Control</b>					
Adams Rite	Satin Chrome	Yes	Standard SC1 Keyway	DL1200/26D1	1YND2
Von Duprin	Satin Chrome	Yes	Standard SC1 Keyway	DL1200ET/26D	3CCK6