





	D	W	Mfr.	Item
Keying	(in.)	(in.)	Model	No.
PowerPlex Self-Power	ed			
Schlage "C"	33/16	35/16	P2031XSLL62641	6NVN9
Best & Equivalents	3¾16	35/16	P2031BLL62641	6NVP0
Battery-Powered				
Schlage "C"	213/16	35/16	E2031XSLL62641	2ZU99
Best & Equivalents	2 <sup>13</sup> /16	35/16	E2031BLL62641	1NEZ7

# 2000 Series, Grade 1 Electronic Push-Button Locks

- 100 individual user codes
- For 1%"- to 2½"-thick doors: 2¾" backset

No wiring to install. Nonhanded, field-reversible locks have a vandal-resistant, all-metal keypad and a solid cast exterior housing and lever. Classroom/storeroom function; no code required for egress. Come with a standard core or are prepped for a SFIC cylinder (not included). Include lock assembly, installation manual, template, reference guide, operations manual, and hardware. Retrofit standard ASA 161 door preps.

PowerPlex Self-Powered—Efficient and innovative electronic locks generate power with each turn of the lever; no batteries required and virtually no maintenance costs. 6NVN9 includes Schlage C keyway, 2 keys. 6NVP0 is for use with Best SFIC 6- or 7-pin length, not included.

Battery-Powered—Feature audible low battery alert, timed relock, codes for 1-time use, antitamper function (invalid entry), and total user lockout codes. Include 3 AA batteries.







Protective keypad covers available, see page 1979.

			SATIN CHROME		ANTIQUE BRASS	
Description	Keying	Hand	Mfr. Model	Item No.	Mfr. Model	Item No.
Programmable Loc	ks, Push-Button, Grade 1	(5000 Series)				
Lever	KIL	Reversible	5021-XS-WL-26D-41	2ZU95	_	
Lever	SFIC	Reversible	5021-B-WL-26D-41	5BB73 *	_	_
Exit Trim, Lever	KIL	Reversible	5010-XS-WL-26D-41	2ZV18	_	
Programmable Loc	ks, Push-Button (L1000 S	Series)				
Lever	Standard	Left	LL-1011-26D-41	5U740	LL-1011-05-41	5U739
Lever	Standard	Right	LR-1011-26D-41	5U742	LR-1011-05-41	5U741
Lever	SFIC	Left	LL-1021-B-26D-41	4YF90 *	LL-1021-B-05-41	4YF89 *
Lever	SFIC	Right	LR-1021-B-26D-41	4YF92 *	LR-1021-B-05-41	4YF91 *
Knob	Standard	Reversible	1011-26D-41	1U140	1011-05-41	1U092
Lever	KIL	Reversible	5021XKWL26D41	9LDD6	_	
Knob	SFIC	Reversible	1021-B-26D-41	4YF88 *	1021-B-05-41	4YF87 *
Knob, Passage	Standard	Reversible	1031-26D-41	1U141	1031-05-41	1U083
Mechanical Push I	Button Lockset					
Knob	Combination Access	Reversible	EE11/1126D41	31NG48	_	
Lever	R/C Schlage	Left	LL1021S26D41	31NG77	_	
Lever	R/C Schlage	Right	LR1021S26D41	31NG80	_	
* Cylinders not incl	uded.					

# **SIMPLEX**°

## Mechanical Access Control Push-Button Locks

- 1 user code
- For 1¾"- to 2¼"-thick doors; 2¾" backset, ½" latch bolt
- Include ASA standard strikes

Provide an alternative to traditional keyed locksets. Classroom/storeroom function, no code required for egress. Retrofit standard ASA 161 door preps.

#### PROGRAMMABLE LOCKS, PUSH-BUTTON, GRADE 1 (5000 SERIES)

Standard KIL core included. Simple 4-screw installation. Compatible with most rim exit devices.

#### PROGRAMMABLE LOCKS, PUSH-BUTTON (L1000 SERIES)

Measure 9"L (inside) x  $3\frac{1}{8}$ "W x  $3\frac{3}{16}$ "D.





Knob

# Mechanical Access Control Locks SIMPLEX

- 1 user code
- For 1%"- to
- 21/2"-thick doors
- 2 cover plates included with each lock
- Satin Stainless Finish

Vandal-resistant, all-metal keypad. Nonhanded, field reversible. Lever locksets are  $7\%_6"L \times 2\%'W \times 3"D.$  Breakaway lever helps keep vandals from damaging drive components. Knob locksets are  $6\%_6"L \times 2\%_6"W \times 3"D.$  No batteries required.

Description	CHOOSE: Backset	ltem No.
Lever Lockset	2% in, 2¼ in	D0001
Knob Lockset	2% in. 2¼ in	D0002

With Deadlocking Latch



CHOOSE: Door Thickness	CHOOSE: Finish	Item No.
With Deadbolt		
1 % to 1 ½, 1 ¾ to 2 ½	Satin Brass, Satin Chrome	D0003
With Deadlocking Latch and Hold	lback	
1 % to 1 ½, 1 ¾ to 2 ½	Satin Brass, Satin Chrome	D0004
With Deadlocking Latch, No Hold	-Back	
1 % to 1 ½, 1 ¾ to 2 ½	Satin Brass, Satin Chrome	D0005
Metal Frame Adapter Kit	<u> </u>	
	Satin Brass Satin Chrome	D0006

### **900 Mechanical Access Control**



■ 1 user code

■ 21/2" backset

Classroom/storeroom function, no code required for exit. Nonhanded, field reversible. No batteries required. Can be used alone or with an existing lockset. Require a 15/8"-dia. mounting hole. Measure 4"W x 5"H.

Note: All locks include a sheet metal strike for outswing doors and a cast box strike for inswing wood frame installation.

**With Deadbolt**—Deadbolt extends 1" from edge of door. Lock remains open and must be manually relocked. Egress by thumbturn.

#### With Deadlocking Latch and Holdback—

SIMPLEX

Helps secure latch against prying. Automatically relocks after egress, except when latch hold-back is activated. No code is required for entry. Exit by thumbturn.

#### With Deadlocking Latch, No Hold-

**Back**—Helps secure latch against prying. Automatically relocks after egress.

**Metal Frame Adapter Kit**—Includes surface-mounted strike with shims to adjust strike box. With  $\frac{1}{4}$ " x  $\frac{3}{8}$ " reversible riser plate for aligning inside housing to strike.