ALARM CONTROLS ASSA ABLOY | hes ASSA ABLOY | VON DUPRIN®

# Electric Strikes

Electric strikes control access by either holding or releasing a latch bolt. Hard-wire electric strikes connect to a power source and a controller (typically a push-button switch, keypad, or card reader).

A fail-safe electric strike needs power to remain locked.

A fail-secure electric strike remains locked even without power. Device prevents entry; a doorknob or lever on the lock allows for egress.

4WY66

4WY69

4WY71

2MXN2

**Rectifiers—**Convert AC power to DC.

| Description | Failure Mode | Input Voltage | Door Frame Type | Faceplate Dim. W | Faceplate Dim. H | Faceplate Dim. D | Pull Force | Grade | Mfr. Model | Item No. | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **Alarm Controls** | | | | | | | | | | | |
| **Mortise Locksets** | | | | | | | | | | | |
| Medium-Duty | Fail Safe | 12/24 V AC/DC | Aluminum/Hollow Metal/Wood | 1 1/4 in | 4 7/8 in | 1/8 in | 1,000 lb | 2 | AES-200 | **48ZW70** | |
| **Rim Type Exit Devices** | | | | | | | | | | | |
| Heavy-Duty | Fail Safe or Fail Secure | 12/24 V AC/DC | Aluminum/Hollow Metal/Wood | 1 1/4 in | 4 7/8 in | 1/8 in | 1,500 lb | 1 | AES-100 | **48ZW69** | |
| **Hes** | | | | | | | | | | | |
| **Cylindrical Locksets** | | | | | | | | | | | |
| Medium-Duty | Fail Safe or Fail Secure | 12/24 V AC/DC | Metal/Wood | 1 1/4 in | 4 7/8 in | 1 11/16 in | 1,500 lb | 1 | 8300C | **49U739** | |
| Medium-Duty | Fail Safe or Fail Secure | 12/24 V AC/DC | Metal/Wood | 1 1/4 in | 4 7/8 in | 1 11/16 in | 1,500 lb | 1 | 8000C | **49U738** | |
| Heavy-Duty | Fail Safe or Fail Secure | 12 V AC/DC | Hollow Metal | 1 1/4 in | 4 7/8 in | 1 11/16 in | 1,500 lb | 1 | 7501-630-12VDC | **2MXL6** | * |
| **Mortise Locksets** | | | | | | | | | | | |
| Cylindrical Locks and Mortise Locks Without a Deadbolt | Fail Secure | 12/24 V AC/DC | Metal/Wood | 1 1/4 in | 4 7/8 in | 1 11/16 in | 3,070 lb | 1 | 1006CLB | **49U737** | |
| **Rim Type Exit Devices** | | | | | | | | | | | |
| Heavy-Duty | Fail Secure | 12/24 V AC/DC | Metal/Wood | — | — | — | 3,070 lb | 1 | 1006 630 | **28XN34** | |
| Heavy-Duty | Fail Safe or Fail Secure | 12/24 V AC/DC | Metal/Wood | 1 1/4 in | 4 7/8 in | 1/8 in | 1,500 lb | 1 | 5000C-12/24D-630 | **49AV53** | |
| Heavy-Duty | Fail Safe or Fail Secure | 12/24 V AC/DC | Metal/Wood | 1 3/4 in | 9 in | 3/4 in | 2,000 lb | 1 | 9600 629 | **45DJ77** | |
| Heavy-Duty | Fail Safe or Fail Secure | 12/24 V AC/DC | Metal/Wood | 1 3/4 in | 9 in | 1/2 in | 1,500 lb | 1 | 9400-12/24D-630 | **49AV57** | |
| Heavy-Duty | Fail Safe or Fail Secure | 24 V AC/DC | Aluminum | 1 3/4 in | 9 in | 1/2 in | 1,000 lb | 2 | 7000-24-789S-626-GR | **2MXL3** | † |
| Heavy-Duty Surface-Mount | Fail Safe or Fail Secure | 12/24 V AC/DC | Hollow Metal/Wood | 1 3/4 in | 9 in | 3/4 in | 1,500 lb | 1 | 9600-630-GR | **2MXN2** | † |
| Heavy-Duty Surface-Mount | Fail Secure | 12/24 V AC/DC | Hollow Metal/Wood | 1 3/4 in | 9 in | 3/4 in | 1,500 lb | 1 | 9500-630-GR | **2MXN3** | * |
| **Von Duprin** | | | | | | | | | | | |
| **Cylindrical Locksets** | | | | | | | | | | | |
| Medium-Duty | Fail Secure | 12/24 V AC/DC | Aluminum/Hollow Metal/Wood | 1 1/16 in, 1 1/4 in, 1 7/16 in | 4 7/8 in, 7 15/16 in | 1/8 in | 1,000 lb | 1 | 5100-3FP SP28 | **4WY66** | |
| **Cylindrical Locksets and Mortise Locksets (Without Deadbolts)** | | | | | | | | | | | |
| Heavy-Duty | Fail Secure | 24 V AC/DC | Aluminum/Hollow Metal/Wood | 1 1/4 in | 4 7/8 in | 1/8 in | 1,500 lb | 1 | 6211 24V US32D CON | **4WY69** | * |
| Heavy-Duty | Fail Secure | 12 V AC/DC | Aluminum/Hollow Metal/Wood | 1 1/4 in | 4 7/8 in | 1/8 in | 1,500 lb | 1 | 6211 12V US32D CON | **4WY70** | * |
| Heavy-Duty | Fail Secure | 24 V AC/DC | Aluminum/Hollow Metal/Wood | 1 3/8 in | 9 in | 3/16 in | 1,500 lb | 1 | 6215 24V US32D CON | **4WY71** | * |
| **Rim Type Exit Devices** | | | | | | | | | | | |
| Heavy-Duty | Fail Secure | 24 V AC/DC | Aluminum/Hollow Metal/Wood | 1 5/8 in | 9 in | 3/4 in | 1,500 lb | 1 | 6112 24V US32D CON | **4WY67** | * |
| Heavy-Duty | Fail Secure | 12 V AC/DC | Aluminum/Hollow Metal/Wood | 1 5/8 in | 9 in | 3/4 in | 1,500 lb | 1 | 6112 12V US32D CON | **4WY68** | * |

**** Fire-rated, stainless steel, and UL 1030 burglary-resistant. † Stainless steel and burglary-resistant.***

Adams Rite ASSA ABLOY

# Narrow-Stile Electric Strikes, Grade 1

- 1500-lb. holding force
- ½" bolt throw
- Case size: 1" x 3⅜" x 1⅝"D
- Strike opening: ⅝" x 1 7/16" x ½"D

Fail-secure strikes fit in frames for aluminum or wood doors in storefronts and other commercial and retail applications. Strikes exceed 500,000 cycles and 70 ft.-lb. dynamic force. Series 7130 strikes are for use when converting from an Adams Rite MS pivoted-bolt deadlock to a deadlatch.

| Finish | Faceplate Height | Input Voltage | Mfr. Model | Item No. |
|---|---|---|---|---|
| **For Aluminum Doors** | | | | |
| Satin Aluminum | 4 7/8 in | 24 V AC/DC | 7100-540-628-00 | **2EUT8** |
| Dark Bronze | 4 7/8 in | 24 V AC/DC | 7100-540-313-00 | **2EUT9** |
| Satin Aluminum | 4 7/8 in | 24 V AC/DC | 7100-510-628-00 | **2EUU1** |
| Dark Bronze | 4 7/8 in | 24 V AC/DC | 7100-510-313-00 | **2EUU2** |
| Satin Aluminum | 6 7/8 in | 24 V AC/DC | 7130-540-628-00 | **2EUU7** |
| Dark Bronze | 6 7/8 in | 24 V AC/DC | 7130-540-313-00 | **2EUU8** |
| Satin Aluminum | 6 7/8 in | 24 V AC/DC | 7130-510-628-00 | **2EUU9** |
| Dark Bronze | 6 7/8 in | 24 V AC/DC | 7130-510-313-00 | **2EUV1** |
| Clear Anodized | 4 7/8 in | 12/24 V AC/DC | 7400 X 628 | **20UM66** |
| **For Wood/Hollow Metal Doors** | | | | |
| Satin Aluminum | 4 7/8 in | 24 V AC/DC | 7140-540-628-00 | **2EUU3** |
| Dark Bronze | 4 7/8 in | 12/24 V AC/DC | 7140-540-313-00 | **2EUU4** |
| Satin Aluminum | 4 7/8 in | 24 V AC/DC | 7140-510-628-00 | **2EUU5** |
| Dark Bronze | 4 7/8 in | 24 V AC/DC | 7140-510-313-00 | **2EUU6** |

2EUT8

2EUU8