

Digital Single Gang Keypad



- 99 user code

Designed for releasing any electric lock. Use in low- to medium-security applications. Features stainless steel plate with plastic backbox. Red/green/yellow LEDs function as indicators and programming prompts. Indoor use.

Description	Voltage	W	H	Mfr. Model	Item No.
12 Button Illuminated Digital Access Keypad, Single Gang	30 VDC or 300 VAC Switched Voltage	2 3/4 in	4 1/2 in	DK-12	10A459



Digital Keypad Systems



- 59 user code
- Weather-resistant; operating temp. of -22° to 158°F

Vandal-resistant, 2-pc. system is designed to control electric locks. Feature narrow-stile cast stainless steel 10-digit keypad and remotely mounted CPU board. Include 3 LEDs and bell button.

Description	Voltage	W	H	Mfr. Model	Item No.
Access Control Keypad	12 or 24 AC/DC	1 1/2 in	7 in	DK-26SS	5KZT7
Wiegand Output Access Control Keypad	12 or 24 AC/DC	1 1/2 in	7 in	DK37WSS	5KZT8



5KZT7

Enclosures for Keypads, Buttons, and Light Switches



Multipurpose Keypad and Push-Button Enclosures—

Polycarbonate enclosures protect against weather, vandalism, and theft. 3FVR4 is smoke-colored to help guard against password theft.

Flip-Up Polycarbonate Protectors—Rugged enclosures help protect keypads and push-button locksets from weather, vandalism, and theft. Easy to install.

Indoor/Outdoor Covers—Polycarbonate; include gaskets and mounting hardware. Large interior space protects dual-action pull stations, keypads, intercoms, push buttons, electrical switches, and duplex plugs.

Description	H	W	D	Color	Std.	Mfr. Model	Item No.
Multipurpose Keypad and Push Button Enclosures							
Protective Cabinet	14 1/2 in	12 1/2 in	6 1/2 in	Clear	cUL, UL	STI-7530	3FVR1
NEMA 4X Protective Cabinet	10 1/8 in	8 7/8 in	3 3/8 in	Clear	cUL, UL	STI-7520	3FVR9
Protective Cover	6 3/4 in	8 3/4 in	5 in	Smoke	cUL, UL	STI-7505	3FVR4
Without Alarm	4 1/32 in	3 3/32 in	1 5/32 in	Clear	—	STI-6519	45YP74
Flip-Up Polycarbonate Protectors							
Universal Stopper Cover	4 3/4 in	8 1/4 in	1 5/64 in	Clear	UL, cUL, ADA	STI-7700	54JF51
Protective Cover For Biometrics	3 in	3 1/2 in	2 11/16 in	Clear	cUL, UL	STI-6514	3FVR2
Protective Cover For Keypads	3 1/4 in	3 3/8 in	2 in	Clear	UL cUL ADA	STI-6516	3FVR3
Indoor/Outdoor Pull Station Covers							
Without Alarm	8 3/2 in	5 1/16 in	2 21/32 in	Clear	cUL, UL	STI-13000NC	5AFX7
Without Alarm, Universal Stopper	6 in	4 7/8 in	3 11/64 in	Clear/Red/Gray	UL S2466, ADA	STI-14200NR-2003	45YP77
Without Alarm, Fire Label	8 3/2 in	5 1/16 in	2 21/32 in	Red	cUL, UL	STI-13010FR	5AFX8
Without Alarm	10 13/64 in	7 13/64 in	5 1/2 in	Clear	cUL, UL	STI-3150	2KFK3
Without Alarm	8 3/2 in	5 1/16 in	4 in	Clear	cUL, UL	STI-13200NC	5AFY4
Wire Cage	7 1/2 in	6 1/2 in	3 1/2 in	White	UL and cUL	STI-9705	16DB41
Indoor Pull Station Covers							
Without Alarm	8 7/8 in	6 13/16 in	3 3/4 in	Red/Clear	UL, cUL, ADA	STI-1200	10PD6
With Alarm	8 7/8 in	6 13/16 in	3 3/4 in	Red/Clear	UL, cUL, ADA, FM, NY to BSA	STI-1100	10PD7
With Alarm	8 7/8 in	6 13/16 in	5 3/4 in	Clear	cUL, UL	STI-1130	2KFK3
Without Alarm	8 7/8 in	6 13/16 in	5 3/4 in	Clear	cUL, UL	STI-1230	2KFK4
Indoor/Outdoor Covers							
Enclosed Backbox	8 3/2 in	5 1/16 in	4 in	Clear/Black	cUL, UL	STI-13400NK	5AFY5



Protective Cabinet 3FVR1



Indoor/Outdoor Pull Station Cover w/ out Alarm 5AFY4

Plug-in Power Supplies



Ideal for powering a wide range of DC devices. Wall-mounted. Include internal thermal fuse and 16-ft. output cable.

Description	Input Voltage	Output Current (Amps)	Mfr. Model	Item No.
12V DC Plug-In Power Supply	120	700mA	PSP-12	5KZX8
24V DC Plug-In Power Supply	120	350mA	PSP-24	5KZX9



5KZX8

Linear Power Supplies



Allow for wire runs without the use of conduit from power supply to door. Use with voltage-sensitive safety and security components, including card readers, motion sensors, and DC cameras. Also recommended for where an interface with a fire alarm system or battery backup (internal charging) is needed. Use with sealed lead-acid batteries (not included).

Description	Input Voltage	Voltage Output	No. of Outputs	Encl. Width (in.)	Encl. Height (in.)	Encl. Depth (in.)	Mfr. Model	Item No.
Dual Voltage Boxed Power Supply	120V AC	12 or 24V DC	1	9 in	12 in	4 in	BPS-12/24-1	5KZX3
12V Boxed Power Supply	120V AC	12V DC	4	14 in	14 in	4 in	BPS-12-45	5KZX4
24V Boxed Power Supply	120V AC	24V DC	4	14 in	14 in	4 in	BPS-24-3	5KZX6
24V Boxed Power Supply	120V AC	24V DC	8	15 in	18 in	6 in	BPS-24-6	5KZX7



5KZX3