



Norton
ASSA ABLOY



Powered Door Operators

- Nonhanded
 - Acceptable for fire and smoke barrier doors
- Low-energy operators function as standard spring-force closers during close cycles, when door is opened manually, or if power is lost or turned off. Hold-open time is adjustable from 0 to 30 sec. If door is obstructed, motor stops and the door closes with standard closer. Include 2 radio-frequency wall

switches powered by 9V batteries, 6" x 6" face plates with Americans with Disabilities (ADA) logo, and built-in 1.1A power supply. Connect to wall outlet. Rated 120VAC, 60 Hz. Ideal for doctors' offices, retirement facilities, schools, churches, and other applications where noise may be a concern.

Arm Type	Housing Length	Housing Width	Housing Height	Max. Door Opening	ALUMINUM PAINTED Item No.	DARK BRONZE PAINTED Item No.	BLACK PAINTED Item No.
Heavy-Duty, 5700 Series							
Hinge (Pull) Side - Includes Radio Frequency Wall Switches	29 in	4 5/8"	5 1/4 in	180°	5EU12	4AVD2	—
Slide Track, Stop (Push) Side - Includes Radio Frequency Wall Switches	29 in	4 5/8"	5 1/4 in	180°	5EU13	—	—
Double Lever - Includes Radio Frequency Wall Switches	29 in	4 9/8"	5 1/4 in	180°	—	4AVD3	—
Heavy-Duty, 5800 Series							
Parallel, Regular - Includes Door Opening Solution, Narrow Stile Push Plates	8 in	2 1/2"	9 in	95°	—	—	48ZD73
Parallel, Regular - Includes 3 in Square Push Plates, Door Opening Solution	8 in	2 1/2"	9 in	95°	—	—	48ZD74



Door Closers

Rack and pinion closers have a lightweight aluminum alloy body. Feature adjustments for closing, sweep, latch, speed, and backcheck. Closers have a standard arm, which is suitable for doors with low exposure to wind and abuse. For regular, top jamb, and parallel arm installation.

Heavy-Duty, 2700 Series—Features larger closer body and spring. Adjust for door sizes 1 to 6 (Grade 1).

Standard-Duty, 1100 Series—Medium-size body and spring for effective door control. Adjust to door sizes 1 to 4 (Grade 1) or fixed at door size.

Standard, Standard Delayed-Action, and Extra Heavy-Duty 5800 Series—Extra Heavy-Duty feature cast iron construction that increases body life and reduces leakage. Adjustable backcheck, closing speed and latching speed. Tri-style packed regular and parallel arm and top jamb mounting.



Description	Housing Length	Housing Width	Housing Height	► CHOOSE: Color	Max. Door Opening	NONHANDLED Item No.	NONHANDLED, HOLD-OPEN Item No.
Heavy-Duty, Full Cover, 2700 Series							
Standard, Sizes 1 to 6	13 in	2 3/4"	2 1/2 in	Aluminum, Dark Bronze	180°	D8978	—
Standard-Duty, 1100 Series							
Standard, Sizes 1 to 4	9 1/8 in	2 5/8"	1 1/8 in	Aluminum, Dark Bronze	180°	D8972	D8974
Standard, Sizes 1 to 4	9 1/8 in	2 5/8"	1 1/8 in	Aluminum	180°	D8973	—
Standard, Sizes 1 to 4	9 3/4 in	2 5/8"	1 3/4 in	Dark Bronze	180°	D8973	—
Standard-Duty, 5800 Series							
Adjustable, Sizes 1 to 6	12 1/4 in	2 1/4"	3 1/2 in	Aluminum, Dark Bronze	85° to 130°	G6741	—
Adjustable, Sizes 1 to 6	12 1/4 in	2 1/4"	3 1/2 in	—	—	—	G6742
Standard-Duty Delayed Action, 5800 Series							
Adjustable, Sizes 1 to 6	12 1/4 in	2 1/4"	3 1/2 in	Aluminum	130°	—	48GG10
Adjustable, Sizes 1 to 6	12 1/4 in	2 1/4"	3 1/2 in	Dark Bronze	130°	—	48GG11
Extra Heavy-Duty, 5800 Series							
Adjustable, Sizes 1 to 6	12 1/4 in	2 1/4"	3 1/2 in	Aluminum, Dark Bronze	—	G6745	G6746



2WHF8 (shown with optional cover 2WHL8)



5PHG9

STANLEY

Hydraulic Door Closers

Fully adjustable from 1 to 6. Feature delayed action and back check. Include wood and machine screws, sex nuts, and self-tapping screws. Aluminum finish.

Standard-Duty—For interior doors to 4 1/2-ft. wide and exterior doors to 4-ft wide. Door closer cover not included, order 2WHL8 separately.

- Cast aluminum

Heavy-Duty and Extra Heavy-Duty—Plastic cover included. Door closers have all-weather fluid for optimal performance in harsh climates.

- Cast iron

Description	Housing Height	Housing Width	Housing Length	Mfr. Model	Item No.
Standard-Duty					
Non Hold-Open Arm, Tri-Packed, Grade 1	2 5/8 in	3 3/8"	9 1 3/16 in	QDC311NC689	2WHF9
Hold-Open Arm, Grade 1	2 5/8 in	3 3/8"	9 1 3/16 in	QDC312NC689	2WHG2
Dead-Stop Cushion Non Hold-Open Arm, Grade 1	2 5/8 in	3 3/8"	9 1 3/16 in	QDC313NC689	2WHG6
Dead-Stop Cushion Hold-Open Arm, Grade 1	2 5/8 in	3 3/8"	9 1 3/16 in	QDC314NC689	2WHG5
Heavy-Duty					
Non Hold-Open Arm, Tri-Packed, Grade 1	2 1/8 in	3 3/8"	12 in	QDC211F689	2WHF8
Hold-Open Arm, Grade 1	2 1/8 in	3 3/8"	12 in	QDC212F689	2WHG1
Dead-Stop Cushion Non Hold-Open Arm, Grade 1	2 1/8 in	3 3/8"	12 in	QDC213F689	2WHG4
Tri Pack, Non Hold Open, Parallel, Top Jamb and Regular, Adjustable 1 to 6	2 1/8 in	12"	12 in	QDC215S689	45CK42
Extra Duty Arm, Non Hold Open, Top Frame, Adjustable 1 to 6	3 1/2 in	12 3/8"	12 3/8 in	QDC115R689	45CK80
Extra Heavy-Duty					
Tri-Packed Arm, Big Body, Grade 1	3 1/2 in	2 1/4"	12 3/8 in	QDC111R689	5PHG9
Accessories					
Door Closer Cover	—	—	—	15918 CVR FULL	2WHL8
Door Closer Door Closer Sex Nuts	—	—	—	SZ QDC300 689	2WHL7
				15928 LPP SN 689	